LEGEND

| \$ | BENCH MARK | LP 🌣 | LIGHT POLE |
|---------------|-------------------------|-----------------|----------------|
| Θ | BOREHOLE | | - ELECTRIC |
| FH 📀 | EXISTING FIRE HYDRANT | PP- <u>O</u> - | POWER POLE |
| w | - EXISTING WATERLINE | | TREE |
| WМЩ | EXISTING WATER METER | * | TREE |
| WV 😝 | EXISTING WATER VALVE | Ö | BUSH |
| x | - FENCE LINE | 75 0 | TRAFFIC SIGN |
| GM 🖸 | GAS METER | MB 🗆 | MAIL BOX |
| GV 🖂 | GAS VALVE | TMH 💿 | TELEPHONE |
| GP O | GATE POST | OHT | - OVERHEAD T |
| —G— | - EXISTING GAS LINE | WWF | WELDED WIR |
| SGCI | SINGLE GRATE CURB INLET | SPO | STEEL POST |
| DGCI | DOUBLE GRATE CURB INLET | | UTILITY EASE |
| SSMH 🔘 | SANITARY SEWER M.H. | | - SUBDIVISION |
| SMH () | STORM SEWER M.H. | | - SUBDIVISION |
| TPED T | TELEPHONE PEDESTAL | | - SUBDIVISION |
| — <i>ss</i> — | - SANITARY SEWER | | - BUILDING LIN |
| —TUG— | - TELEPHONE UNDERGROUND | w | - PROPOSED W |
| — EUG — | - ELECTRIC UNDERGROUND | | - PROPOSED R |
| — <i>LC</i> — | -LOW CHORD | <u> </u> | - FLOODPLAIN |
| | | | |



BOUNDARY




THE CITY OF TULSA, OKLAHOMA FINAL PLANS FOR

ELM CREEK · WEST POND

SWD NO. 8845 PROJECT No. 148150 ACCOUNT NO. 6014-5451101-040522148150

DESIGN DATA SOUTH MADISON AVENUE, SOUTH NORFOLK AVENUE, SOUTH OWASSO AVENUE. EAST 5TH PLACE AND EAST 5TH STREET AADT 2018 = 3,900 AADT 2038 = 10,000 = 55% D = 5% T₃ (% AADT) = 30 MPH 20yr. FLEX ESALS = 2.3 M




UTILITY CONTACTS

| UTILITY COMPANY | NUMBER |
|--|--------------|
| AEP/PSO – LONNY HICKS | 918-250-6211 |
| AT&T – KEVIN WINGARD | 580-931-7688 |
| AT&T DISTRIBUTION - ALFORD NICHOLS JR. | 918-596-4237 |
| CENTURYLINK – MIKE SMITH | 405-853-7164 |
| CITY OF TULSA (SEWER) – AARON JOHNSON | 918-596-9564 |
| CITY OF TULSA (STORM) – BRAD JACKSON | 918-596-9569 |
| CITY OF TULSA (TRAFFIC) – RUSSELL BAUSCH | 918-591-4292 |
| CITY OF TULSA (WATER) – RYAN MCKASKLE | 918-596-9566 |
| COX COMMUNICATIONS - GARY HAMILTON | 918-286-4666 |
| ONG – STEVE BOLIN | 918-831-8389 |
| VYVE – MARCUS WRIGHT | 405-395-1100 |

CURRENT CITY OF TULSA STANDARD SPECIFICATIONS AND STANDARD DETAILS GOVERN. ALL OTHER CONSTRUCTION AND MATERIALS SHALL BE IN ACCORDANCE WITH THE 2009 OKLAHOMA STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION.

APPROVED BY:

ENTIRE PROJECT IS WITHIN CORPORATE LIMITS OF THE CITY OF TULSA. THIS PROJECT COMPLIES WITH ALL OKLA. DEPT. OF ENV. QUALITY (ODEQ) REQUIREMENTS





PAUL ZACHARY, P.E. CITY ENGINEER

DATE

INDEX_OF_SHEETS

INDEX OF SHEETS

| <u>SHEET No.</u> | PAGE No. | PAGE TITLE | SHEET No. | PAGE No. | PAGE TITLE | | THE FOLLOWING CITY OF TULSA STAN WILL BE USED FOR THIS P | NDARD DRAWINGS ROJECT: |
|--|--|---|---------------------------------|--------------------------------------|---|-------------------------------------|--|---|
| 01 02 03 04 | G00 G01 G02 G03 | COVER SHEET INDEX OF SHEETS PAY QUANTITIES PAY ITEM NOTES | 78 79 80 | D01 D02 D03 | DEMOLITION PLAN SHEET NO. 1 OF 3 DEMOLITION PLAN SHEET NO. 2 OF 3 DEMOLITION PLAN SHEET NO. 3 OF 3 | 126 - 304 - | PROJECT SIGN STD SILT FENCE AND CONSTRUCTION ENTRA BEDDING DETAIL RIGID PIPE | NCE |
| 05 06 07 08 | G04 G05 G06 G07 | GENERAL CONSTRUCTION NOTES ROADWAY SUMMARY SHEET WATERLINE PAY QUANTITIES & NOTES WATERLINE SUMMARY & WASTEWATER PAY QUANTITIES & NOTES | 81 82 83 | C14 C15 C16 | TYPICAL SECTION SHEET NO. 1 OF 2 TYPICAL SECTION SHEET NO. 2 OF 2 DRIVEWAY DETAIL | 312 - 313 - 315 - | FIRE HYDRANT STD DETAIL FRAME & LID FOR WATER VAUL VALVE BOX THRUST BLOCKS AND TRENCH CONDITIONS | |
| 09 10 11 | R10 R11 R12 | RIGHT-OF-WAY MAP SURVEY DATA - ALIGNMENT DATA SHEETS SITE PLAN | 84 85 86 87 | C17 C18 C19 C20 | PLAN & PROFILE S. MADISON AVE. SHEET NO. 1 OF 3 PLAN & PROFILE S. MADISON AVE. SHEET NO. 2 OF 3 PLAN & PROFILE S. MADISON AVE. SHEET NO. 3 OF 3 PLAN & PROFILE S. NORFOLK AVE. & E. 5TH PLACE SHEET NO. 1 OF 2 | 505 - 601 - 602 - | METER SETTINGS FOR 5/8" X 3/4" AND 3, METER CAN WITH RIM AND LID PULL BOX INSTALLATION CONDUIT INSTALLATION SIGNAL POLE FOOTING DETAILS | 4 WATER SERVICE |
| 12 13 14 | C10 C11 C12 | GRADING PLAN OVER–ALL GRADING PLAN SHEET NO. 1 OF 3 GRADING PLAN SHEET NO. 2 OF 3 | 88 89 90 | C21 C22 C23 | PLAN & PROFILE S. NORFOLK AVE. & E. 5TH PLACE SHEET NO. 2 OF 2 PLAN & PROFILE S. OWASSO AVE. SHEET NO. 1 OF 2 PLAN & PROFILE S. OWASSO AVE. SHEET NO. 2 OF 2 | 606 - 607A - 607B - 608A - | EMERGENCY PRE-EMPTION DETAIL TRAFFIC SIGNAL SERVICE POLE AND SERVICE TRAFFIC SIGNAL PEDESTAL SERVICE STREET NAME SIGNS | E TO SIGNAL STANDARD |
| 15 16 17 18 | C13 L10 L11 L12 | GRADING PLAN SHEET NO. 3 OF 3 HARDSCAPE KEY PLAN HARDSCAPE LAYOUT PLAN-A HARDSCAPE LAYOUT PLAN-B | 91 92 93 94 95 | ST11 ST12 ST13 ST14 ST15 | STORMWATER MANAGEMENT PLAN DRAINAGE SHEETS DRAINAGE AREA MAP DRAINAGE SHEETS DRAINAGE DESIGN TABLE STORM SEWER OVER-ALL PLAN MISCELLANEOUS STORM SEWER PROFILES | 611A - 611B - 613 - | TRAFFIC SIGNS POLE WIRING DETAIL DOWNTOWN PEDESTAL WIRING DETAIL PEDESTAL AND MAST ARM POLE DETAIL TRAFFIC SIGNALS AND ACCESSORIES | |
| 19 20 21 22 23 | L13 L14 L15 L16 L17 | HARDSCAPE LAYOUT PLAN-C HARDSCAPE LAYOUT PLAN-D HARDSCAPE LAYOUT PLAN-E HARDSCAPE LAYOUT PLAN-F HARDSCAPE LAYOUT PLAN-G | 96 97 98 99 | W10 W11 W12 W13 | OVER-ALL PLAN WATERLINE SHEET NO. 1 OF 3 WATERLINE SHEET NO. 2 OF 3 WATERLINE SHEET NO. 3 OF 3 | 614B - 616 - 617A - 617B - | SIGNAL HEAD WIRNG MAST ARM BRACKETS SIGNAL POLES AND MAST ARMS SINGLE MAST ARM DETAILS BONDING DIAGRAM | |
| 24 25 26 27 | L18 L19 L20 L21 | HARDSCAPE LAYOUT ENLARGEMENTS NOT USED SITE DETAILS-A SITE DETAILS-B | 100 101 102 103 | SS10 SS11 SS12 SS13 | SANITARY SEWER OVER-ALL PLAN SANITARY SEWER PLANS SHEET NO. 1 OF 3 SANITARY SEWER PLANS SHEET NO. 2 OF 3 SANITARY SEWER PLANS SHEET NO. 3 OF 3 | 625 - 727 - 729 - 731 - | REMOVAL OF TRAFFIC ITEMS CONCRETE PAVEMENT STD DETAILS FOR RES CONCRETE PAVEMENT STD DETAILS FOR RES STD CONCRETE PAVEMENT CUT & REPAIR STD PIPE BEDDING DETAIL FOR STORM SEWE | IDENTIAL & COLLECTOR STREETS (2 OF 2) |
| 28 29 30 31 | L22 L23 L24 L30 | SITE DETAILS-C SITE FURNISHINGS DETAILS AERATING FOUNTAIN DETAILS LANDSCAPE PLAN KEY MAP | 104 105 106 107 | C24 C25 C26 C27 | EROSION CONTROL SHEET WALL PLAN & PROFILE SHEET NO. 1 OF 2 WALL PLAN & PROFILE SHEET NO. 2 OF 2 BLOCK WALL DETAILS SHEET NO. 1 OF 1 | 753 - 754 - 755 - | CONFIGURATIONS OF CAST IRON CURB INLET | I.D. STORMWATER MANHOLE AND JUNCTION BO |
| 32 33 34 35 36 | L31 L32 L33 L34 | LANDSCAPE SCHEDULE & NOTES LANDSCAPE DETAILS LANDSCAPE PLAN-AREA A LANDSCAPE PLAN-AREA B | 108 109 110 | C28 TS1 TS2 | PAVEMENT MARKING AND SIGNING PLAN TRASHTROOPER FLOATABLES INTERCEPTOR MODEL TTB-10X10-33 TRASHTROOPER DESIGN ASSUMPTIONS HYDRAULIC IMPACT ANALYSIS AND MAINTENANCE | 765 - 766 - 767 - 770 - | STD REINFORCED CONCRETE STORMWATER IN STD STORMWATER FRAMES STD STORMWATER GRATES STD CAST IRON CURB STANDARD DROP INLET 15", 18", 24" | |
| 36 37 38 39 | L35 L36 L37 L38 | LANDSCAPE PLAN-AREA C LANDSCAPE PLAN-AREA D LANDSCAPE PLAN-AREA E IRRIGATION DETAILS | 111 112 113 114 | TS3 X01 X02 X03 | TRASHTROOPER OPERATION AND MAINTENANCE PLAN CROSS SECTIONS – S. MADISON AVE. STA. 10+50 TO STA. 12+00 CROSS SECTIONS – S. MADISON AVE. STA. 12+50 TO STA. 14+00 CROSS SECTIONS – S. MADISON AVE. STA. 14+50 TO STA. 16+00 | 776 - | STD PRECAST CONCRETE STORMWATER MANH STANDARD PIPE HEADWALLS 15" TO 42" STD SIDEWALK RAMP | IOLE |
| 40 41 42 43 44 | L39 L40 L41 L42 L43 | IRRIGATION PLAN-AREA A IRRIGATION PLAN-AREA B IRRIGATION PLAN-AREA C IRRIGATION PLAN-AREA D IRRIGATION PLAN-AREA D | 115 116 117 118 119 | X04 X05 X06 X07 X08 | CROSS SECTIONS - S. MADISON AVE. STA. 16+50 TO STA. 18+50 CROSS SECTIONS - S. MADISON AVE. STA. 19+00 TO STA. 20+58.71 CROSS SECTIONS - NORFOLK & 5TH PLACE STA. 30+50 TO STA. 31+86.19 CROSS SECTIONS - NORFOLK & 5TH PLACE STA. 32+50 TO STA. 34+00 CROSS SECTIONS - NORFOLK & 5TH PLACE STA. 34+50 TO STA. 36+00 | CET4 | THE FOLLOWING ODOT : WILL BE USED FOR 5-3-2 RCB-C1-3&4&5(2-20) SMD-3-0 | THIS PROJECT: TCS1-1-01 TCS5-1-00 TCS9-1-01 |
| 45 46 47 48 | E01 E02 E03 E04 E05 | EXISTING ELECTRICAL 1 EXISTING ELECTRICAL 2 SITE PLAN 1 SITE PLAN 2 SITE PLAN 3 | 120 121 122 123 | X09 X10 X11 X12 | CROSS SECTIONS - NORFOLK & 5TH PLACE STA. 36+50 TO STA. 38+00 CROSS SECTIONS - S. OWASSO AVE. STA. 40+50 TO STA. 42+50 CROSS SECTIONS - S. OWASSO AVE. STA. 43+00 TO STA. 45+00 CROSS SECTIONS - S. OWASSO AVE. STA. 45+50 TO STA. 47+10.15 | SCES | -3-0 RWF-3-2 TFL-1-0 GPI-4-0 LTU-4-0 | TCS2-1-00 TCS6-1-02 TCS14-1-00 TCS4-1-01 TCS7-1-02 TCS24-1-02 |
| 49 50 51 52 53 54 55 55 56 57 | E06 E07 E08 E09 E10 E11 E12 E13 | SITE PLAN 3 SITE PLAN 4 SITE PLAN 5 LIGHTING CONTROLLER SCHEMATIC 1 LIGHTING CONTROLLER SCHEMATIC 2 AERATOR CONTROLLER SCHEMATIC POND ELECTRICAL DETAILS 1 POND ELECTRICAL DETAILS 2 LIGHTING AND MOUNTING DETAIL | | | SURVI | TY D | ΔΤΔ | |
| 58 59 60 61 | E14 E15 E16 E17 | PHOTOMETRIC READING 1 PHOTOMETRIC READING 2 PHOTOMETRIC READING 3 PHOTOMETRIC READING 4 | | | BENCHMARK LOCATION: ADS BENCHMARK - #60 - 3" | BRASS | HORIZONTAL DATUM: OKLAHOMA NORTH (ZONE 3501) | |
| 62 | E18 | PHOTOMETRIC READING 5 | | | CAP-FLUSH-SET APPROXIMATEL) SOUTH OF THE INTERSECTION O AND S. UTICA AVE., IN LEFT TU | F 21ST ST | STATE PLANE COORDINATE SYSTEM, NAD 1983 (1993) | ELM CREEK WEST POND PROJECT No. 148150 |
| 63 64 65 | S01 S02 S03 | GENERAL NOTES RETAINING WALL LOCATIONS GENERAL PLAN AND ELEVATIONS WALL A-1 | | | OF NORTHBOUND TRAFFIC. N=418593.311 | | VERTICAL DATUM: NAVD 1988 | FROJECT NO. 148150 |
| 66 67 68 69 | S04 S05 S06 S07 | GENERAL PLAN AND ELEVATIONS WALL A-2 GENERAL PLAN AND ELEVATIONS WALL B-1 GENERAL PLAN AND ELEVATIONS WALLS B-2, B-3 AND B-4 GENERAL PLAN AND ELEVATIONS WALL C-1 | | | E=2568765.684 ELEV. = 745.11 | | <u>SCALE_FACTOR:</u> N/A | INDEX OF SHEETS |
| 70 71 72 | S08 S09 S10 | GENERAL PLAN AND ELEVATIONS WALLS C-2 AND C-3 GENERAL PLAN AND ELEVATIONS WALL D-1 GENERAL PLAN AND ELEVATIONS WALL D-2 | | | | | | ENGINEERING SERVICES DEPARTMENT |
| 73 74 | S11 S12 | GENERAL PLAN AND ELEVATIONS WALL E GENERAL PLAN AND ELEVATIONS WALLS F AND G | | | | | REVISION BY DATE | GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 918.437.0282 / WWW.GUYENGR PLAN SCALE: DRAWN DGD 01/19 APPROVED: |
| 75 76 77 | S13 S14 S15 | GENERAL PLAN AND ELEVATIONS WALL H TYPICAL SECTIONS RETAINING WALL DETAILS | | | | | | N/A DESIGNED MZV 01/19 SURVEY DMM 09/18 PROFILE SCALE PRO L MCR |



| JNIAL DATUM: | | | | | | | | |
|--|---------------|-----------------------|-------|-------|------------|-----|----|------|
| MA NORTH (ZONE 3501) PLANE COORDINATE | EL | ELM CREEK WEST POND | | | | | | |
| , NAD 1983 (1993) A L DATUM: | | PROJ | ECT | ΓNο | . 14815 | 0 | | |
| P88 FACTOR: | | INDI | EX (| DF SH | HEETS | | | |
| | | TY OF T ENGINEERIN | | | | | | |
| | | OUY ENGIN | | | | | | .COM |
| REVISION BY DAT | PLAN SCALE | DRAWN | DGD | 01/19 | APPROVED | : | | |
| | N/A | DESIGNED | MZV | | | | | |
| | | SURVEY | DMM | 09/18 | | | | |
| | PROFILE SCALE | PROJ. MGR. | | | | | | |
| | HORIZONTAL: | LEAD ENGR. | | | | | | |
| | N/A | FIELD MGR. | | | | | | |
| | VERTICAL | RECOMMENT | DED: | | | | | |
| | N/A | DESIGN MAN | IAGER | 2 | CITY ENGIN | EER | | _ |
| | | | | | DATE: | | | |
| | FILE: | DRAWI | NG: | | PAGE NO. | | | G01 |
| | ATLAS PAGE | NO: 01 & 08 | | | SHEET NO. | 02 | OF | 123 |
| | | | | | | | | |

| NO | SPEC. NO | DESCRIPTION | UNIT | TOTAL QUANTITY | |
|----------|------------------|---|----------------------|-------------------|---------|
| 1 | 201(A) | I CLEARING & GRUBBING | 1,48 | AC | 15.9 |
| 2 | 202(A) | UNCLASSIFIED EXCAVATION | 2,10,40,60 | CY | 199,319 |
| 3 | 205(A) | TYPEA - SALVAGED TOPSOIL | 107 | CY | 1,304 |
| 4 | 220 | SWPPP DOCUMENTATION AND MANAGEMENT | 64 | EA | 1 |
| 5 | 221(C) | TEMPORARY SILT FENCE | 12 | LF | 2,949 |
| 6 | 221(D) | TEMPORARY SEDIMENT FILTER | 12,61,62 | EA | 5 |
| 7 | 221(K) | TEMPORARY FIBER LOG | 12 | LF | 414 |
| 8 | 230(A) | SOLID SLAB SODDING | 13,14,15 | SY | 1,476 |
| 9 | 303(A) | A GGREGATE BASE TYPE A | 2,3,4 | CY | 4,527 |
| 10 | 310(B) | SUBGRADE, METHOD B | 2 | SY | 13,581 |
| 11 | 325 | SEPARATOR FABRIC | 2,5 | SY | 15,365 |
| 12 | 411(B) | SUPERPAVE, TYPE S3 (PG 64-22 OK) | 16,17,50 | TON | 2,553 |
| 13 | 411(C) | SUPERPAVE, TYPE S4 (PG 64-22 OK) (INSOLUBLE) | 16,17,50 | TON | 1.247 |
| 14 | 509(A) | CLASS AA CONCRETE | 20,108 | CY | 408 |
| 15 | 510(A) | RETAINING WALL - (SEGMENTAL BLOCK) | 43 | SY | 148 |
| 16 | 510(A) | RETAINING WALL - (CANTILEVER) | 101,102,103,104 | SY | 1,330 |
| 17 | 510(A) | RETAINING WALL - (DRILLED SHAFT) | 101,102,103,104 | SY | 6,356 |
| 18 | 510(A) 511(A) | RENFORCING STEEL | 109 | LB | 62,841 |
| 19 | 516(A) | DRILLED SHAFTS 36" DIAMETER | 105 | LF | 4,619 |
| 20 | 516(C) | CROSSHOLE SONIC LOGGING | 106 | EA | 4,019 |
| 21 | 609(B) | COMBINED CURB & GUTTER (6" BARRIER) | 20,22,23,24 | | 5.883 |
| 22 | 610(A) | 4" CONCRETE SIDEWALK | 20,23,25 | SY | 853 |
| 23 | 610(A) | 4" STA MPED CONCRETE SIDEWALK | 52 | SY | 91 |
| 24 | 610(A) | 6" CONCRETE DRIVEWAY (H.E.S.) | 20,23,24,25 | SY | 694 |
| 25 | 610(B) | TACTILE WARNING DEVICE | 20,20,24,20 | SF | 136 |
| 26 | 611(A) | 4' I.D. MANHOLE, COMPLETE IN PLACE | 26,28,34,44,57 | EA | 5 |
| 20 | 611(A) | | 26,28,34,44,57 | EA | 4 |
| 28 | 611(A) 611(A) | | | EA | 4 |
| 20 | | 6' I.D. MANHOLE, COMPLETE IN PLACE | 26,28,34,44,57 | EA | |
| 29 30 | 611(A) | | | | 5 |
| 30 | 611(B) | A DDITIONAL DEPTH IN 4' I.D. MANHOLE (STORM SEWER) | | VF | 7 |
| 32 | 611(B) | A DDITIONAL DEPTH IN 5' I.D. MANHOLE (STORM SEWER) | 44 | VF | 7 |
| 32 | 611(B) | ADDITIONAL DEPTH IN 8' I.D. MANHOLE (STORM SEWER) | 31,32,33,34,35,56 | VF | 17 |
| 34 | 611(G) | NLET, TY PE CICI DES. 2 (STD), COMPLETE N PLACE | | EA | 6 |
| 35 | 611(G) | NLET, TY PE CICI DES. 2 (B), COMPLETE N PLACE | 31,32,33,34,35,56 | EA | 4 |
| | 611(G) | NLET, TY PE CICI DES. 2 (D), COMPLETE N PLACE | 31,32,33,34,35,56 | EA | 3 |
| 36 | 611(G) | NLET, TY PE CICI DES. 3 (STD), COMPLETE N PLACE | 31,32,33,34,35,56 | EA | 3 |
| 37 | 611(G) | INLET WITH MANHOLE, TY PE CICI DES. 3 (STD), COMPLETE N PLACE | 26,31,32,33,34,35,56 | EA | 2 |
| 38 | 611(G) | INLET, TY PE CICI DES. 3 (B), COMPLETE N PLACE | 31,32,33,34,35,56 | EA | 1 |
| 39 | 611(G) | INLET WITH MANHOLE, TY PE CICI DES. 3 (B), COMPLETE N PLACE | 26,31,32,33,34,35,56 | EA | 2 |
| 40 | 611(G) | INLET WITH MANHOLE, TY PE CICI DES. 3 (D), COMPLETE N PLACE | 26,31,32,33,34,35,56 | EA | 3 |
| 41 | 611(H) | A DD'L DEPTH IN INLET CI DES. 3 | 35 | VF | 19 |
| 42 | 612(A) | MANHOLES ADJUST TO GRADE (PUBLIC) | 20,21,26,27,28 | EA | 8 |
| 43 | 619(A) | REMOVAL OF STRUCTURES & OBSTRUCTIONS | 10,21,51,53,65,66 | LSUM | 1 |
| 44 | 619(B) | | 10,21 | SY | 5,092 |
| 45 | 619(B) | | 10,21,65 | SY | 15,579 |
| 46 | 619(B) | | 10,21,65 | SY | 1,198 |
| 47 | 619(B) | | 10,21,65 | LF | 8,195 |
| 48 | 619(B) | | 10,21,27,63,65 | EA | 17 |
| 49 | 619(B) | | 10,21,63,65 | LF | 4,131 |
| 50 | 619(B) | REMOVAL OF EXISTING STORM MANHOLE | 10,21,27,63,65 | EA | 18 |
| 51 | 619(B) | REMOVAL OF SANITARY PIPE | 10,21,63,65 | LF | 3,526 |
| 52 | 619(B) | REMOVAL OF MANHOLE (SANITARY) | 10,21,27,63,65 | EA | 19 |
| 53 | 619(B) | REMOVAL OF WATERLINE PIPE | 10,21,63,65 | LF | 4,782 |
| 54 | 641 | MOBILIZATION | 58 | EA | 1 |
| 55 | 642 | CONSTRUCTION STAKING | 7,47 | EA | 1 |
| 56 | SPECIAL | TYPE 1 APC ARTERIAL PATCH | 9 | CY | 681 |
| 57 | SPECIAL | PIPE FENCE | | LF | 73 |
| 58 | SPECIAL | STONE V ENEER | | SY | 3,577 |
| 59 | SPECIAL | QUICK SET FLOWABLE FILL | 19,32 | CY | 10 |
| 60 | SPECIAL | URBAN RIGHT-OF-WAY RESTORATION | 11,14,29,41,42,48,59 | EA | 1 |
| 61 | SPECIAL | PROJECT SIGN (CITY OF TULSA) | 46 | EA | 2 |
| 62 | SPECIAL | HANDICA P RAMP | | EA | 17 |
| 63 | SPECIAL | OWNERALLOWANCE | | ALLOW | 1 |
| | SPECIAL | TRASH TREATMENT SY STEM (COMPLETE IN PLACE) | 1 | EA | 1 |

| item No | SPEC. NO | DESCRIPTION | PAY NOTES | UNIT | TOTAL QUANTITY | |
|------------|----------|---|-----------|-------|-------------------|--|
| 65 | SPECIAL | SHADE TREES | | EA | 174 | |
| 66 | SPECIAL | GROUNDCOVER PLANTINGS | | SF | 1,950 | |
| 67 | SPECIAL | LANDSCAPE PLANTINGS (SHRUBS AND ORN. GRASSES) | | SF | 5,250 | |
| 68 | SPECIAL | PLANTING SOIL MIX FOR LANDSCAPE AREAS | | CY | 780 | |
| 69 | SPECIAL | IMPORTED TOPSOIL (PLAZA PLANTERS - LAWN) | | CY | 545 | |
| 70 | SPECIAL | PEA GRAVEL MULCH (3" DEEP) FOR MID LEVEL PLANTER | | TON | 32 | |
| 71 | SPECIAL | BERMUDA SOD | | SY | 7,910 | |
| 72 | SPECIAL | SITE IRRIGATION SY STEM | | EA | 1 | |
| 73 | SPECIAL | SITE IRRIGATION METER, BFP, AND CONTROLLER | | EA | 1 | |
| 74 | SPECIAL | PARK A MENITIES / FURNISHING (6TH/ MA DISON A V E.) | | EA | 1 | |
| 78 | SPECIAL | A ERATION FOUNTAINS (3 HP) | | EA | 6 | |
| 79 | SPECIAL | CONTROLLER FOR A ERATION FOUNTAINS | | EA | 1 | |
| 80 | SPECIAL | DECORATIVE PEDESTRIAN PAVING (CONCRETE PAVERS) | SY | 4,665 | | |
| 81 | SPECIAL | CONCRETE EDGE RESTRAINT FOR PAVERS (6" WIDE) | LF | 2,370 | | |
| 82 | SPECIAL | CONCRETE RAMPS - 6" THICK | SY | 525 | | |
| 83 | 610(A) | CONCRETE SIDEWALKS - 4" THICK | | SY | 3,195 | |
| 84 | SPECIAL | PA VILION - 40' x 40' | | EA | 1 | |
| 85 | SPECIAL | PA VILION - 35' x 35' | | EA | 2 | |
| 86 | SPECIAL | 42" HT. ORNAMENTAL RAILING | | LF | 4,150 | |
| 87 | SPECIAL | STAIR HANDRAILS | | SF | 286 | |
| 88 | SPECIAL | BENCH (6 FT. LONG WITH BACK) | | EA | 35 | |
| 89 | SPECIAL | LITTER RECEPTACLE | | EA | 15 | |
| 90 | SPECIAL | BIKE RACK | | EA | 24 | |
| 91 | SPECIAL | 8' WIDE BOA RDWALK (ON PIERS) | | SF | 4,370 | |
| 92 | SPECIAL | PIER / OVERLOOKS (WITH STRUCTURE) | | SF | 11,400 | |
| 93 | SPECIAL | FISHING DOCK (EAST SIDE OF POND) | SF | 875 | | |
| 94 | SPECIAL | AUTOFILL WATER VALVE FOR POND | | EA | 1 | |
| 95 | SPECIAL | RAIN GARDENS (PARKING LOT ISLANDS) | | SF | 1,450 | |
| 96 | SPECIAL | SITE STAIRS (CONCRETE) | | SF | 1,075 | |
| 97 | SPECIAL | CONCRETE SEAT WALL (RAISED PLANTERS) | | LF | 770 | |

| ITEM NO | SPEC. NO | DESCRIPTION | PAY NOTES | UNIT | |
|------------|----------|---|-----------|-------|-------|
| 98 | SPECIAL | IDENTIFICATION OF EQUIPMENT LAY DOWN A REA, LOCAL SITE LOCATION | | LOT | 1 |
| 99 | 607 | ELECTRICAL SERVICE & METERING | | EA | 2 |
| | | SITE LIGHTING | | | |
| 100 | 610 | LIGHTING CONTROL PANELS | | EA | 3 |
| 101 | 800.2 | 12' POLE WITH LED LIGHT FIXTURE | | EA | 43 |
| 102 | 800.2 | OUTDOOR UNDER DECK LED LIGHT FIXTURE | | EA | 16 |
| 103 | 610 | CONCRETE POLE BASES | | EA | 43 |
| 104 | 602.1 | 3/4" RGS CONDUIT | | FT | 250 |
| 105 | 602.1 | 2" PV C CONDUIT/buried | FT | 3,330 | |
| 106 | 601.1 | IN GROUND JUNCTION BOXES | EA | 12 | |
| 107 | 611 | #12 THWN COPPER WIRE | FT | 3,000 | |
| 108 | 611 | #10 THWN COPPER WIRE | | | 6,000 |
| 109 | 611 | #8 THWN COPPER WIRE | FT | 500 | |
| 110 | 611 | #6 THWN COPPER WIRE | | FT | |
| 111 | 611 | #1 THWN COPPER WIRE | | FT | 1,500 |
| | | AERATORS | | | |
| 112 | SPECIAL | AND A SSOCIATED CONTROL EQUIP. INCLUDING 120V XFMR. | | EA | 2 |
| 113 | SPECIAL | AND (3) #12 120V CONTROL WIRES | | FT | 800 |
| 114 | 602.1 | 2" PV C CONDUIT | | FT | 600 |
| 115 | 601.1 | IN GROUND JUNCTION BOXES | | EA | 6 |
| 116 | 611 | #12 THWN COPPER WIRE | | FT | 1,500 |
| 117 | 611 | #10 THWN COPPER WIRE | | FT | 1,500 |
| 115 | 611 | #8 THWN COPPER WIRE | | FT | |
| 116 | 611 | #6 THWN COPPER WIRE | | FT | 1,000 |
| | | SHELTER ELECTRICAL | | | |
| 117 | SPECIAIL | 120V GFCI RECEPTA CLES AT SHELTERS | | EA. | 8 |

h

| item No | SPEC. NO | DESCRIPTION | PAYNOTES | UNIT | TOTAL QUANTITY | | | |
|------------|----------|--|-------------|------|-------------------|--|--|--|
| 130 | 613(A) | RCP 18" ROUND, COMPLETE IN PLACE | 30,32,45,54 | LF | 939 | | | |
| 131 | 613(A) | RCP 24" ROUND, COMPLETE IN PLACE | LF | 354 | | | | |
| 132 | 613(A) | CP 36" ROUND, COMPLETE IN PLACE 30,32,45,54 LF | | | | | | |
| 133 | 613(A) | RCP 42" ROUND, COMPLETE IN PLACE | 30,32,45,54 | LF | 185 | | | |
| 134 | 613(A) | RCP 48" ROUND, COMPLETE IN PLACE | 30,32,45,54 | LF | 384 | | | |

| STC | STORM WATER OPTION 2 | | | | | | | | | |
|------------|----------------------|--|----------|------|-------------------|--|--|--|--|--|
| ITEM NO | SPEC. NO | DESCRIPTION | PAYNOTES | UNIT | TOTAL QUANTITY | | | | | |
| 135 | 613(EE) | (SP) 18" CORRUGATED POLYPROPYLENE PIPE | 32,45,54 | LF | 939 | | | | | |
| 136 | 613(EE) | (SP) 24" CORRUGATED POLY PROPY LENE PIPE | 32,45,54 | LF | 354 | | | | | |
| 137 | 613(EE) | (SP) 36" CORRUGATED POLY PROPY LENE PIPE | 32,45,54 | LF | 200 | | | | | |
| 138 | 613(EE) | (SP) 42" CORRUGATED POLY PROPY LENE PIPE | 32,45,54 | LF | 185 | | | | | |
| 139 | 613(EE) | (SP) 48" CORRUGATED POLY PROPY LENE PIPE | 32,45,54 | LF | 384 | | | | | |

£



THIS DOCUMENT IS PRELIMINARY IN NATURE AND IS NOT A FINAL, SIGNED AND SEALED DOCUMENT

| NTITIES | | | | | | | | |
|----------------------------------|-----------|------|-------------------|--|--|--|--|--|
| DESCRIPTION | PAY NOTES | UNIT | total Quantity | | | | | |
| FIC STRIPE (PLASTIC)(4" WIDE) | 36 | LF | 5,980 | | | | | |
| FIC STRIPE (PLASTIC)(24" WIDE) | 36 | LF | 391 | | | | | |
| FIC STRIPE (PLASTIC) (SYMBOL) | 36 | EA | 2 | | | | | |
| TRUCTION SIGNS 0 TO 6.25 SF | 37 | SD | 1,456 | | | | | |
| STRUCTION SIGNS 6.26 TO 15.99 SF | 37 | SD | 4,456 | | | | | |
| TRUCTION SIGNS 16.00 TO 32.99 SF | 37 | SD | 3,020 | | | | | |
| RICADES (TYPE III) | 37 | SD | 14,448 | | | | | |
| NING LIGHTS (TYPEA) | 38 | SD | 16,832 | | | | | |
| INELIZER CONES | 37 | SD | 820 | | | | | |
| IND SIGN | | SF | 189 | | | | | |
| SIGN POST | | LF | 190 | | | | | |
| IN POST | | LF | 57 | | | | | |

| | ELM CREEK WEST POND | | | | | | | | | |
|----------|---------------------|--------|--------------------|--------------------------|------|-------|------------|-----|----|------|
| | | | PROJECT No. 148150 | | | | | | | |
| | | | | PA | Y QI | JANT | ITIES | | | |
| | | Y OF T | | | | | 1A | | | |
| | | | | UY ENGIN ST, TULSA OK | | | | | | .COM |
| REVISION | BY | DATE | PLAN SCALE: | DRAWN | DGD | 01/19 | APPROVED | : | | |
| | | | N/A | DESIGNED | MZV | 01/19 | | | | |
| | | | | SURVEY | DMM | 09/18 | | | | |
| | | | PROFILE SCALE: | PROJ. MGR. | | | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | | | |
| | | | N/A | FIELD MGR. | | | | | | |
| | | | VERTICAL | RECOMMEND | DED: | | | | | |
| | | | N/A | DESIGN MAN | AGER | | CITY ENGIN | EER | | - |
| | | | | | | | DATE: | | | |
| | | | FILE: | DRAWI | NG: | | PAGE NO. | | | G02 |
| | | | | | | | OUEEEE NO | 00 | | 123 |
| | | | ATLAS PAGE | NO: 01 & 08 | | | SHEET NO. | 03 | OF | 123 |

PAY ITEM NOTES (08/09/2017)

- ALL COSTS FOR REMOVING TREES, SHRUBS, STUMPS, POSTS, AND ALL OTHER DEBRIS AND/OR OBSTRUCTIONS NOT COVERED BY A SEPARATE PAY ITEM ARE INCLUDED IN THE PRICE BID.
- THIS QUANTITY INCLUDES AN ADDITIONAL 5% ABOVE PLAN QUANTITY FOR UNDERCUTTING OF UNSUITABLE SUBGRADE MATERIAL OR ADDITIONAL PATCHING AS DIRECTED BY THE ENGINEER
- TYPE A AGGREGATE BASE WAS ESTIMATED TO BE USED AS THE BASE MATERIAL FOR 90% OF THE PATCHING. QUICK SET FLOWABLE FILL WAS ESTIMATED TO BE USED AS THE BASE MATERIAL FOR 10% OF THE PATCHING. ACTUAL QUANTITIES TO BE DETERMINED BY THE ENGINEER.
- INCLUDES COMPACTION OF AGGREGATE TO 98% AASHTO T180 MODIFIED PROCTOR
- SEPARATOR FABRIC SHALL BE USED AT ALL PAVEMENT PATCHES AND RECONSTRUCTION SECTIONS. THE SEPARATOR FABRIC SHALL BE CUT AND OVERLAPPED A MINIMUM OF 2 FT AT ALL EDGES OF THE REPAIR.
- CONSTRUCTION STAKING SHALL INCLUDE SURVEYING AND THE FURNISHING, PLACING, AND MAINTAINING OF THE CONSTRUCTION LAYOUT STAKES NECESSARY FOR THE PROPER COMPLETION AND INSPECTION OF THE ENTIRE PROJECT
- NOT USED.
- THIS PAY ITEM INCLUDES THE FOLLOWING:
 - A. SAW CUTTING
 - B. REMOVAL OF THE EXISTING CONCRETE AND/OR ASPHALTIC CONCRETE ROADWAY (CY)
 - C. TYPE S3 ASPHALTIC CONCRETE OR PC CONCRETE COMPLETE AND IN PLACE PER DETAIL
 - D. SEALING OF EDGES AND TACK COAT
 - DOES NOT INCLUDE THE FOLLOWING:
 - A. UNCLASSIFIED EXCAVATION
 - B. SUBGRADE METHOD B (SY)
 - C. SEPARATOR FABRIC (SY)
 - D. AGGREGATE BASE (TYPE A)
 - E. ASPHALT CONCRETE LEVELING OR SURFACE COURSE
- WASTE MATERIAL TO BECOME THE PROPERTY OF THE CONTRACTOR AND SHALL BE REMOVED FROM THE SITE IN A MANNER APPROVED BY THE ENGINEER
- CONTRACTOR SHALL REPAIR ANY IRRIGATION SYSTEMS DAMAGED OR REQUIRING RELOCATION DURING THE CONSTRUCTION OF THIS PROJECT TO THE SATISFACTION OF THE PROPERTY OWNER AND CITY ARBORIST. COST SHALL BE NCLUDED IN THE PRICE BID
- EROSION PROTECTION SHALL BE PLACED AROUND DRAINAGE INLETS AS REQUIRED TO PREVENT ENTRANCE OF EROSION MATERIAL. EROSION PROTECTION SHALL BE PLACED AS NECESSARY TO PREVENT EROSION WASH TO ADJACENT PROPERTY. ALL EROSION PROTECTION INSTALLED MUST BE MAINTAINED BY THE CONTRACTOR FOR THE DURATION OF THE PROJECT EROSION PROTECTION SHALL BE REMOVED AT THE END OF THE PROJECT AS DIRECTED BY THE ENGINEER, COST TO BE INCLUDED IN THE PRICE BID. THE PRICE INCLUDES THE COST OF SEDIMENT REMOVAL PER THE STORMWATER MANAGEMENT ΡΙ ΔΝ
- THE PAY ITEM FOR SOLID SLAB SODDING INCLUDES QUANTITIES FOR PLACEMENT AND COMPACTION OF SUITABLE BACKELL 13 AND SOD AT EXISTING GRASS AREAS WHICH MAY BE DAMAGED DURING CONSTRUCTION OF CURBS, SIDEWALKS, DRIVEWAYS, AND OTHER MISCELLANEOUS ITEMS. THE QUANTITIES ARE BASED ON UTILIZING A 3 FOOT WIDE STRIP IN THESE AREAS, THE SOD SHALL BE OF LIKE KIND TO THE EXISTING SOD, THE CONTRACTOR WILL BE RESPONSIBLE FOR THE REPAIR OR REPLACEMENT OF DAMAGE TO EXISTING GRASS THAT EXCEEDS THESE LIMITS.
- PAY ITEM INCLUDES ALL MOWING WITHIN THE RIGHT-OF-WAY AS DIRECTED DURING CONSTRUCTION
- COST OF WATERING AND FERTILIZING SHALL BE INCLUDED. FERTILIZERS SHALL BE 10-20-10 AND SHALL BE APPLIED AT THE 15 RATE OF 1.5 LBS PER 10 SQ YDS. FERTILIZER SHALL BE APPLIED PER SECTION 230.04H OF ODOT STANDARD SPECIFICATIONS. WATERING SHALL BE APPLIED AS NECESSARY UNTIL VEGETATION IS ESTABLISHED OR UNTIL THE WORK IS ACCEPTED AS COMPLETE
- THE COST OF TACK COAT, EDGE JOINT SEAL MATERIAL AND SCREENINGS FOR BLOTTING, AND ALL LABOR ASSOCIATED WITH THESE ITEMS. SHALL BE INCLUDED IN ASPHALT CONCRETE.
- 17. ESTIMATED AT 112 LBS PER SQ YD PER 1 INCH THICK
- NOT USED 18.

Μ

œ

- 19. LOCATIONS TO BE DETERMINED IN THE FIELD AND WORK TO BE PERFORMED AT THE DIRECTION OF THE FIELD ENGINEER. QUANTITY IS ESTIMATED AND MAY BE OMITTED IN ITS ENTIRETY.
- THE USE OF FLY-ASH IN CONCRETE IS PROHIBITED
- ALL SAW CUTTING AND REMOVAL SHALL BE INCLUDED IN THE COST OF THE ITEM TO BE ADJUSTED, REMOVED, REPAIRED, 21. OR REPLACED.
- THIS ITEM SHALL BE MEASURED AS THE ACTUAL AMOUNT OF CURB AND/OR GUTTER INSTALLED. NO PAYMENT WILL BE MADE 22 FOR CURB AND/OR GUTTER THROUGH DRIVEWAYS AND INLETS.
- INCLUDES ALL COST OF SAWED JOINTS AND SEALING OF ALL JOINTS INCLUDING LONGITUDINAL JOINTS. 23.
- CURB, GUTTER, AND/OR SIDEWALK ASSOCIATED WITH THE DRIVEWAY AND THROUGH THE DRIVEWAY IS INCLUDED IN THE 24 COST OF THE DRIVEWAY
- ONE SIDEWALK PANEL ON EACH SIDE OF DRIVEWAYS SHALL BE A MINIMUM OF 6" THICK OR MATCH EXISTING DRIVEWAY 25 THICKNESS, WHICHEVER IS GREATER. NO ADDITIONAL PAYMENT SHALL BE MADE FOR THE COST OF THE THICKENED SIDEWALK THROUGH THIS AREA.
- THIS ITEM SHALL INCLUDE THE COST OF NEW MANHOLE FRAME AND COVER PER CITY OF TULSA STD NO.752, STD NO. 753, STD NO., 754 STD NO, 761 AND STD NO, 762.
- ALL SANITARY AND STORM SEWER MANHOLE CASTINGS AND LIDS THAT ARE LOCATED IN THE STREET AND ARE DISTURBED 27 BY THE CONTRACTOR SHALL BE REPLACED WITH NEW LIDS AND CASTINGS AND THE OLD ONES SHALL BE SALVAGED AND DELIVERED TO THE METAL RECYCLE BINS IN THE STOCKROOM AREA AT SEWER OPERATIONS AND MAINTENANCE, 9319 E. 42ND STREET NORTH, BETWEEN THE HOURS OF 7:30 AM AND 3:00 PM MONDAY THROUGH FRIDAY
- THE TOTAL COST FOR RUBBERIZED ASPHALT AND/OR SILICONE AT MANHOLES, VALVE BOXES, INLETS, AND INLET APRONS, SHALL BE INCLUDED.
- ALL HOUSE NUMBERS SHALL BE REPLACED/ REESTABLISHED THROUGHOUT PROJECT LIMITS. COST TO BE INCLUDED IN URBAN RIGHT OF WAY RESTORATION. CONTRACTOR SHALL REESTABLISH DRAINS, ROOF DRAINS AND OTHER DRAINAGE THROUGH THE CURBS IN ACCORDANCE WITH CITY OF TULSA STANDARD 758.
- REINFORCED CONCRETE PIPE TO BE CLASS III. ALL REINFORCED CONCRETE PIPE AND MANHOLES TO BE SUPPLIED WITH AN OMNI-FLEX JOINT GASKET OR APPROVED EQUAL. MASTIC JOINT SEALANT SHALL NOT BE ALLOWED.
- INCLUDES THE COST REQUIRED TO MAKE CONNECTION AND REMOVAL OF EXISTING INLETS. THE COST OF PC CONCRETE CURB AND GUTTER THROUGH THE INLET, 5' EACH SIDE OF THE INLET, AND THE PC CONCRETE INLET APRON SHALL BE INCLUDED, GRATE AND FLOWLINE ELEVATIONS SHALL MATCH EXISTING CONDITIONS UNLESS OTHERWISE NOTED IN THE PLANS

- 32. QUICK SET FLOWABLE FILL TO BE USED TO BACKFILL AROUND STREET CURB INLETS AND PIPES AS DIRECTED BY THE ENGINEER
- 33. ALL INLETS COMPLETE IN PLACE SHALL BE CAST IN PLACE CONCRETE OR PRECAST CONCRETE. NO BRICK INLETS SHALL BE ALLOWED. THIS PAY ITEM INCLUDES INLET FRAME, GRATE, HOOD AND CONCRETE
- 34. NO MASONRY STRUCTURES SHALL BE CONSTRUCTED WITHIN THE RIGHT OF WAY
- 35 ADDITIONAL DEPTH IN INLET SHALL BE MEASURED AND PAID FOR ALL INLETS EXCEEDING 3.71 VERTICAL FT, CALCULATED FROM THE CENTER ELEVATION OF THE LOWEST CAST IRON CURB TO THE FLOWLINE OF THE OUTLET PIPE.
- ALL PLASTIC PAVEMENT MARKINGS SHALL BE EITHER: 36.

EXTRUDED-APPLIED THERMOPLASTIC (USE ON ASPHALT PAVEMENT), THERMOPLASTIC PAVEMENT MARKINGS SHALL ONLY BE APPLIED WHEN THE SURFACE TEMPERATURE EXCEED 55°F FOR ALL OF THE SIX HOURS PRIOR TO INSTALLATION AND MAXIMUM WIND GUSTS ARE BELOW 15 MPH AT THE TIME OF APPLICATION. PRICE BID TO INCLUDE FLEX TABS OR LIKE KIND FOR POST CONSTRUCTION LANE MARKING/SEPARATION. MECHANICALLY APPLIED PREFORMED PLASTIC TAPE ("COLD TAPE") WILL NOT BE ACCEPTED.

0P

- MULTLEOLYMER PAINT (LISE ON CONCRETE PAVEMENT) MULTLEOLYMER PAVEMENT MARKINGS SHALL ONLY RE APPLIED 30 DAYS AFTER PAVING WHEN PAVEMENT SURFACE EXCEED 40°F FOR ALL OF THE SIX HOURS PRIOR TO INSTALLATION WITH A MINIMUM WIND CHILL TEMPERATURE OF 35°F. PRICE BID TO INCLUDE FLEX TABS OR LIKE KIND FOR POST CONSTRUCTION LANE MARKING/SEPARATION.
- REFLECTORIZED SHEETING ON SIGNS AND BARRICADES SHALL BE OF A CUBIC PRISMATIC TYPE AND SHALL MEET THE 37 SPECIFICATIONS ESTABLISHED FOR ASTM D 4956-01 TYPE IX RETROREFLECTIVE SHEETING, REFLECTORIZED SHEETING ON DRUMS AND TUBE CHANNELIZERS SHALL BE OF A HIGH-INTENSITY TYPE AND SHALL MEET THE SPECIFICATIONS ESTABLISHED FOR ASTM D 4956-01 TYPE III RETROREFLECTIVE SHEETING.
- 38. IF WARNING LIGHTS ARE TO BE USED ON TRAFFIC CONTROL DEVICES, TYPE "A" LIGHTS SHALL ONLY BE USED ON DEVICES WARNING OF UNEXPECTED HAZARDS, AND SHALL NOT BE USED FOR DELINEATION OF THE TRAVELED WAY, ONLY TYPE "C" WARNING LIGHTS SHALL BE USED FOR DELINEATION OF THE TRAVELED WAY, AND TYPE "C" LIGHTS SHALL NOT BE USED FOR ANY OTHER PURPOSE
- 39. NOT USED.
- THE CONTRACTOR SHALL BE PAID FOR UNCLASSIFIED EXCAVATION ON THE BASIS OF PLAN QUANTITY. ANY ADDITIONAL 40. EXCAVATION REQUIRED OR OVERRUN OF PLAN QUANTITY WILL BE PAID FOR ON THE BASIS OF UNIT PRICE BID FOR THE ITEM. CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING ADEQUATE SURVEY TO VERIFY ANY ADDITIONAL QUANTITIES.
- A CERTIFIED ARBORIST SHALL OVERSEE ALL PLANTINGS AND OR REMOVAL OF TREES. CONTACT CITY ARBORIST TO ACCEPT 41 FINAL PLANTINGS. CONTACT #: 918-596-2548
- TREE GRATES ARE NOT ACCEPTABLE PER CITY ARBORIST. CONCRETE PAVERS ARE TO BE USED AS NECESSARY AROUND 42. TREES
- UNIT PRICE SHALL INCLUDE COST OF ALL MATERIAL, LABOR, AND EQUIPMENT REQUIRED TO CONSTRUCT WALL PER 43. MANUFACTURER'S RECOMMENDATIONS.
- ADDITIONAL DEPTH IN A MANHOLE SHALL BE MEASURED FROM 6FT AS MEASURED FROM THE TOP OF RIM TO THE LOWEST 44. FLOWLINE.
- 45. THIS PAY ITEM SHALL BE COMPLETE IN PLACE AND SHALL INCLUDE ALL PIPE. STANDARD BEDDING MATERIAL AND TRENCH EXCAVATION, JOINT GASKETS AND ALL OTHER INCIDENTALS. NO ADDITIONAL COST WILL BE MADE
- PRICE BID FOR THIS ITEM SHALL BE PAYMENT IN FULL FOR THE INSTALLATION, MAINTENANCE AND SUBSEQUENT REMOVAL 46 OF ALL NECESSARY CONSTRUCTION TRAFFIC CONTROL REQUIRED FOR COMPLETION OF THE PROJECT
- THE COST TO REPLACE REMOVED OR DAMAGED SECTION CORNERS AND ALL OTHER PERMANENT RIGHT OF WAY MARKERS. 47. SHALL BE INCLUDED IN THE PRICE BID FOR THIS ITEM. NO ADDITIONAL PAYMENT WILL BE MADE
- ALL EXISTING DRAINAGE STRUCTURES SHALL BE CLEANED AND CLEARED OF ALL SEDIMENTATION AND DEBRIS TO THE 48 RIGHT OF WAY, COST OF CLEARING SHALL BE INCLUDED IN THE PRICE BID.
- 49. NOT USED
- 50. PG 70-28 OK OR PG 76-28 OK MAY BE DESIRABLE IN HIGH VOLUME AREAS WHERE SLOW, STANDING, OR TURNING TRAFFIC OCCURS, SUCH AS URBAN INTERSECTIONS OR OFF-RAMPS. OFF RAMPS SHOULD AT LEAST USE THE SAME BINDER AS THE MAINI INF

A HIGHER GRADE OF ASPHALT BINDER THAN INDICATED ON THE PLANS MAY BE USED, BUT AT NO ADDITIONAL COST TO THE DEPARTMENT.

| BINDER GRADE | MESALS | ADT | NOTES |
|--------------|--------|-----------|--|
| PG 64-22 OK | < 3 | < 5,000 | USE WHEN MORE THAN 4-6 INCHES BELOW THE SURFACE. ALSO USE FOR SHOULDERS, DRIVEWAYS, BELOW PCC, AND TEMPORARY CONSTRUCTION. |
| PG 70-28 OK | < 10 | < 10,000 | USE ONLY IN THE TOP 4-6 INCHES FOR DRIVING LANES. |
| PG 76-28 OK | >= 10 | >= 10,000 | USE ONLY IN THE TOP 4-6 INCHES FOR DRIVING LANES. |
| PG 76-28 E | - | | CONTACT ODOT MATERIALS DIVISION FOR RECOMMENDED USE. |

¹ USE ADT ONLY WHEN ESAL COMPUTATIONAL DATA IS NOT AVAILABLE. CALCULATE THE DESIGN ESALS BASED ON 20 YEARS.

- 51. PAY ITEM INCLUDES REMOVAL OF ALL STRUCTURES AND OBSTRUCTIONS WITHIN PROJECT LIMITS NOT SPECIFIED BY OTHER ITEMS OF WORK
- BOMANITE-BOMACRON, PATTERNED CONCRETE OR EQUAL, USE BRICK RUNNING BOND PATTERN, COLONIAL RED COLOR. 52. PAINTING OF STAMPED CONCRETE IS PROHIBITED
- 53. INCLUDES SAWING NOT INCLUDED IN OTHER ITEMS OF WORK
- STANDARD BEDDING MATERIAL TO BE TYPE A AGGREGATE BASE COMPACTED TO 95% STANDARD PROCTOR DENSITY. 54. AGGREGATE BASE IN THE ROADWAY SHALL BE 98% MODIFIED PROCTOR.
- 55.
- FOR INLET DESIGN NUMBERS AND CONFIGURATIONS REFER TO CITY OF TULSA STANDARD NO. 755. INLET DETAIL / LIST WILL 56. BE PROVIDED IN THE PLANS FOR CONFIGURATIONS NOT SHOWN IN CITY OF TULSA STANDARDS.
- ALL MANHOLES SHALL BE COMPLETE IN PLACE. THIS PAY ITEM INCLUDES FRAME, COVER, CONCRETE AND ALL OTHER 57 INCIDENTALS REQUIRED FOR PLACEMENT
- MOBILIZATION FOR THE PROJECT (EXCLUDING WATER MOBILIZATION) IS TO BE INCLUDED IN THIS PAY ITEM. THE MAXIMUM 58 ALLOWABLE AMOUNT WILL BE IN ACCORDANCE WITH THE OKLAHOMA DEPARTMENT OF TRANSPORTATION STANDARD SPECIFICATION TABLE 641.1

- 59.
- PAVEMENT TO BE REPAIRED.
- 61.
- 62.

64.

66.

63.

COMPLETION.

- THIS ITEM 65
- 67. NOT USED. 68. NOT USED.
- 101.
 - 102

 - 106.
 - 107.
 - 108.
 - 109.

- 103. 104.

CONTRACTOR SHALL COORDINATE WITH HOMEOWNERS TO RESET ALL PAVERS, LANDSCAPE STONE, PRIVATE SIDEWALKS AND FENCES THAT ARE DISTURBED DURING CONSTRUCTION OPERATIONS. ALL MATERIALS, LABOR, AND EQUIPMENT REQUIRED FOR RESETTING OF SUCH ITEMS IS TO BE INCLUDED IN PRICE BID FOR URBAN RIGHT OF WAY RESTORATION.

UNCLASSIFIED EXCAVATION INCLUDES REMOVAL OF AGGREGATE BASE AND MODIFIED SUBGRADE UNDER EXISTING

PRICE BID SHALL INCLUDE MAINTENANCE, SEDIMENT REMOVAL, DISPOSAL, AND REMOVAL OF FILTERS AT PROJECT

INCLUDES 5 TYPE 1-B SEDIMENT FILTERS.

SHALL INCLUDE ALL COSTS ASSOCIATED WITH PLUGGING/ PATCHING HOLES IN EXISTING STRUCTURES TO REMAIN.

THE CONTRACTOR SHALL BE RESPONSIBLE FOR CONTROL AND MAINTENANCE OF THE STORM WATER DRAINAGE FROM THE CONSTRUCTION SITE. STORM WATER PONDING ON THE CONSTRUCTION SITE THAT IS THE RESULT OF CONSTRUCTION WILL NOT BE ALLOWED. ALL COST ASSOCIATED WITH STORM WATER MANAGEMENT SHALL BE INCLUDED IN THE PRICE BID FOR

ITEMS TO BE REMOVED MAY OR MAY NOT BE PRESENT IN ANY SPECIFIED CONDITION

ALL TRAFFIC MATERIALS REMOVED SHALL BE HANDLED PER COT SPECIFICATION 625 REMOVAL OF TRAFFIC ITEMS.

EXCAVATION FOR RETAINING WALL AND FOOTING, BACKFILL BEHIND RETAINING WALL, DOWELS, WATERSTOPS, EXPANSION JOINT MATERIAL BACKER ROD, SEALER, FILTERFABRIC AND PIPE UNDER DRAIN ASSEMBLY SHALL BE INCLUDED IN THE PRICE BID PER SY OF RETAINING WALL IN ACCORDANCE WITH ODOT SPECIFICATION 510.06.

PLACE BACKFILL IN ACCORDANCE WITH ODOT 2009 SPECIFICATION 202.04B EMBANKMENTS.BACKFILL SHALL BE IN ACCORDANCE WITH THE PARAMETERS SPECIFIED IN THE TERRACON REPORT 04175021 (MARCH 21, 2017).

IF EXCAVATED MATERIAL DOES NOT MEET CRITERIA FOR "BACKFILL" PER RETAINING WALL GENERAL NOTES, THE CONTRACTOR SHALL CONSIDER THE MATERIAL WASTE AND DISPOSE OF IN ACCORDANCE WITH ODOT SPECIFICATION 104.09

THERE IS AN ESTIMATED XX LBS OF REINFORCING STEEL AND XX CY OF CLASS A CONCRETE IN THE RETAINING WALL AND FOOTING. RETAINING WALL IS MEASURED FROM TOP OF FOOTING TO TOP OF RETAINING WALL. WALL AND FOOTING CONCRETE AND ALL REINFORCING STEEL IS INCLUDED IN THE PRICE BID PER SY OF RETAINING WALL

ALL DRILLED SHAFTS SHALL INCLUDE CROSS-HOLE SONIC LOGGING TUBES IN ACCORDANCE WITH THE SPECIAL PROVISIONS. INCLUDE ALL COSTS OF THE ACCESS TUBES IN THE UNIT PRICE BID FOR DRILLED SHAFTS. ALL REINFORCING STEEL IN THE DRILLED SHAFTS SHALL BE INCLUDED IN THE UNIT PRICE BID FOR DRILLED SHAFTS.

CROSSHOLE SONIC LOGGING SHALL BE PERFORMED IN ACCORDANCE WITH THE SPECIAL PROVISION. THE QUANTITIES INCLUDE THE TESTING OF A MINIMUM OF 1 DRILLED SHAFT FOR EACH SIZE DRILLED SHAFT PER WALL. THE FIRST PRODUCTION SHAFT OF EACH SIZE SHALL BE TESTED BEFORE THE OTHER SHAFTS OF THAT SIZE CAN BE DRILLED. AS A MINIMUM, ONE OUT OF EVERY SIX DRILLED SHAFTS SHALL BE TESTED PER WALL. ADDITIONAL TESTING SHALL BE PERFORMED AT THE DISCRETION OF THE ENGINEER BASED ON PREVIOUS TEST RESULTS, AT NO ADDITIONAL COST TO THE

THIS ITEM INCLUDES 205 CY OF TYPE A SALVAGED TOPSOIL TO BE USED FOR THE ROADWAY AND 1099 CY OF TYPE A SALVAGED TOPSOIL TO BE USED FOR THE PARK

THIS ITEM INCLUDES 177 CY FOR THE 10X10 REINFORCED CONCRETE BOX 14 CY FOR JUNCTION BOX NR 1 7 CY FOR JUNCTION BOX NR. 2, AND 210 CY FOR THE WEIR STRUCTURE

THIS ITEM INCLUDES 27,896 LBS FOR THE 10X10 REINFORCED CONCRETE BOX, 2,536 LBS FOR JUNCTION BOX NR. 1, 1,268 LBS FOR JUNCTION BOX NR. 2, AND 31,141 LBS FOR THE WEIR STRUCTURE



| | | | | | EL | ELM CREEK WEST POND | | | | | | |
|-------|--|----|-----|---|-------------------------|----------------------------|-------|-------|------------|-----|-----|------|
| | THIS | | _ | | PROJECT No. 148150 | | | | | | | |
| | DOCUMENT IS PRELIMINARY IN NATURE AND IS | | | | | ΡΑϡ | / ITI | EM N | OTES | | | |
| | NOT A FINAL, SIGNED AND SEALED | | | | | Y OF T | | , | | | /IA | |
| | DOCUME | NT | | | | UY ENGIN ST, TULSA OK 7 | | | | | | .COM |
| REVIS | SION | BY | DAT | E | PLAN SCALE: | DRAWN | DGD | 01/19 | APPROVED | : | | |
| | | | | | N/A | DESIGNED | MZV | 01/19 | | | | |
| | | | | | | SURVEY | DMM | 09/18 | | | | |
| | | | | | PROFILE SCALE: | PROJ. MGR. | | | | | | |
| | | | | | HORIZONTAL: | LEAD ENGR. | | | | | | |
| | | | | | N/A | FIELD MGR. | | | | | | |
| | | | | | VERTICAL | RECOMMEND | DED: | | | | | |
| | | | | | N/A | DESIGN MAN | AGER | 1 | CITY ENGIN | EER | | - |
| | | | | | | | | | DATE: | | | |
| | | | | | FILE: DRAWING: PAGE NO. | | | | | G03 | | |
| | | | | | ATLAS PAGE | NO: 01 & 08 | | | SHEET NO. | 04 | OF | 123 |
| | | | | | | | | | | | | |

GENERAL CONSTRUCTION NOTES (09/12/2016)

- 1. ALL CONSTRUCTION AND MATERIALS SHALL BE IN ACCORDANCE WITH THE 2009 OKLAHOMA DEPARTMENT OF TRANSPORTATION STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION AND THE CURRENT CITY OF TULSA ENGINEERING SERVICES DEPARTMENT'S STANDARD SPECIFICATIONS AND STANDARD DETAILS AND STANDARD DRAWINGS AND CITY OF TULSA SPECIAL PROVISIONS.
- 2. THE CONTRACTOR SHALL COMPLY WITH ALL FEDERAL, STATE AND LOCAL LAWS GOVERNING SAFETY, HEALTH AND SANITATION. THE CONTRACTOR SHALL PROVIDE ALL SAFEGUARDS, SAFETY DEVICES AND PROTECTIVE EQUIPMENT, AND TAKE ANY OTHER NEEDED ACTION ON AS HIS OWN RESPONSIBILITY OR AS THE ENGINEER MAY DETERMINE REASONABLY NECESSARY TO PROTECT PROPERTY IN CONNECTION WITH THE PERFORMANCE OF WORK COVERED BY THE CONTRACT.
- 3. PAY ITEMS SHALL BE AS SPECIFIED ON THE CITY OF TULSA OR ON THE ODOT STANDARD DRAWINGS EXCEPT AS MODIFIED BY THE CONTRACT.
- 4. THE CONTRACTOR SHALL DETERMINE THE EXACT LOCATION OF ALL EXISTING UTILITIES BEFORE COMMENCING WORK IN EACH AREA. THE CONTRACTOR IS FULLY RESPONSIBLE FOR ANY AND ALL DAMAGES WHICH MIGHT RESULT FROM HIS FAILURE TO LOCATE AND PRESERVE ANY AND ALL UTILITIES.
- 5. THE LOCATIONS OF THE UTILITIES ARE SHOWN ACCORDING TO ALL AVAILABLE INFORMATION. THE CONTRACTOR SHALL NOTIFY EACH UTILITY OWNER PRIOR TO COMMENCEMENT OF WORK TO VERIFY BOTH HORIZONTAL AND VERTICAL LOCATIONS. THE FOLLOWING IS A LIST OF UTILITY OWNERS; AT&T, PUBLIC SERVICE COMPANY OF OKLAHOMA (AEP), OKLAHOMA NATURAL GAS (ONG), COX COMMUNICATIONS, MCI/VERIZON, EASYTEL COMMUNICATIONS, WELLSCO VALLOR TELECOM, CITY OF TULSA-WATER AND SEWER, CITY OF TULSA-TRAFFIC OPERATIONS. SEE TITLE SHEET FOR CONTACT INFORMATION.
- 6. THE CONTRACTOR SHALL GIVE THE NOTIFICATION CENTER OF OKLAHOMA ONE-CALL SYSTEM, INC. NOTICE OF ANY EXCAVATION NO SOONER THAN TEN DAYS NOR LATER THAN 48 HOURS, EXCLUDING SATURDAYS, SUNDAYS AND LEGAL HOLIDAYS, PRIOR TO THE COMMENCEMENT OF WORK. PHONE 1-800-522-6543.
- 7. THE CONTRACTOR SHALL TAKE REASONABLE PRECAUTIONS TO PREVENT EXCESS MOISTURE FROM INCLEMENT WEATHER OR OTHER SOURCES FROM ENTERING ANY STREET EXCAVATION. IF EXCESS MOISTURE DOES ENTER THE EXCAVATION THROUGH THE NEGLIGENCE OF THE CONTRACTOR AND THE ADJOINING PAVEMENT IS ADVERSELY EFFECTED BY THE EXCESS MOISTURE, THE CONTRACTOR SHALL REPLACE THE ADJOINING PAVEMENT AND SUBBASE AT HIS SOLE EXPENSE.
- 8. THE CONTRACTOR SHALL PRESERVE THE INTEGRITY OF THE SANITARY SEWER STRUCTURES AND ALL OTHER UTILITY STRUCTURES WITHIN THE PROJECT EXTENTS.
- THE CONTRACTOR SHALL WORK IN COOPERATION WITH THE CITY OF TULSA TO ESTABLISH, INSTALL, MAINTAIN, AND OPERATE COMPLETE, ADEQUATE, AND SAFE TRAFFIC CONTROLS DURING THE ENTIRE CONSTRUCTION PERIOD. ALL FLAGMEN, BARRICADES, AND TRAFFIC CONTROL DEVICES SHALL BE APPROVED BY THE FIELD ENGINEERING REPRESENTATIVE.
- 10. CONSTRUCTION SIGNAGE WILL BE INSTALLED IN A MANNER APPROVED BY THE ENGINEER, IN ACCORDANCE WITH CHAPTER VI OF THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, CURRENT ADDITION, AND APPLICABLE ODOT STANDARD DRAWINGS. THE CONTRACTOR SHALL PROVIDE A PROPOSED TRAFFIC CONTROL PLAN FOR APPROVAL BY THE ENGINEER PRIOR TO BEGINNING WORK.
- 11. THE CONTRACTOR SHALL NOTIFY THE CITY OF TULSA FIELD ENGINEERING, 918-596-9404, A MINIMUM OF 48 HOURS PRIOR TO COMMENCING WORK OR PRIOR TO REMOVING TRAFFIC SIGNS.
- 12. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE REPLACEMENT OF ALL EXISTING TRAFFIC SIGNS AND MARKINGS REMOVED OR DAMAGED AS LISTED IN THE SIGNAGE SCHEDULE FOR THE PROJECT. ALL SIGNS AND POLES PROVIDED SHALL BE NEW AND UNDAMAGED AND SHALL MEET THE REQUIREMENTS OF COT SPECIFICATION 608 TRAFFIC SIGNS. ALL TRAFFIC MATERIALS REMOVED SHALL BE HANDLED PER COT SPECIFICATION 625 REMOVAL OF TRAFFIC ITEMS.
- 13. THE CONTRACTOR WILL BE RESPONSIBLE FOR PREPARATION AND DISTRIBUTION OF A WRITTEN NOTICE TO RESIDENTS 48 HOURS PRIOR TO BEGINNING PAVEMENT REMOVAL AND MILLING AND OVERLAY OPERATIONS.
- 14. LOCAL AND THROUGH TRAFFIC SHALL BE MAINTAINED THROUGH THE PROJECT AT ALL TIMES.
- 15. ALL PUBLIC AND PRIVATE STREETS AND DRIVES SHALL BE ACCESSIBLE AT ALL TIMES.
- 16. ALL BROKEN CONCRETE, WASTE MATERIAL, AND OTHER DEBRIS SHALL BECOME THE PROPERTY OF THE CONTRACTOR AND SHALL BE REMOVED FROM THE LIMITS OF THE PROJECT AND DISPOSED OF IN A MANNER APPROVED BY THE ENGINEER. NO ADDITIONAL PAYMENT WILL BE MADE FOR THE DISPOSAL OF THIS MATERIAL.
- 17. ALL EXCAVATED MATERIAL NOT REQUIRED IN THE PROJECT SHALL BECOME THE PROPERTY OF THE CONTRACTOR AND SHALL BE DISPOSED OF BY THE CONTRACTOR IN A MANNER ACCEPTABLE TO THE ENGINEER WITHOUT COST TO THE CITY. THE CONTRACTOR WILL BE REQUIRED TO OBTAIN AN EARTH CHANGE PERMIT IF ANY MATERIAL IS STORED ON THE PROJECT SITE AND/OR DISPOSED OF WITHIN THE CITY LIMITS.
- 18. ALL TREES, BRUSH AND OTHER DEBRIS THAT MIGHT INTERFERE WITH THE FLOW OF WATER IS TO BE CLEANED OUT TO THE RIGHT-OF-WAY LINE IN A MANNER APPROVED BY THE ENGINEER. ALL COST TO BE INCLUDED IN THE PRICE BID FOR OTHER ITEMS OF WORK. TREES OUTSIDE THE FILL SLOPES AND THE TOP OF CUT SLOPES SHALL NOT BE DISTURBED EXCEPT WITH THE WRITTEN APPROVAL OF THE ENGINEER.
- 19. WHERE MATERIALS ARE TRANSPORTED IN THE PROSECUTION OF WORK, VEHICLES SHALL NOT BE LOADED BEYOND THE CAPACITY RECOMMENDED BY THE VEHICLE MANUFACTURER OR AS PRESCRIBED BY ANY FEDERAL, STATE OR LOCAL LAW OR REGULATION.
- 20. ANY DAMAGE TO THE ROADWAY PAVEMENT, CURB, DRIVEWAYS OR SIDEWALK CAUSED BY THE CONTRACTOR'S OPERATION SHALL BE REPAIRED TO THE ENGINEER'S SATISFACTION AND SHALL BE ACCOMPLISHED AT THE CONTRACTOR'S SOLE EXPENSE. ALL DISTURBED ITEMS SHALL BE REPAIRED TO MATCH EXISTING MATERIALS AND PATTERNING.
- 21. IF THE CONTRACTOR ENCOUNTERS VOIDS WHEN PATCHING STREETS, THE CONTRACTOR SHALL CALL FIELD ENGINEERING AT 918-596-7814 FOR AN INSPECTION BEFORE PROCEEDING WITH WORK.
- 22. THE PROJECT SHALL BE CONSTRUCTED WITH CONTINUOUS FLOW OF MATERIAL SUPPLIED TO THE PROJECT SUCH THAT THE LAYDOWN MACHINE WILL REMAIN IN MOTION. ANY DELAY IN FORWARD PROGRESSION OF THE LAYDOWN MACHINE MAY REQUIRE A TRANSVERSE JOINT AS DIRECTED BY THE ENGINEER.
- 23. NO FLY ASH IS ALLOWED TO BE USED ON THIS PROJECT.
- 24. PHYSICAL TESTING FOR QUALITY ASSURANCE SHALL BE FURNISHED BY THE CITY.

- 25. CONTRACTOR IS RESPONSIBLE FOR ALL NECESSARY QUALITY CONTROL TESTING TO ENSURE THAT PROJECT REQUIREMENTS ARE MET.
- 26. MASONRY STRUCTURES SHALL NOT BE CONSTRUCTED WITHIN THE STREET RIGHT-OF-WAY.
- 27. ALL CONCRETE CURB AND GUTTERS SHALL BE MONOLITHIC POURS. DOWELED-ON CURBS WILL NOT BE ALLOWED.
- 28. NO LIFTING HOLES WILL BE ALLOWED ON ANY REINFORCED CONCRETE PIPES OR REINFORCED CONCRETE BOXES.
- 29. CURB RAMP CONSTRUCTION SHALL COMPLY WITH THE CURRENT AMERICANS WITH DISABILITIES ACT STANDARDS.
- 30. REFLECTORIZED SHEETING ON SIGNS AND BARRICADES SHALL BE OF A CUBIC PRISMATIC TYPE AND SHALL MEET THE SPECIFICATIONS ESTABLISHED FOR ASTM D 4956-01 TYPE IX RETROREFLECTIVE SHEETING. REFLECTORIZED SHEETING ON DRUMS AND TUBE CHANNELIZERS SHALL BE OF A HIGH-INTENSITY TYPE AND SHALL MEET THE SPECIFICATIONS ESTABLISHED FOR ASTM D 4956-01 TYPE III RETROREFLECTIVE SHEETING.
- 31. ALL SANITARY AND STORM SEWER MANHOLE CASTINGS AND LIDS THAT ARE LOCATED IN THE STREET AND ARE DISTURBED BY THE CONTRACTOR SHALL BE REPLACED WITH NEW LIDS AND CASTINGS AND THE OLD ONES SHALL BE SALVAGED AND DELIVERED TO THE METAL RECYCLE BINS IN THE STOCKROOM AREA AT SEWER OPERATIONS AND MAINTENANCE, 9319 E. 42ND STREET NORTH, BETWEEN THE HOURS OF 7:30 AM AND 3:00 PM MONDAY THROUGH FRIDAY.
- 32. THE SIGN PLACEMENT STATIONING AND LOCATIONS SHOWN ON THE PLAN SHEETS AND SUMMARY SHEETS ARE APPROXIMATE. EXACT STATIONING AND LOCATIONS SHALL BE VERIFIED BY THE CONTRACTOR SO THAT THE SIGN IS INSTALLED IN ACCORDANCE WITH CITY OF TULSA STANDARDS, CURRENT AMERICANS WITH DISABILITIES ACT STANDARDS, AND THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES IN ORDER TO PROVIDE OPTIMUM VISIBILITY TO THE ONCOMING/APPROACHING MOTORIST. IF A PROPOSED LOCATION CONFLICTS WITH OTHER SIGNS, UTILITIES, OR OTHER ROADWAY FEATURES, THE ENGINEER SHALL BE NOTIFIED.
- 33. POST LENGTHS SHOWN ON SIGN SUMMARY ARE APPROXIMATE. EXACT LENGTHS SHALL BE DETERMINED BY A FIELD SURVEY CONDUCTED BY THE CONTRACTOR.
- 34. ALL ASPHALT STREETS THAT ARE TO BE RECONSTRUCTED SHALL BE LEFT WITH A DRIVABLE SURFACE AT ALL TIMES. THE CONTRACTOR WILL NOT BE ALLOWED TO MILL OFF ALL THE ASPHALT BEFORE EXCAVATION BEGINS.
- 35. THE CONTRACTOR SHALL REPLACE ANY SECTION CORNERS OR OTHER PERMANENT RIGHT OF WAY MARKERS REMOVED OR DISTURBED AS A RESULT OF THE CONSTRUCTION OF THIS PROJECT. REPLACEMENT OF SECTION CORNERS OR ANY OTHER MONUMENTS SHALL BE PERFORMED BY A LICENSED LAND SURVEYOR AUTHORIZED TO PERFORM WORK IN THE STATE OF OKLAHOMA.
- 36. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE CONTROL AND MAINTENANCE OF THE STORMWATER DRAINAGE. STORMWATER PONDING ON THE CONSTRUCTION SITE THAT IS THE RESULT OF CONSTRUCTION WILL NOT BE ALLOWED.
- 37. STRAW OR HAY BALES AS STORMWATER BEST MANAGEMENT PRACTICES ARE NO LONGER ALLOWED ON CONSTRUCTION PROJECTS.
- 38. THE CONTRACTOR MUST CALL 1-800-458-4251 IMMEDIATELY IF A NATURAL GAS PIPELINE IS CUT, DAMAGED, OR OTHERWISE DISTURBED.
- 39. PRIOR TO FINAL ACCEPTANCE, ALL EXPOSED CURB SURFACES SHALL BE CLEANED OF ALL DISCOLORATION SUCH AS ASPHALT STAIN, TIRE MARKS, OR OTHER DISFIGUREMENT.
- 40. ALL FEATURES OF THIS PROJECT INCLUDING, BUT NOT LIMITED TO, SIDEWALKS, CURB RAMPS, AND CROSSWALKS SHALL COMPLY WITH THE AMERICANS WITH DISABILITIES ACT, ACCESSIBILITY GUIDELINES, AND THE PROPOSED ACCESSIBILITY GUIDELINES FOR PEDESTRIAN FACILITIES IN THE PUBLIC RIGHT-OF-WAY, PUBLISHED ON JULY 26, 2011 BY THE U.S. ACCESS BOARD. WHERE SPATIAL LIMITATIONS OR EXISTING FEATURES WITHIN THE LIMITS OF THE PROJECT PREVENT FULL COMPLIANCE WITH THIS ACT, THE CONTRACTOR SHALL IMMEDIATELY NOTIFY THE ENGINEER UPON DISCOVERY OF SUCH FEATURES. THE CONTRACTOR SHALL NOT PROCEED WITH ANY ASPECT OF THE WORK, WHICH IS NOT IN FULL COMPLIANCE WITH THE ADA WITHOUT PRIOR WRITTEN APPROVAL FROM THE ENGINEER. ANY WORK, WHICH IS NOT PERFORMED WITHIN THE GUIDELINES OF THE ADA, FOR WHICH THE CONTRACTOR DOES NOT HAVE WRITTEN APPROVAL, SHALL BE CORRECTED AT THE CONTRACTOR'S EXPENSE.
- 41. ALL TRENCH WIDTHS & BEDDING MATERIAL SHALL BE AS SHOWN ON COT STANDARD PIPE BEDDING DETAIL, STANDARD NO. 751. SPECIFIED TRENCH WIDTHS SHALL BE MAINTAINED FULL DEPTH FROM THE FLOWLINE TO THE GRADING TEMPLATE. THE CONTRACTOR SHALL KEEP THE OPEN TRENCH DRAINED.
- 42. THE CONTRACTOR SHALL NOTIFY THE METROPOLITAN TULSA TRANSIT AUTHORITY (MTTA), ERIC SMITH 918-830-0024, A MINIMUM OF 48 HOURS PRIOR TO COMMENCING WORK, LANE CLOSURES OR PRIOR TO DETOURING TRAFFIC.
- 43. CONTRACTOR SHALL NOT STORE EQUIPMENT OR MATERIALS IN THE FLOODPLAIN.

THIS DOCUMENT IS PRELIMINARY IN NATURE AND IS NOT A FINAL, SIGNED AND SEALED DOCUMENT



| | | | EL | M CRE | EF | < WI | EST PO | ONE |) | | |
|----------|----|------|--|----------------------------|------|-------|-------------|------|--------|--|--|
| | | | | PROJE | ECT | ۲No | . 14815 | 0 | | | |
| | | | GEN | GENERAL CONSTRUCTION NOTES | | | | | | | |
| | | | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | | | | | |
| | | | GUY ENGINEERING S 6910 E. 14TH ST, TULSA OK 74112 / PH: 914 | | | | | | GR.COM | | |
| REVISION | BY | DATE | PLAN SCALE: | DRAWN | DGD | 01/19 | APPROVED: | | | | |
| | | | N/A | DESIGNED | MZV | 01/19 | | | | | |
| | | | | SURVEY | DMM | 09/18 | | | | | |
| | | | PROFILE SCALE: | PROJ. MGR. | | | | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | | | | |
| | | | N/A | FIELD MGR. | | | | | | | |
| | | | VERTICAL | RECOMMEND | DED: | | | | | | |
| | | | N/A | DESIGN MAN | AGER | | CITY ENGINE | ER | _ | | |
| | | | | | | | DATE: | | | | |
| | | | FILE: DRAWING: PAGE NO. | | | | | | G04 | | |
| | | | ATLAS PAGE | NO: 01 & 08 | | | SHEET NO. | 05 o | F 123 | | |

| | | | | | SURFAC | ING SUMM | IARY | | | | | |
|--------------|---------------|---------|----------------------------|-------------------|---------------------|-----------------------|--|--|---------------------------------|---|---------------------------------|-------------------------|
| STATIONS | | LENGTH | UNCLASSIFIED EXCAVATION | AGGREGATE BASE | SEPARATOR FABRIC | SUBGRADE, METHOD B | SUPERPAVE, TYPE S3 (PG 64-22 OK) | SUPERPAVE, TYPE S4 (PG 64-22 OK) | TYPE 1 APC PATCH ARTERIAL | COMBINED CURB & GUTTER (6" BARRIER) | STAMPED CONCRETE SIDEWALK | 4" CONCRETE SIDEWALK |
| | | | 202(A) | 303(A) | 325 | 310(B) | 411(B) | 411(C) | SPECIAL | 609(B) | 610(A) | 610(A) |
| | | L.F. | CY | CY | SY | SY | TON | TON | CY | LF | SY | SY |
| MADISON STRE | ET | | | | | | | | | | | |
| 10+22.50 | 20+75.95 | 1,053 | 3,694 | 1,847 | 6,242 | 5,540 | 1,344 | 537 | | 2,284 | | 315 |
| NORFOLK AVE | NUE AND E. 5T | H PLACE | | | | | | | | | | |
| 30+22.50 | 37+65.50 | 743 | 1,980 | 990 | 3,467 | 2,971 | 686 | 274 | | 1,582 | 85 | 347 |
| S OWASSO AV | ENUE | | | | • | | | | | • | • | |
| 39+67.00 | 47+18.50 | 752 | 1,598 | 799 | 2,897 | 2,396 | 523 | 209 | | 1,438 | 6 | 72 |
| 4TH STREET | | | | | | | | | | | | |
| | | 629 | 144 | 72 | 217 | 217 | | 24 | 72 | 259 | | 29 |
| 6TH STREET | | | | | | | | | | | | |
| | | 259 | 1,206 | 603 | 1,810 | 1,810 | | 203 | 608 | 320 | | 90 |
| | | TOTAL = | 8,622 | 4,311 | 14,633 | 12,934 | 2,553 | 1,247 | <mark>681</mark> | 5,883 | 91 | 853 |

| | SUMMARY OF REMOVALS | | | | | | | | | |
|----------------|---|--------------------------------------|--|---|--|------------------------------------|---|---------------------------------------|--|---|
| | REMOVAL OF CONCRETE PAVEMENT 619(B) | REMOVAL OF APC PAVEMENT 619(B) | REMOVAL OF ASPHALT PAVEMENT 619(B) | REMOVAL OF CURB AND GUTTER 619(B) | REMOVAL OF EXISTING INLET 619(B) | REMOVAL OF STORM PIPE 619(B) | REMOVAL OF MANHOLE (STORM) 619(B) | REMOVAL OF SANITARY PIPE 619(B) | REMOVAL OF MANHOLE (SANITARY) 619(B) | REMOVAL OF WATER LINE PIPE 619(B) |
| | S.Y. | S.Y. | S.Y. | L.F. | EA. | L.F. | EA. | L.F. | EA. | L.F. |
| DEMOLITION S | HEET 1 O | F3 | | | | | | | | |
| | 2299 | 4834 | 1198 | 3215 | 8 | 1576 | 8 | 1265 | 7 | 1622 |
| DEMOLITION S | HEET 2 O | F3 | | | | | | | | |
| | 2601 | 5788 | | 3,360 | 5 | 1,790 | 8 | 1,296 | 7 | 1,510 |
| DEMOLITION SHE | EET 3 OF 3 | | | | | | | | | |
| | 192 | 4957 | | 1,620 | 4 | 765 | 2 | 965 | 5 | 1,650 |
| TOTALS = | 5,092 | 15,579 | 1,198 | 8,195 | 17 | 4,131 | 18 | 3,526 | 19 | 4,782 |

| | | | | SI | GNSUMN | IARY | | | | |
|----------|--------|------------------------------|--------------------|---------|-----------|---------------------------|------------------|------------------------------------|---|-------------------------------------|
| STATION | | MUTCD NAME | MUTCD SIGN DES. | SECTION | SIZE | DESCRIPTION | NOTES | GROUND SIGN COT 608A (SF) | 1-3/4" SIGN POST COT 608B (LF) | 2" SIGN POST COT 608E (LF) |
| ADISON | AVE | - | | | | · · · · · | | | | |
| 10+40.80 | I RT | SUPPLEMENTAL WARNING PLAQUES | W16-7P | 2D.28 | 24" X 12" | LEFTARROW | INSTALL NEW SIGN | 2.0 | | |
| 10+40.80 | RT | PEDESTRIAN | W11-2 | 2C.50 | 36" X 36" | PEDESTRIAN CROSSING | INSTALL NEW SIGN | 9.0 | 10 | 3 |
| 10+53.00 | LT | STOP | R1-1 | 5B.02 | 36" X 36" | STOP | INSTALL NEW SIGN | 9.0 | 10 | 3 |
| 10+64.50 | LT | STOP | R1-1 | 5B.02 | 36" X 36" | STOP | INSTALL NEW SIGN | 9.0 | 10 | 3 |
| 10+64.50 | LT | STREET NAME (1 LINE) | COT 608 | 2D.45 | 24" X 6" | E 6TH ST. | INSTALL NEW SIGN | 2.0 | | |
| 10+64.50 | LT | STREET NAME (1 LINE) | COT 608 | 2D.45 | 24" X 6" | S MADISON AVE. | INSTALL NEW SIGN | 2.0 | | |
| 10+69.00 | LT | BYCICLE SIGNS | R5-3 | 9B.08 | 24" X 24" | NO MOTOR VEHICLES | INSTALL NEW SIGN | 4.0 | 10 | 3 |
| 20+32.00 | LT | BYCICLE SIGNS | R5-3 | 9B.08 | 24" X 24" | NO MOTOR VEHICLES | INSTALL NEW SIGN | 4.0 | 10 | 3 |
| 20+33.00 | RT | STOP | R1-1 | 5B.02 | 36" X 36" | STOP | INSTALL NEW SIGN | 9.0 | 10 | 3 |
| 20+33.00 | RT | STREET NAME (1 LINE) | COT 608 | 2D.45 | 24" X 6" | E 4TH ST | INSTALL NEW SIGN | 2.0 | | |
| 20+33.00 | RT | STREET NAME (1 LINE) | COT 608 | 2D.45 | 24" X 6" | S MADISON AVE | INSTALL NEW SIGN | 2.0 | | |
| 20+46.00 | RT | SUPPLEMENTAL WARNING PLAQUES | W16-7P | 2D.28 | 24" X 12" | LEFT ARROW | INSTALL NEW SIGN | 2.0 | | |
| 20+46.00 | RT | PEDESTRIAN | W11-2 | 2C.50 | 36" X 36" | PEDESTRIAN CROSSING | INSTALL NEW SIGN | 9.0 | 10 | 3 |
| ORFOLI | KAVE 8 | & 5TH PL | | | | | | | | |
| 30+36.00 | RT | SUPPLEMENTAL WARNING PLAQUES | W16-7P | 2D.28 | 24" X 12" | LEFT ARROW | INSTALL NEW SIGN | 2.0 | | |
| 30+36.00 | RT | PEDESTRIAN | W11-2 | 2C.50 | 36" X 36" | PEDESTRIAN CROSSING | INSTALL NEW SIGN | 9.0 | 10 | 3 |
| 30+55.00 | LT | STOP | R1-1 | 5B.02 | 36" X 36" | STOP | INSTALL NEW SIGN | 9.0 | 10 | 3 |
| 30+55.00 | LT | STREET NAME (1 LINE) | COT 608 | 2D.45 | 24" X 6" | VETERANS WAY | INSTALL NEW SIGN | 2.0 | | |
| 30+55.00 | LT | STREET NAME (1 LINE) | COT 608 | 2D.45 | 24" X 6" | E 6TH ST | INSTALL NEW SIGN | 2.0 | | |
| 30+55.00 | LT | STREET NAME (1 LINE) | COT 608 | 2D.45 | 24" X 6" | S NORFOLK AVE | INSTALL NEW SIGN | 2.0 | | |
| 32+30.00 | RT | CHANGES IN HORIZONTAL ALIGN. | W1-1(R) | 2C.04 | 24" X 24" | RIGHT CURVE | INSTALL NEW SIGN | 4.0 | 10 | 3 |
| 32+30.00 | RT | CHANGES IN HORIZONTAL ALIGN. | W13-1P (20) | 2C.08 | 24" X 24" | ADVISORY SPEED (20 MPH) | INSTALL NEW SIGN | 4.0 | | |
| 33+13.00 | LT | CHANGES IN HORIZONTAL ALIGN. | W1-6 | 2C.12 | 48" X 24" | ONE-DIRECTION LARGE ARROW | INSTALL NEW SIGN | 8.0 | 10 | 3 |
| 33+78.00 | LT | CHANGES IN HORIZONTAL ALIGN. | W1-6 | 2C.12 | 48" X 24" | ONE-DIRECTION LARGE ARROW | INSTALL NEW SIGN | 8.0 | 10 | 3 |
| 35+58.00 | LT | CHANGES IN HORIZONTAL ALIGN. | W1-1(L) | 2C.04 | 24" X 24" | LEFT CURVE | INSTALL NEW SIGN | 4.0 | 10 | 3 |
| 35+58.00 | LT | CHANGES IN HORIZONTAL ALIGN. | W13-1P (20) | 2C.08 | 24" X 24" | ADVISORY SPEED (20 MPH) | INSTALL NEW SIGN | 4.0 | | |
| 36+48.00 | RT | STOP | R1-1 | 5B.02 | 36" X 36" | STOP | INSTALL NEW SIGN | 9.0 | 10 | 3 |
| 37+08.00 | LT | STOP | R1-1 | 5B.02 | 36" X 36" | STOP | INSTALL NEW SIGN | 9.0 | 10 | 3 |
| WASSO | AVE | | | | | | | | | |
| 40+25.00 | RT | STOP | R1-1 | 5B.02 | 36" X 36" | STOP | INSTALL NEW SIGN | 9.0 | 10 | 3 |
| 40+25.00 | RT | STREET NAME (1 LINE) | COT 608 | 2D.45 | 24" X 6" | S OWASSO AVE | INSTALL NEW SIGN | 2.0 | | |
| 40+25.00 | RT | STREET NAME (1 LINE) | COT 608 | 2D.45 | 24" X 6" | E 5TH ST | INSTALL NEW SIGN | 2.0 | | |
| 43+93.00 | RT | STOP | R1-1 | 5B.02 | 36" X 36" | STOP | INSTALL NEW SIGN | 9.0 | 10 | 3 |
| 43+93.00 | RT | STREET NAME (1 LINE) | COT 608 | 2D.45 | 24" X 6" | E 4TH ST | INSTALL NEW SIGN | 2.0 | | |
| 43+93.00 | RT | STREET NAME (1 LINE) | COT 608 | 2D.45 | 24" X 6" | E 5TH ST | INSTALL NEW SIGN | 2.0 | | |
| 46+93.00 | RT | STOP | R1-1 | 5B.02 | 36" X 36" | STOP | INSTALL NEW SIGN | 9.0 | 10 | 3 |
| 46+93.00 | RT | STREET NAME (1 LINE) | COT 608 | 2D.45 | 24" X 6" | E 4TH ST | INSTALL NEW SIGN | 2.0 | | |
| 46+93.00 | RT | STREET NAME (1 LINE) | COT 608 | 2D.45 | 24" X 6" | S OWASSO AVE | INSTALL NEW SIGN | 2.0 | | |
| 4TH ST | | <u>.</u> | | | | 1 | | -1 | 1 | |
| | 1 | DEAD END | W14-1 | 2C.26 | 36" X 36" | DEAD END | INSTALL NEW SIGN | 9.0 | 10 | 3 |
| | 1 | | VV | 20.20 | 30 × 30 | | MOTALE NEW OIGN | 0.0 | 10 | |

| SUMMARY OF DRIVES | | | | | | | | | |
|-------------------|-----------|----|---------------------|------------------|---------|-------------------------------------|--|--|--|
| DRIVE No. | STATION | | Drive Width, "W" | RETURN RADIUS | LENGTH | 6" CONCRETE DRIVEWAY (H.E.S.) | | | |
| NO. | | | | | | 610(B) | | | |
| | | | FT | FT | LF | SY | | | |
| MADISON | ST. | | | | | | | | |
| D1 | 19+60.00 | RT | 97.3 | 10 | 13.5 | 152.1 | | | |
| NORFOLK | & 5TH PL. | | | | | | | | |
| D2 | 30+75.00 | LT | 21.3 | 10 | 22.2 | 59.9 | | | |
| D3 | 31+86.19 | RT | 20.3 | 15 | 18.5 | 54.8 | | | |
| OWASSO | ST. | | | | | | | | |
| D4 | 41+85.10 | RT | 20.0 | 10 | 16.5 | 43.1 | | | |
| E 4TH ST. | a. | | | | | | | | |
| D5 | 101+36.68 | RT | 52.4 | 10 | 6.5 | 40.6 | | | |
| D6 | 101+79.82 | RT | 21.3 | 5 | 6.5 | 18.6 | | | |
| D7 | 102+09.45 | RT | 22.1 | 5 | 6.5 | 17.7 | | | |
| D8 | 102+46.03 | RT | 33.4 | 5 | 6.5 | 27.2 | | | |
| D9 | 103+19.83 | RT | 20.4 | 5 | 6.5 | 16.6 | | | |
| D10 | 103+61.27 | RT | 26.4 | 5 | 18.5 | 58.2 | | | |
| D11 | | | 41.3 | 6 | 18.2 | 85.6 | | | |
| D12 | | | 24.0 | 6 | 15.3 | 43.2 | | | |
| D13 | 104+09.11 | RT | 25.2 | 5 | 6.5 | 20.1 | | | |
| D14 | 105+11.92 | RT | 15.7 | 5 | 6.5 | 13.3 | | | |
| D15 | 105+84.78 | RT | 15.0 | 5 | 6.5 | 12.6 | | | |
| D16 | | | 13.3 | 5 | 18.7 | 30.1 | | | |
| | | | | | TOTAL = | 693.7 | | | |

| SUMMARY OF F | <u>PAVEMENT MA</u> | RKINGS (PER | MANEN | 1) | | | | | | | | |
|------------------|--|-------------|--------|-------------|------|---|---|---|--|---|---------------------------------------|----------|
| LOCATION | | | | = (PLASTIC) | | | | | | | | |
| | 856(A) | 856(A) | 856 | (A) | | | M CR | | < \ \ / I | | | |
| | L.F. | L.F. | L.I | Ε. | | | | | | 201 F | | |
| MADISON AVE | | 1,924 | 25 | 8 | | | PROJ | ECT | ⁻ No | . 14815 | 0 | |
| NORFOLK & 5TH ST | | 1,333 | 13 | 3 | | | | | | | - | |
| OWASSO AVE | | 1,292 | | | | | ROAD | NAY | ์ รเ | JMMAF | YY Y | |
| 4TH ST | 144 | 1,287 | | | | | | SF | HEE ⁻ | Г | | |
| TOTALS = | 144 | 5,836 | 39 | 1 | | | | | | - | | |
| | | | | | | | ry of 1 | | | | | |
| | | | | | | G | ENGINEERIN I ST, TULSA OK | NG SEF | RVICES | S DEPARTM ERVICES, | IENT | сом |
| | | RE | VISION | BY | DATE | G | ENGINEERIN I ST, TULSA OK | NG SEF | RVICES NG SI PH: 918.4 | S DEPARTM ERVICES, | IENT INC. /.guyengr.c | СОМ |
| cov. | THIS | REY | VISION | BY | DATE | E 6910 E. 14TH | ENGINEERIN I ST, TULSA OK | NG SEF | RVICES NG SI PH: 918.4 | S DEPARTN ERVICES, 137.0282 / WWW | IENT INC. /.guyengr.c | СОМ |
| | THIS DOCI IMENT IS | | VISION | BY | DATE | G 6910 E. 14TH PLAN SCALE: N/A | UY ENGIN SUY ENGIN ST, TULSA OK DRAWN DESIGNED SURVEY | NG SEF | RVICES NG SI PH: 918.4 01/19 | S DEPARTN ERVICES, 137.0282 / WWW | IENT INC. /.guyengr.c | СОМ |
| 100 B | THIS DOCUMENT IS PRELIMINARY IN | | VISION | BY | DATE | G 6910 E. 14TH PLAN SCALE: | NGINEERIN UY ENGIN IST, TULSA OK DRAWN DESIGNED SURVEY PROJ. MGR. | NG SEF | RVICES NG SI PH: 918.4 01/19 01/19 | S DEPARTN ERVICES, 137.0282 / WWW | IENT INC. /.guyengr.c | СОМ |
| 500 B | DOCUMENT IS | | VISION | BY | DATE | G 6910 E. 14TH PLAN SCALE: N/A | DRGINEERIN ST, TULSA OK DRAWN DESIGNED SURVEY PROJ. MGR. LEAD ENGR. | NG SEF | RVICES NG SI PH: 918.4 01/19 01/19 | S DEPARTN ERVICES, 137.0282 / WWW | IENT INC. /.guyengr.c | СОМ |
| S OU BE | DOCUMENT IS PRELIMINARY IN NATURE AND IS NOT A FINAL, | | VISION | BY | DATE | E 6910 E. 14TH PLAN SCALE: N/A PROFILE SCALE: | NGINEERIN I ST, TULSA OK DRAWN DESIGNED SURVEY PROJ. MGR. LEAD ENGR. FIELD MGR. | NG SEF | RVICES NG SI PH: 918.4 01/19 01/19 | S DEPARTN ERVICES, 137.0282 / WWW | IENT INC. /.guyengr.c | СОМ |
| S COU BR | DOCUMENT IS PRELIMINARY IN NATURE AND IS NOT A FINAL, SIGNED AND | | VISION | BY | DATE | PLAN SCALE: N/A PROFILE SCALE: HORIZONTAL: N/A VERTICAL | DRGINEERIN ST, TULSA OK DRAWN DESIGNED SURVEY PROJ. MGR. LEAD ENGR. | NG SEF | RVICES NG SI PH: 918.4 01/19 01/19 | S DEPARTN ERVICES, 137.0282 / WWW | IENT INC. /.guyengr.c | СОМ |
| | DOCUMENT IS PRELIMINARY IN NATURE AND IS NOT A FINAL, SIGNED AND SEALED | | VISION | BY | DATE | PROFILE SCALE: HORIZONTAL: N/A | NGINEERIN I ST, TULSA OK DRAWN DESIGNED SURVEY PROJ. MGR. LEAD ENGR. FIELD MGR. | NG SEF | RVICES NG SI PH: 918.4 01/19 01/19 | S DEPARTM ERVICES, 137.0282 / WWW APPROVED | IENT INC. | сом |
| L ON IN | DOCUMENT IS PRELIMINARY IN NATURE AND IS NOT A FINAL, SIGNED AND | | VISION | BY | DATE | PROFILE SCALE: N/A PROFILE SCALE: N/A HORIZONTAL: N/A VERTICAL N/A | NGINEERIN SUY ENGIN 1 ST. TULSA OK DRAWN DESIGNED SURVEY PROJ. MGR. LEAD ENGR. FIELD MGR. RECOMMEN DESIGN MAT | NG SEF IEERI 74112 / DGD MZV DMM DMM DED: NAGER | RVICES NG SI PH: 918.4 01/19 01/19 | CITY ENGIN | IENT INC. . GUYENGR.C : : | _ |
| South Courte | DOCUMENT IS PRELIMINARY IN NATURE AND IS NOT A FINAL, SIGNED AND SEALED | | VISION | BY | DATE | PLAN SCALE: PLAN SCALE: N/A PROFILE SCALE: HORIZONTAL: N/A VERTICAL | NGINEERIN ST, TULSA OK DRAWN DESIGNED SURVEY PROJ. MGR. LEAD ENGR. FIELD MGR. RECOMMEN | NG SEF IEERI 74112 / DGD MZV DMM DMM DED: NAGER | RVICES NG SI PH: 918.4 01/19 01/19 | S DEPARTM ERVICES, 137.0282 / WWW APPROVED | IENT INC. . GUYENGR.C : : | - G05 |



ΤÌΥ

WATERLINE PAY ITEM NOTES (09/24/2018)

- TESTING AND CHI ORINATION OF WATER MAINS SHALL BE PERFORMED BY THE CITY OF THE SA. TESTING, CHI ORINATION AND FLUSHING SHALL BE DONE IN ACCORDANCE WITH SECTION 109.3 OF THE GENERAL SPECIFICATIONS
 - A. CONTRACTOR SHALL FURNISH AND INSTALL TEMPORARY PLUGS WITH ADEQUATE BLOCKING OR RESTRAINTS, PLUS CORPORATION STOPS, AS DIRECTED BY CITY TESTING PERSONNEL, THEN, ONCE TESTING, CHLORINATION AND FLUSHING BY CITY PERSONNEL IS COMPLETED, REMOVE TEMPORARY BLOCKING AND TIE INTO EXISTING SYSTEM, USING FITTINGS SWABBED INTERNALLY WITH 2% BLEACH SOLUTION
 - B TESTING CHI ORINATION AND FUSHING OF NEW WATER MAIN SHALL BE PERFORMED BY CITY PERSONNEL ON MAINS WHICH ARE PHYSICALLY DISCONNECTED FROM THE EXISTING WATER SYSTEM. TESTING, CHLORINATION, AND FLUSHING OF NEW WATER MAINS SHALL NOT BE PERFORMED AGAINST VALVES WHICH ARE PHYSICALLY CONNECTED TO EXISTING SYSTEM.
 - C. ALL COSTS FOR TEMPORARY PLUGS, BLOCKING, RESTRAINING, CORPORATION STOPS, TUBING, THREADED CONNECTIONS, BLEACH AND OTHER INCIDENTALS SHALL BE INCLUDED IN THE UNIT PRICE BID FOR PIP
- BURIED BOLTS, HARNESS LUGS, AND COUPLINGS SHALL BE GIVEN TWO COATS OF KOPPER'S BITUMASTIC 300-M (DRY MIL THICKNESS OF 16 MILS) OR EQUAL COST TO BE INCLUDED IN UNIT PRICE BID FOR PIPE AND FITTINGS.
- CONTRACTOR TO EXCAVATE ALL UTILITY CROSSINGS AHEAD OF PIPE LAYING SO THAT THE GRADES CAN BE ADJUSTED ON THE PROPOSED WATER MAIN TO AVOID UTILITY CONFLICTS. FAILURE TO DO SO SHALL NOT ENTITLE THE CONTRACTOR TO CLAIM EXTRA COMPENSATION FOR ADJUSTMENTS TO THE PROPOSED WATER MAIN. COST FOR EXCAVATING UTILITY SINGS SHALL BE INCLUDED IN UNIT PRICE BID FOR PIPE.
- NOT USED
- NOT USED
- NOT USED
- NOT USED
- ALL COSTS FOR COMPONENTS NECESSARY TO RESTRAIN JOINTS FOR PIPE AND FITTINGS DESIGNATED RESTRAINED JOINT ("RJ") SHALL BE INCLUDED IN UNIT PRICE BID FOR PIPE OR FITTINGS.
 - A. DUCTILE IRON PIPE RESTRAINED JOINT SYSTEMS: US PIPE TRELEX, GRIFFIN SNAPLOK, MCWANE THRUSTLOCK, AMERICAN FLEXRING, EBAA MEGALUG, STAR STARGRIP, SMITH-BLAIR CAMLOCK, CLOW TUFGRIP OR EQUAL SHALL BE USED ON THIS PROJECT. SHOULD RJ PIPE BE SPECIFIED THROUGH UNCASED BORES, ONLY USPIPE TRFLEX, GRIFFIN SNAPLOK, MCWANE THRUSTLOCK, OR AMERICAN FLEXRING IS TO BE USED. LOCKING GASKETS NOT
 - B. NOT USED

C. NOT USED.

NO ADDITIONAL PAYMENT SHALL BE MADE

- ALL CUT ENDS AND WHERE SALVAGED FITTINGS HAVE BEEN REMOVED FROM ABANDONED WATER LINES LEFT IN PLACE, SHALL BE PLUGGED WITH 24-IN OF CONCRETE INSIDE THE PIPE. COST OF CONCRETE PLUGGING TO BE INCLUDED IN UNIT PRICE BID FOR PIPE. NO ADDITIONAL PAYMENT SHALL BE MADE.
- NOT USED
- DETECTABLE MYLAR MARKING TAPE SHALL BE INSTALLED OVER DUCTILE IRON PIPE AS PER CONST SPEC 307.3 AND 307.4. 11. COST WILL BE INCLUDED IN COST OF DUCTILE IRON PIPE.
- ALL LABOR MATERIALS AND EQUIPMENT TO CONNECT PROPOSED WATER MAINS TO EXISTING WATER MAINS ARE INCLUDED IN COST OF SLEEVES/ADAPTORS. CONTRACTOR TO EXCAVATE ALL EXISTING WATER MAINS AHEAD OF PIPE LAYING SO THAT THE GRADES CAN BE ADJUSTED ACCORDINGLY, FAILURE TO DO SO SHALL NOT ENTITLE THE CONTRACTOR TO CLAIM EXTRA COMPENSATION FOR ADJUSTMENTS TO THE PROPOSED WATER MAIN. COST FOR EXCAVATING EXISTING WATER MAINS SHALL BE INCLUDED IN UNIT PRICE BID FOR SLEEVES. NO ADDITIONAL PAYMENT SHALL BE MADE
- (OPTIONAL) AT THE DIRECTION OF THE ENGINEER, CONTRACTOR SHALL FURNISH A "LICENSED AND BONDED 13. PLUMBER", WHICH SHALL INCLUDE ALL COSTS OF LABOR, TOOLS, PERMIT FEES, AND EQUIPMENT TO REROUTE THE EXISTING CUSTOMER SERVICE ON CUSTOMER PROPERTY TO THE PROPOSED CUSTOMER METER CAN. COST SHALL NOT EXCEED AN ALLOWANCE OF \$1000 PER OCCURRENCE. MATERIALS SHALL BE PAID UNDER SEPARATE BID ITEMS. NO ADDITIONAL PAYMENT SHALL BE MADE.
- CONTRACTOR IS REMINDED TO BACKFILL ALL TRENCHES EXCAVATED ACROSS ANY EXISTING OR PROPOSED DRIVING OR PARKING SURFACE WITH 11/2 -IN TYPE A AGGREGATE BASE. PLACED IN 8-INCH MAXIMUM LIFTS AND COMPACTED TO 98% MODIFIED PROCTOR DENSITY. COST TO BE INCLUDED IN COST OF EXCAVATION AND BACKFILL. NO ADDITIONAL PAYMENT SHALL BE MADE
- WATER SERVICE CONNECTIONS SHALL INCLUDE COST OF MATERIAL, LABOR AND EQUIPMENT TO REMOVE AND INSTALL SADDLES, SERVICE CLAMPS, CORPORATION STOPS, BENDS, 3-PART UNIONS, COUPLINGS, SETTERS AND ANY OTHER INCIDENTALS REQUIRED FOR A COMPLETE WATER SERVICE CONNECTION WITH EXCEPTION OF METER CANS, RIMS AND LIDS. NO ADDITIONAL PAYMENT SHALL BE MADE. METER CANS, LIDS AND RIMS SHALL BE PAID AS A SEPARATE BID ITEM.
 - A. SHORT SERVICE SHALL BE ANY SERVICE LINE THAT IS 25-FEET OR LESS IN LENGTH. SHORT SERVICES DO NOT INCLUDE PAVEMENT REPLACEMENT. I.E. ¾-INCH WATER SERVICE CONNECTIONS (SHORT SERVICE)
 - B. LONG SERVICE SHALL BE ANY SERVICE LINE THAT IS GREATER THAN 25-FEET UP TO 80-FEET IN LENGTH. LONG SERVICES INCLUDE PAVEMENT REPLACEMENT AND/ OR COST TO BORE. EXAMPLE: 3/-IN WATER SERVICE CONNECTIONS (LONG SERVICE)
 - C. SHORT AND LONG SERVICE LINES EXCEEDING THE ABOVE PARAMETERS WILL BE COMPENSATED FOR LINEAR OOTAGE ABOVE AND BEYOND. COMPENSATION SHALL BE PAID AS "SERVICE LINES, EXTENSION", PER LF
- NOT SERVICE LINES ON NON-ARTERIALS SHALL BE EITHER COPPER TUBING (TYPE K SOFT ANNEALED CONFORMING TO ASTM B 88) OR PEX TUBING (UPONOR AQUA PEX 5206 BLUE CONFORMING TO ASTM F876/F877/F2023), PEX TUBING IS NOT PERMITTED WITHIN ARTERIAL RIGHT OF WAY, WHEN CONTRACTOR ELECTS TO USE PEX TUBING:
 - NCH WATER SERVICE CONNECTION SHALL USE 1-INCH PEX TUBING MINIMUI B. 1-INCH WATER SERVICE CONNECTION SHALL USE 11/4-INCH PEX TUBING MINIMUM
- CONTRACTOR'S PLUMBER SHALL PROVIDE AN INFORMATIONAL BROCHURE TO THE PROPERTY OWNERS OUTLINING THE STEPS REQUIRED TO THOROUGHLY FLUSH THEIR WATERLINES AFTER CONNECTION TO THE NEW WATER MAIN. ALL COSTS TO PRODUCE AND DISTRIBUTE THE BROCHURE SHALL BE INCLUDED IN THE PRICE BID FOR THIS ITEM.

- THE "OWNER ALLOWANCE" CAN BE USED FOR VARIOUS WORK AND MISCELLANEOUS ITEMS NOT IDENTIFIED IN THE 18 CONTRACT DOCUMENTS WITH THE FOLLOWING PROVISIONS: THE ALLOWANCE SHALL BE USED FOR COST OF MATERIALS, LABOR. INSTALLATION AND OVERHEAD AND PROFIT FOR ADDITIONAL WORK AND MISCELLANEOUS ITEMS THAT ARE NOT IDENTIFIED IN THE CONSTRUCTION DOCUMENTS AND PLANS, AND NOT INCLUDED IN THE BID ITEMS OF THE CONTRACT 2
 - HE ALLOWANCE SHALL BE USED ONLY AT THE DISCRETION OF THE CITY. ANY ALLOWANCE BALANCE REMAINING AT THE COMPLETION OF THE PROJECT WILL BE CREDITED BACK TO THE CITY ON THE FINAL APPLICATION FOR PAYMENT SUBMITTED BY THE CONTRACTOR.
 - B. THE CONTRACTOR SHALL PROVIDE, TO THE CITY, A WRITTEN REQUEST FOR THE USE OF ANY ALLOWANCE, WITH A CHEDULE OF VALUES, AND ALL ASSOCIATED BACKUP INFORMATION, INCLUDING ANY TIME EXTENSIONS REQUIRED TO PERFORM THE WORK
 - C. THE CONTRACTOR SHALL PROCEED WITH THE WORK INCLUDED IN THE ALLOWANCE ONLY AFTER RECEIVING A WRITTEN ORDER, FROM THE ENGINEER AND CITY AUTHORIZING SUCH WORK. PROCEEDING WITH WORK IN THE ALLOWANCE WITHOUT A WRITTEN ORDER FROM THE CITY WILL BE AT THE CONTRACTOR'S EXPENSE

19. NOT USED

- 20. NOT USED
- 21. TOP OF VALVE BOX SHALL BE FLUSH WITH FINISHED GRADE
- 22. NOT USED
- 23. NOT USED
- SPOT ELEVATIONS ON THE MAIN WATER LINE RELATIVE TO FINISHED GRADE SHALL BE PROVIDED AT EACH 100-FT 24. INTERVAL, COMPLETE WITH STATION AND OFFSET. IN ADDITION, ALL VALVES, FITTINGS, FIRE HYDRANTS (TOP OF NUT) AND OTHER MAJOR APPURTENANT ITEMS SHALL BE SHOWN WITH THE PROPER DESCRIPTION, STATION, OFFSET AND **FI EVATION**
- 25. NOT USED
- 26. NOT USED
- PRESSURE TESTING AND CHLORINATION OF WATER MAINS SHALL NOT BE PERFORMED UNTIL THE CITY INSPECTOR HAS 27. RECEIVED REQUIRED CONSTRUCTION AS-BUILT RECORDS

WATERLINE PAY QUANTITIES

| ITEM NO | SPEC. NO | DESCRIPTION | PAYNOTES | UNIT | TOTAL QUANTITY |
|------------|----------|---|-----------------|-------|-------------------|
| 140 | COT 302 | EXCA VATION AND BACKFILL, UNCLASSIFIED | 14 | CY | 1,519 |
| 141 | COT 307 | 2 INCH DIP, CL 51 POLYETHYLENE WRA PPED (RJ) | 1,2,3,8,9,11,27 | LF | 20 |
| 142 | COT 307 | 6 INCH DIP, CL 51 POLYETHYLENE WRA PPED (RJ) | 1,2,3,8,9,11,27 | LF | 1,085 |
| 143 | COT 307 | 6 INCH DIP, CL 51 POLYETHYLENE WRA PPED | 1,2,3,9,11,27 | LF | 1,630 |
| 144 | COT 312 | 6 INCH DUCTILE IRON 11-1/4 DEGREE BEND (RJ) | 2,8,24 | EA | 12 |
| 145 | COT 312 | 6 INCH DUCTIL E IRON 22-1/2 DEGREE BEND (RJ) | 2,8,24 | EA | 12 |
| 146 | COT 312 | 6 INCH DUCTILE IRON 45 DEGREE BEND (RJ) | 2,8,24 | EA | 8 |
| 147 | COT 312 | 2 INCH DUCTILE IRON PLUG (RJ) | 2,8,24 | EA | 2 |
| 148 | COT 312 | 6 INCH DUCTILE IRON PLUG (RJ) | 2,8,24 | EA | 11 |
| 149 | COT 312 | 6 INCH X 6 INCH DUCTILE IRON TEE (RJ) | 2,8,24 | EA | 11 |
| 150 | COT 312 | 16 INCH X 6 INCH DUCTILE IRON TEE (RJ) | 2,8,24 | EA | 1 |
| 151 | COT 312 | 2 INCH DUCTILE IRON SLEEVE (RJ) | 2,8,12 | EA | 2 |
| 152 | COT 312 | 6 INCH DUCTILE IRON SLEEVE (RJ) | 2,8,12 | EA | 2 |
| 153 | COT 312 | 16 INCH DUCTILE IRON SLEEVE (RJ) | 2,8,12 | EA | 1 |
| 154 | COT 315 | PRIVATE SERVICE CONNECTION BY LICENSED BONDED PLUMBER | 13,17 | EA | 1 |
| 155 | COT 315 | 3/4 NCH WATER SERVICE CONNECTION (SHORT) | 15,16 | EA | 2 |
| 156 | COT 315 | 1 INCH WATER SERVICE CONNECTION (SHORT) | 15,16 | EA | 6 |
| 157 | COT 315 | 1 INCH WATER SERVICE CONNECTION (LONG) | 15,16 | EA | 4 |
| 158 | COT 315 | 1 INCH WATER METER CAN, LID & RIM | | EA | 12 |
| 159 | COT 317 | 6 INCH GATE VALVE (RJ) | 8 | EA | 7 |
| 160 | COT 317 | 6 INCH FIRE HY DRANT EXTENSION | | EA | 7 |
| 161 | COT 317 | 3-WAY FIREHYDRANT, IN PLACE | 24 | EA | 7 |
| 162 | COT 318 | VALVEBOX | 21,24 | EA | 7 |
| 163 | COT 318 | VALVE BOX EXTENSION | 21,24 | VF | 14 |
| 164 | SPECIAL | CONSTRUCTION AS-BUILT | 24 | EA | 1 |
| 165 | SPECIAL | OWNER ALLOWANCE | 18 | ALLOW | 1 |



- 5.
- PLANS.
- 7.
- 8.
 - INTERSECTION
- 10.
- 11.
- 12.
- 13. TRAFFIC UTILITY LOCATES
- 14.
- 15.
- PRIOR TO INSTALLATION



THIS

PX :59 2019 ຕູ້

WATERLINE CONSTRUCTION NOTES (09/24/2018)

THE CITY OF TULSA FIELD ENGINEERING DEPARTMENT SHALL INSPECT ALL TRENCHING, BEDDING, PIPE INSTALLATION, BACKFILL AND COMPACTION

ALL CONSTRUCTION AND MATERIALS SHALL BE IN ACCORDANCE WITH CURRENT STANDARD SPECIFICATIONS AND STANDARD DETAILS, CITY OF TULSA ENGINEERING SERVICES DEPARTMENT

EXISTING SERVICE CONNECTIONS ARE TO BE KEPT IN SERVICE UNTIL CONNECTIONS TO NEW MAIN ARE MADE. ALL SERVICE LINE RECONNECTIONS SHALL BE MADE BY THE CONTRACTOR. SERVICE RECONNECTIONS SHALL BE INSTALLED AS PER CITY OF TULSA STANDARD SPECIFICATIONS AND STANDARD DETAILS.

MINIMUM COVER OVER WATER LINES SHALL BE AS NOTED ON PLANS.

CONTRACTOR SHALL REPLACE EXISTING GRASS WITH SEED/SOD OF SAME TYPE AND VARIETY OR AS NOTED ON

CONTRACTOR SHALL BORE EXISTING TREES UNDER DRIP LINE, UNLESS DIRECTED OTHERWISE BY ENGINEER.

CONTRACTOR SHALL BORE EXISTING DRIVEWAYS. UNLESS DIRECTED OTHERWISE BY ENGINEER

WATER OPERATIONS SHALL OPERATE ALL VALVES ON TRANSMISSION MAINS (16" AND LARGER), CONTRACTOR SHALL OPERATE ALL VALVES ON DISTRIBUTION MAINS (SMALLER THAN 16") WITH THE COORDINATION OF FIELD ENGINEERING AND WATER OPERATIONS AND IN THE PRESENCE OF A FIELD ENGINEERING INSPECTOR.

a ATTEMPTS WILL BE MADE WITH ASSISTANCE FROM THE CONTRACTOR TO NOTIFY ALL AFFECTED CUSTOMERS 48-HOURS IN ADVANCE. PARTICULARLY IF COMMERCIAL OR INDUSTRIAL CUSTOMERS ARE INVOLVED. PRIOR TO SHUTDOWN, FIELD ENGINEERING WILL NOTIFY WATER OPERATIONS, AT 918-596-9488, GIVING AN ESTIMATED DOWNTIME. WATER OPERATIONS WILL NOTIFY THE FIRE DEPARTMENT OF ALL FIRE HYDRANTS OUT OF SERVICE AND WHEN THEY ARE BACK IN SERVICE, BY STREET ADDRESS OR

b. WHERE COMMERCIAL, INDUSTRIAL, OR CRITICAL CUSTOMERS ARE AFFECTED, AND FOR ALL LINES 16-INCH AND LARGER IN SIZE. FIELD ENGINEERING WILL REQUEST WATER OPERATIONS TO SHUT DOWN THE MAIN. THERE WILL BE A MINIMUM OF 48-HOUR NOTICE TO WATER OPERATIONS.

CONTRACTOR SHALL PROVIDE AT LEAST 48 HOUR NOTICE TO ALL RESIDENTS OR BUSINESSES AFFECTED BEFORE TURNING OFF ANY WATER. CONTRACTOR SHALL BE RESPONSIBLE FOR PLACING DOOR HANGERS ON AFFECTED HOMES AND BUSINESSES.

CONTRACTOR SHALL GIVE THE NOTIFICATION CENTER OF THE OKLAHOMA ONE-CALL SYSTEM, INC, NOTICE OF ANY EXCAVATION NO SOONER THAN 48 HOURS OR LATER THAN 10 DAYS, EXCLUDING SATURDAYS, SUNDAYS, FGAL HOLIDAYS PRIOR TO COMMENCEMENT OF WORK, PHONE 1-800-522-6543.

LOCAL AND THROUGH TRAFFIC SHALL BE MAINTAINED THROUGH PROJECT AT ALL TIMES. OPEN CUT STREET CROSSINGS REQUIRE AN APPROVED TRAFFIC CONTROL PLAN WITH TRAFFIC CONTROL DEVICES IN ACCORDANCE WITH CURRENT MUTCD REQUIREMENTS.

ANY DAMAGE CAUSED BY CONTRACTOR TO ADJACENT TRAFFIC SIGNAL INFRASTRUCTURE SHALL BE REPAIRED AT CONTRACTOR'S EXPENSE TO THE SATISFACTION OF THE TRAFFIC ENGINEER

PRIOR TO PAVEMENT SAWING AND EXCAVATION NEAR SIGNALIZED INTERSECTION, CONTRACTOR SHALL CONTACT ENGINEERING SERVICES, TRAFFIC OPERATIONS, 918-596-9766, FOR SITE SPECIFIC, UNDERGROUND

CONSTRUCTION FOR ALL ENGINEERING SERVICES FACILITIES SHALL BE IN COMPLIANCE WITH THE LATEST EDITION OF TITLE 252, DEPARTMENT OF ENVIRONMENTAL QUALITY, CHAPTER 626, PUBLIC WATER SUPPLY CONSTRUCTION STANDARDS, OKLAHOMA DEPARTMENT OF ENVIRONMENTAL QUALITY (ODEQ

ALL EXCAVATED MATERIAL NOT REQUIRED IN OTHER AREAS OF THE PROJECT SHALL BECOME THE PROPERTY OF THE CONTRACTOR AND SHALL BE DISPOSED OF BY THE CONTRACTOR IN A MANNER ACCEPTABLE TO THE ENGINEER WITHOUT COST TO THE CITY. THE CONTRACTOR SHALL BE REQUIRED TO OBTAIN AN EARTH CHANGE PERMIT IF ANY EXCESS MATERIAL IS TO BE DISPOSED OF WITHIN THE CITY LIMITS OF TUI SA.

ANY CHANGES FROM APPROVED PLANS SHALL BE SUBMITTED TO THE CITY OF TULSA FOR WRITTEN APPROVAL

| | | | EL | ELM CREEK WEST POND | | | | | | |
|----------|----|------|--------------------|----------------------------|-------|-------|----------------|-----|----|------|
| | | | PROJECT No. 148150 | | | | | | | |
| | | | (| WAT ITNAUQ | - • • | | E PAY & NOT | ES | | |
| | | | | Y OF T | | | | | | |
| | | | | UY ENGIN ST, TULSA OK 3 | | | | | | .COM |
| REVISION | BY | DATE | PLAN SCALE: | DRAWN | DGD | 01/19 | APPROVED | : | | |
| | | | N/A | DESIGNED | MZV | 01/19 | | | | |
| | | | | SURVEY | DMM | 09/18 | | | | |
| | | | PROFILE SCALE: | PROJ. MGR. | | | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | | | |
| | | | N/A | FIELD MGR. | | | | | | |
| | | | VERTICAL | RECOMMEND | DED: | | | | | |
| | | | N/A | DESIGN MAN | AGER | | CITY ENGIN | EER | | - |
| | | | | | | | DATE: | | | |
| | | | FILE: | DRAWI | NG: | | PAGE NO. | | | G06 |
| | | | ATLAS PAGE | NO: 01 & 08 | | | SHEET NO. | 07 | OF | 123 |

| SPEC. NO. | ITEM | UNIT | TOTAL | LINE A | LINE B | LINE C | LINE D |
|-----------|---|------|-------|--------|--------|--------|--------|
| COT 307 | 2 INCH DIP, CL51 POLY ETHYLENE WRAPPED (RJ) | LF | 20 | - | 10 | 10 | |
| COT 307 | 6 INCH DIP, CL51 POLY ETHYLENE WRAPPED (RJ) | LF | 1085 | 450 | 304 | 28 | 30 |
| COT 307 | 6 INCH DIP, CL51 POLY ETHYLENE WRAPPED | LF | 1630 | 676 | 456 | 43 | 45 |
| COT 312 | 6 INCH DUCTILE IRON 11-1/4 DEGREE BEND | EA | 12 | 4 | 2 | 4 | |
| COT 312 | 6 INCH DUCTILE IRON 22-1/2 DEGREE BEND | EA | 12 | 2 | 4 | 2 | |
| COT 312 | 6 INCH DUCTILE IRON 45 DEGREE BEND | EA | 8 | 2 | 2 | 2 | |
| COT 312 | 2 INCH DUCTILE IRON PLUG (RJ) | EA | 2 | | 1 | 1 | |
| COT 312 | 6 INCH DUCTILE IRON PLUG (RJ) | EA | 11 | 4 | 4 | 1 | |
| COT 312 | 6 INCH X 6 INCH DUCTILE IRON TEE (RJ) | EA | 11 | 4 | 2 | 1 | |
| COT 312 | 16 INCH X 6 INCH DUCTILE IRON TEE (RJ) | EA | 1 | 1 | | - | |
| COT 312 | 2 INCH DUCTILE IRON SLEEVE (RJ) | EA | 2 | - | 1 | 1 | |
| COT 312 | 6 INCH DUCTILE IRON SLEEVE (RJ) | EA | 2 | 1 | - | - | |
| COT 312 | 16 INCH DUCTILE IRON SLEEVE (RJ) | EA | 1 | 1 | - | - | |
| COT 315 | PRIVATE SERVICE CONNECTION BY LICENSED BONDED PLUMBER | EA | 1 | | 2 | - | |
| COT 315 | 3/4 INCH WATER SERVICE CONNECTION (SHORT) | EA | 2 | 1 | 1 | - | |
| COT 315 | 1 INCH WA TER SERVICE CONNECTION (SHORT) | EA | 6 | 1 | 4 | - | |
| COT 315 | 1 INCH WA TER SERVICE CONNECTION (LONG) | EA | 4 | 1 | 2 | - | |
| COT 315 | 1 INCH WA TER METER CAN, LID & RIM | EA | 12 | 3 | 7 | - | |
| COT 317 | 6 INCH GATE VALVE (RJ) | EA | 7 | 3 | 1 | - | |
| COT 317 | 6 INCH FIRE HYDRANT EXTENSION | EA | 7 | 3 | 1 | - | |
| COT 317 | 3-WAY FIRE HYDRANT, IN PLACE | EA | 7 | 3 | 1 | - | |
| COT 318 | VALVEBOX | EA | 7 | 3 | 1 | | |
| COT 318 | VALVE BOX EXTENSION | VF | 14 | 6 | 2 | | |

| WAS | WASTEWATER PAY QUANTITIES | | | | | | | | | | |
|------------|---------------------------|---------------------------------------|----------|------|-------------------|--|--|--|--|--|--|
| ITEM NO | SPEC. NO | DESCRIPTION | PAYNOTES | UNIT | TOTAL QUANTITY | | | | | | |
| 166 | 302 | EXCAVATION AND BACKFILL, UNCLASSIFIED | 1 | CY | 1,881 | | | | | | |
| 167 | 307(A) | 10" DIP, AWWA C151, CLASS 51 | | LF | 492 | | | | | | |
| 168 | 307(A) | 18" DIP, AWWA C151, CLASS 50 | | LF | 1,025 | | | | | | |
| 169 | 307(B) | 12" DIP, AWWA C151, CLASS 50 | | LF | 364 | | | | | | |
| 170 | 616(S) | 10" PLUG | | EA | 1 | | | | | | |
| 171 | 616(S) | 12" PLUG | | EA | 2 | | | | | | |
| 172 | 616(S) | 18" PLUG | | EA | 2 | | | | | | |
| 173 | COT 314 | 4' I.D. MANHOLE, COMPLETE IN PLACE | 101 | EA | 10 | | | | | | |
| 174 | COT 314 | ADD'L DEPTH IN MANHOLE | 102 | VF | 33 | | | | | | |
| 175 | 421 | MODIFICATION OF MANHOLE INVERT | | EA | 3 | | | | | | |

WASTEWATER PAY ITEM NOTES

- 1. IF BLASTING IS REQUIRED, IT SHALL BE DONE IN ACCORDANCE WITH THE CITY OF TULSA BLASTING ORDINANCE. ALL EXCAVATIONS SHALL BE PAID FOR AS UNCLASSIFIED EXCAVATION.
- 101. PAY ITEM INCLUDES MANHOLE RING, COVER, GROUT, SEALS, WATER-TIGHT LIDS.
- 102. ADDITIONAL DEPTH IN A MANHOLE SHALL BE MEASURED FROM 6FT AS MEASURED FROM THE TOP OF RIM TO THE LOWEST FLOWLINE.


WASTEWATER CONSTRUCTION NOTES

- 1. ALL CONSTRUCTION AND MATERIALS SHALL BE IN ACCORDANCE WITH THE OCTOBER, 2013, STANDARD SPECIFICATIONS AND STANDARD DRAWINGS FOR WATER AND WASTEWATER, CITY OF TULSA ENGINEERING SERVICES DEPARTMENT.
- 2. UTILITIES SHOWN HEREIN ARE INTENDED FOR INFORMATION PURPOSES ONLY AND ARE NOT TO BE CONSTRUED AS THE EXTENT OR EXACT LOCATION AND DEPTH OF UTILITIES THAT MAY BE ENCOUNTERED DURING THE COURSE OF CONSTRUCTION. THE CONTRACTOR SHALL FIELD VERIFY THE PRESENCE, TYPE, SIZE, LOCATION AND DEPTH OF ALL EXISTING UTILITIES IN THE PROJECT AREA PRIOR TO CONSTRUCTION.
- 3. CONTRACTOR SHALL GIVE THE NOTIFICATION CENTER OF THE OKLAHOMA ONE-CALL SYSTEM, INC. NOTICE OF ANY EXCAVATION NO EARLIER THAN TEN (10) DAYS, NOR LATER THAN 48 HOURS, EXCLUDING SATURDAYS, SUNDAYS, AND LEGAL HOLIDAYS, PRIOR TO COMMENCEMENT OF WORK. PHONE NUMBER IS 1-800-522-6543.
- 4. GEOTECHNICAL REPORT AVAILABLE FOR REVIEW AT THE OFFICE OF GUY ENGINEERING. NEITHER THE CITY OF TULSA OR GUY ENGINEERING. GUARANTEES THE ACCURACY OF THE SOIL CONDITIONS.
- 5. ALL EXCAVATED MATERIALS NOT REQUIRED IN OTHER AREAS OF THE PROJECT, INCLUDING PAVEMENT DEBRIS MATERIAL, SHALL BECOME PROPERTY OF THE CONTRACTOR AND SHALL BE DISPOSED OF BY THE CONTRACTOR IN A MANNER ACCEPTABLE TO THE ENGINEER WITHOUT COST TO THE CITY OF TULSA. THE CONTRACTOR SHALL BE REQUIRES TO OBTAIN AN EARTH CHANGE PERMIT IF ANY EXCESS MATERIAL IS TO BE DISPOSED OF WITHIN THE CITY LIMITS OF THE CITY OF TULSA.
- 6. ANY DAMAGE TO THE ROADWAY PAVEMENT CAUSED BY THE CONTRACTOR'S OPERATIONS SHALL BE REPAIRED TO THE ENGINEERS SATISFACTION AND SHALL BE ACCOMPLISHED AT THE CONTRACTOR'S SOLE EXPENSE.
- 7. FOR OPEN ROAD CUT, CONTRACTOR IS TO MAINTAIN ONE-WAY TRAFFIC. CONTRACTOR SHALL PRESENT A TRAFFIC CONTROL PLAN TO THE CITY OF TULSA FIELD ENGINEERING DIVISION.
- 8. CONSTRUCTION TRAFFIC CONTROL SHALL BE IN ACCORDANCE WITH THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD). THE CONTRACTOR SHALL WORK IN COOPERATION WITH THE CITY OF TULSA TO ESTABLISH, INSTALL, MAINTAIN, AND OPERATE COMPLETE, ADEQUATE AND SAFE TRAFFIC CONTROLS DURING THE ENTIRE CONSTRUCTION PERIOD. THE CONTRACTOR SHALL PLACE TRAFFIC CONTROL, FLAGMEN, BARRICADES AND SEVICES WITHIN THE VICINITY OF THE CONSTRUCTION AS REQUIRED. MAINTENANCE AND LIGHT CHECKS SHALL BE DONE WEEKLY AND INVOICE FURNISHED TO INSPECTOR AND SIGNED BY THE SUPERINTENDENT.
- 9. LOCAL AND THROUGH TRAFFIC SHALL BE MAINTAINED THROUGH THE PROJECT AT ALL TIMES. ALL PUBLIC STREETS SHALL BE ACCESSIBLE FOR TRAFFIC FROM ANY DETOUR DURING CONSTRUCTION OF THIS PROJECT.
- 10. CONTRACTOR SHALL VACUUM TEST ALL MANHOLES ACCORDING TO THE CITY OF TULSA, PUBLIC WORKS DEPARTMENT STANDARDS AND SPECIFICATIONS.
- 11. MANHOLES IN THE FLOOD PLAIN SHALL HAVE SEALED LIDS AND FRAMES.





ELM CREEK WEST POND **PROJECT No. 148150** WATERLINE SUMMARY & WASTEWATER PAY QUANTITIES & NOTES CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 918 437 0282 / WWW GUYENGR COM PLAN SCALE: DRAWN DGD 01/19 APPROVED: REVISION BY DATE DESIGNED MZV 01/19 N/A SURVEY DMM 09/18 ROFILE SCALE: PROJ. MGR. LEAD ENGR. RIZONTAL FIELD MGR. N/A RECOMMENDED: TICAL N/A DESIGN MANAGER CITY ENGINEER DATE: G07 FILE DRAWING PAGE NO ATLAS PAGE NO: 01 & 08 SHEET NO. 08 OF 123




sday, April 23, 2019 1:49:31 PM 16-1050E Elm Ck West Pond, 148150-1, COT\CIV3D\PLANS\1050-RON


| | | | OWNERSHIP TABLE | | |
|-----|-------|--|---|--|--|
| NO. | DOC | . NO. | OWNERSHIP | | |
| | BOOK | PAGE | IDENTIFICATION | | |
| | | | Not Used | | |
| | 20151 | 14560 | Maboto, LLC | | |
| | 20040 | 81560 | City of Tulsa | | |
| | 20041 | 40217 | David Taylor and Julie Taylor | | |
| | 6818 | 2409 | Anna J. Brundage | | |
| | 20140 | 89219 | Derold W. Wofford & Mark A. Woffard | | |
| | 5629 | 1371 | Wiltom Enterprises, L.L.C. | | |
| | 6828 | 1555 | Sokol Living Trust | | |
| | 20120 | 56309 | City of Tulsa | | |
| | 5923 | 123 | Lee F. Hamrick | | |
| | 6738 | 784 | Troy L. Imel | | |
| | 5390 | 255 | William Keith Miller | | |
| | 20081 | 04183 | The City of Tulsa, Oklahoma | | |
| | 20160 | 94854 | Tulsa Development Authority | | |
| | 6904 | 978 | Brightside Properties LLC | | |
| | 20161 | 21893 | Tulsa Development Authority Warranty Deed | | |
| | 20161 | 12127 | Matthew Tarvin and Gabriela Tarvin | | |
| | 4617 | 1184 | Richard L. Thomas | | |
| | 20070 | 22356 | Veterans of Foreign Wars Post 577 | | |
| | 20081 | 2008104183 The City of Tulsa, Oklahoma Quit Claim Deed | | | |
| | 20081 | 04183 | The City of Tulsa, Oklahoma Quit Claim Deed | | |
| | 20081 | 24004 | Good Day Properties, L.L.C. Special Warranty Deed | | |
| | 6461 | 2119 | Koenig Properties, Inc. | | |
| | 20160 | 17922 | Evanston Properties, L.L.C. General Warranty Deed | | |
| | 20161 | 20653 | Tulsa Development Authority Warranty Deed | | |
| | 5807 | 589 | Angelica Rodriguez | | |
| | 5767 | 906 | Martha K. Plank | | |
| | 20170 | 94829 | Matthew Presley | | |
| | 6407 | 1418 | Alberto Villegas | | |
| | 5997 | 375 | - | | |
| | 5997 | 375 | JDVB, Inc. | | |
| | | 04183 | The City of Tulsa, Oklahoma Quit Claim Deed | | |
| | 6916 | 2158 | Brightside Properties, LLC | | |
| | 5767 | 906 | Martha K. Plank | | |
| | 20110 | | Bryca Nikole Brewer, Trustee of the Brewer Family Irrevocable Trust | | |
| | 20150 | 04897 | Maynard Bernd Investments, LLC | | |
| | 4150 | 262 | Lewis Roach | | |
| | 6904 | 978 | Brightside Properties LLC | | |
| | 20130 | | Steve R. Lee | | |
| | 20070 | 57503 | Steve R. Lee | | |
| | 6904 | 978 | Brightside Properties LLC | | |
| | 20080 | 45405 | Live Well Properties, LLC | | |
| | 5808 | 968 | Phillip D. and Shian Morrow | | |
| | 20140 | 42185 | Zohra Eshtiba | | |
| | 4712 | 1417 | Steve Cowen | | |
| | 20060 | 71745 | Indian Health Care Resource Center | | |
| | 20060 | 71745 | Indian Health Care Resource Center | | |
| | | | | | |

| | | | | - | | | | | | | |
|----------|--|----|------|---|--|------|-------|------------|-----|----|------|
| | | | | EL | M CRE | Εŀ | < WI | EST P | ЭN | ID | |
| | THIS | | | | PROJECT No. 148150 | | | | | | |
| | DOCUMENT IS PRELIMINARY IN NATURE AND IS NOT A FINAL, | | | RIGHT-OF-WAY MAP | | | | | | | |
| 20' I | NOT A FIN SIGNED A SEALEI | ND | | | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | | | |
| | DOCUME | NT | | GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 918.437.0282 / WWW.GUYENGR.CO | | | | | | | .COM |
| R | VISION | BY | DATE | PLAN SCALE: | DRAWN | DGD | 01/19 | APPROVED | : | | |
| | | | | 1"=60' | DESIGNED | MZV | 01/19 | | | | |
| | | | | | SURVEY | DMM | 09/18 | | | | |
| | | | | PROFILE SCALE: | PROJ. MGR. | | | | | | |
| | | | | HORIZONTAL: | LEAD ENGR. | | | | | | |
| | | | | N/A | FIELD MGR. | | | | | | |
| | | | | VERTICAL | RECOMMENT | DED: | | | | | |
| | | | | N/A | DESIGN MAN | AGER | | CITY ENGIN | EER | | - |
| | | | | | | | | DATE: | | | |
| | | | | FILE: | DRAWING: PAGE NO. R1 | | | 10 | | | |
| | | | | ATLAS PAGE | ATLAS PAGE NO: 01 & 08 | | | SHEET NO. | 09 | OF | 123 |
| | | | | | | | | | | | |






| | BENCH | IMARK/C | ONTROL POINTS |
|----------|-------------|-----------|--|
| ORTHING | EASTING | ELEVATION | DESCRIPTION |
| 6163.495 | 2566079.919 | 697.08 | BM ~ CHISELED "X" ON CURB |
| 6173.355 | 2565607.488 | 692.07 | BM ~ CHISELED "X" ON SIDEWALK |
| 6163.358 | 2565257.482 | 685.71 | BM -80D NAIL IN POWER POLE |
| 5790.715 | 2565235.890 | 685.29 | BM - CHISELED BOX ON NE CORNER OF ELECTRIC BOX PAD |
| 5799.869 | 2564840.978 | 682.17 | BM - CHISELED "X" ON CURB |
| 6376.557 | 2564838.892 | 695.40 | BM - 80D NAIL IN POWER POLE |
| 6861.225 | 2564809.830 | 706.32 | BM - 80D NAIL IN POWER POLE |
| 6941.246 | 2565247.564 | 696.51 | BM - CHISELED BOX ON SIDEWALK |
| 6954.473 | 2565589.782 | 689.61 | BM - SW BOLT OF LIGHT POLE |
| 6857.709 | 2566113.142 | 704.84 | BM - TOP NUT OF FIRE HYDRANT |
| 6537.313 | 2566123.208 | 704.08 | BM - TOP NUT OF FIRE HYDRANT |
| 6184.986 | 2566054.730 | 697.63 | CP - 3/8" IP W/ ORANGE CAP |
| 6201.512 | 2565588.722 | 692.08 | CP - MAG NAIL |
| 6192.955 | 2565235.837 | 684.69 | CP - MAG NAIL |
| 6185.352 | 2564872.248 | 691.73 | CP - MAG NAIL |
| 6545.000 | 2564853.080 | 695.99 | CP - MAG NAIL |
| 6550.316 | 2565228.002 | 690.95 | CP - MAG NAIL |
| 6565.827 | 2565582.509 | 687.01 | CP - MAG NAIL |




| | | | | EL | M CRE | Εŀ | < WI | EST PO | ЛС | D | |
|----|--|----|------|---|--|------|-------|------------|-----------|----|-----------------|
| г | тше | | - | PROJECT No. 148150 | | | | | | | |
| | THIS DOCUMENT IS PRELIMINARY IN NATURE AND IS NOT A FINAL, SIGNED AND SEALED | | | SURVEY | SURVEY DATA - ALIGNMENT DATA SHEETS | | | | | | ETS |
| | | | | | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | | | |
| L | DOCUMENT | | | | GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 918.437.0282 / WWW.GUYENGR.COM | | | | | | |
| RE | VISION | BY | DATE | PLAN SCALE: | DRAWN | DGD | 01/19 | APPROVED | : | | |
| | | | | 1''=60' | DESIGNED | MZV | 01/19 | | | | |
| | | | | | | | | - | | | |
| | | | | | SURVEY | DMM | 09/18 | | | | |
| | | | | PROFILE SCALE: | | DMM | 09/18 | | | | |
| | | | | | PROJ. MGR. LEAD ENGR. | DMM | 09/18 | - | | | |
| | | | | PROFILE SCALE: | PROJ. MGR. LEAD ENGR. FIELD MGR. | | 09/18 | - | | | |
| | | | | PROFILE SCALE: HORIZONTAL: | PROJ. MGR. LEAD ENGR. | | 09/18 | | | | |
| | | | | PROFILE SCALE: HORIZONTAL: N/A | PROJ. MGR. LEAD ENGR. FIELD MGR. | DED: | | CITY ENGIN | EER | | _ |
| | | | | PROFILE SCALE: HORIZONTAL: N/A VERTICAL | PROJ. MGR. LEAD ENGR. FIELD MGR. RECOMMENE | DED: | | CITY ENGIN | EER | | _ |
| | | | | PROFILE SCALE: HORIZONTAL: N/A VERTICAL | PROJ. MGR. LEAD ENGR. FIELD MGR. RECOMMENE | DED: | | | EER | | - R11 |
| | | | | PROFILE SCALE: HORIZONTAL: N/A VERTICAL N/A | PROJ. MGR. LEAD ENGR. FIELD MGR. RECOMMENE DESIGN MAN | DED: | | DATE: | EER 10 | OF | - R11 123 |

120'



AN -:02 9:54 st P, 2019 Ck We 23, Elm





ELM CREEK WEST POND


PROJECT No. 148150

SITE PLAN

CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 918.437.0282 / WWW, GUYEN


THIS DOCUMENT IS PRELIMINARY IN NATURE AND IS NOT A FINAL, SIGNED AND SEALED DOCUMENT

| | | | 0010 2.11111 | 01, 1020/1010 | | 111.010. | | .0011 | | |
|----------|----|------|----------------|---------------|-------|----------|------------|-------|----|-----|
| REVISION | BY | DATE | PLAN SCALE: | DRAWN | DGD | 01/19 | APPROVED: | : | | |
| | | | 1''=60' | DESIGNED | MZV | 01/19 | | | | |
| | | | | SURVEY | DMM | 09/18 | | | | |
| | | | PROFILE SCALE: | PROJ. MGR. | | | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | | | |
| | | | N/A | FIELD MGR. | | | | | | |
| | | | VERTICAL | RECOMMEND | DED: | | | | | |
| | | | N/A | | | | | | | _ |
| | | | 14/7 | DESIGN MAN | IAGER | | CITY ENGIN | EER | | |
| | | | | | | | DATE: | | | |
| | | | FILE: | DRAWI | NG: | | PAGE NO. | | | R12 |
| | | | ATLAS PAGE | NO: 01 & 08 | | | SHEET NO. | 11 | OF | 123 |




Tuesday, April 23, 2019 10:34:33 AM V:\16-1050E Elm Ck West Pond, 148150-1, COT\CIV3D\PLANS\1050-GRADING PLAN MAIN.dw


| | | | 60' |) 1 incl 0 | HORI | 60'ft 60 | 120' | | |
|----------|-----|------|--------------------------|--------------------------|---------------|------------------|---|--|--|
| RE | Yo. | | | | | | EST POND . 148150 | | |
| | | OIG | GRADING PLAN OVER-ALL | | | | | | |
| CALL | OKI | ų | | | | | OKLAHOMA S DEPARTMENT | | |
| | | | G 6910 E. 14TH | UY ENGIN ST, TULSA OK | EER 74112/ | ING S PH: 918 | ERVICES, INC. 437.0282 / WWW.GUYENGR.COM | | |
| REVISION | BY | DATE | PLAN SCALE: 1''=60' | DESIGNED | MZV | 01/19 01/19 | APPROVED: | | |
| | _ | | PROFILE SCALE: | SURVEY PROJ. MGR. | DWW | 01/19 | - | | |
| | - | | HORIZONTAL: | LEAD ENGR. | | | | | |
| | | | N/A VERTICAL | FIELD MGR. RECOMMENE | DED: | | - | | |
| | - | | N/A | DESIGN MAN | AGER | | CITY ENGINEER | | |
| | | | | - SECICIT MAN | | | DATE: | | |
| | | | FILE: | DRAWI | NG: | | PAGE NO. C10 | | |
| | | | ATLAS PAGE | NO: 01 & 08 | | | SHEET NO. 12 OF 123 | | |








uesday, April 23, 2019 10:50:43 AM :\16-1050E Elm Ck West Pond, 148150-1, COT\CIV3D\PLANS\1050-GRADING PLAN SET.dw,





AM 148 2019 10:53:46 Ck West Pond, 23, Elm April 50E






| | | | EL | M CRE | EEł | < WE | EST POND | | | | |
|------------|------------------------|--|----------------|----------------|---|--------------------|---------------|--|--|--|--|
| | $\overline{\ }$ | | | PROJE | EC | T No. | 148150 | | | | |
| NOT FOR | PRELIMINARY PLANS | | | | | HARDSCAPE KEY PLAN | | | | | |
| CONSTRUCTI | | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | | | | | | |
| | | | | | ALABACK DESIGN ASSOCIATES 3202 E. 21ST ST, TULSA OK 74114 PH: 918.742.1463 | | | | | | |
| REVISION | BY | DATE | PLAN SCALE: | DRAWN | BC | 4/26/19 | APPROVED: | | | | |
| | | | AS SHOWN | DESIGNED | MP | 4/26/19 | | | | | |
| | | | | SURVEY | | | | | | | |
| | | | PROFILE SCALE: | PROJ. MGR. | | | | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | | | | |
| | | | | FIELD MGR. | | | | | | | |
| | | | VERTICAL | RECOMMEND | DED: | | | | | | |
| | | | 1 | DESIGN MAN | IAGEF | 2 | CITY ENGINEER | | | | |
| | | | | | | | DATE: | | | | |
| | | | | FILE: DRAWING: | | | PAGE NO. L10 | | | | |
| | ATLAS PAGE NO: 01 & 08 | | | | SHEET NO. 16 OF 123 | | | | | | |





Friday, April 19, 2019 2:00:29 PM Z:\Public & Park\Elm Creek Detention + West Pond\Elm Creek − 6th St. West Pond C0T #17001\Drawings\HSP 1:



00 COT Ne ۍ. ŝħ Creek West + 19, 2019 2:00:30 PM Park\Elm Creek Deten April lic &

|) | |
|---------------------|--|
| I CONCRETE SUB-SLAB | |
| AINT | |
| | |
| | |
| | SITE FURNISHINGS LEGEND |
| | 6' BENCH (DETAIL A/ SHT. L23) |
| VGS | BIKE RACK (DETAIL B/ SHT. L23) |
| W) | LITTER RECEPTACLE (DETAIL C/ SHT. L23) |

CONTACT 811 PRIOR TO DIGGING. CONTRACTOR SHALL BE RESPONSIBLE FOR ANY DAMAGE CAUSED TO THE UTILITIES (BOTH OVERHEAD AND BURIED) WHICH MAY OCCUR DUE TO HIS ACTION OR LACK THEREOF ON THE PROJECT SITE DURING CONSTRUCTION OPERATIONS. CONTRACTOR SHALL SEEK THE ASSISTANCE OF LOCAL UTILITIES AND THE CITY OF TULSA IN LOCATING THE UTILITIES PRIOR TO PERFORMING DIGGING/TRENCHING OPERATIONS IN ANY AREA.


PROVIDE SCHEDULE 40 PVC IRRIGATION SLEEVES BELOW PAVEMENT AS SHOWN. IRRIGATION SLEEVES ARE TO HAVE 18" MIN. COVER. EXTEND SLEEVES 18" MIN. BEYOND EDGE OF PAVEMENT INTO LANDSCAPE AREAS, AND CAP UNTIL READY FOR IRRIGATION INSTALLATION. MARK LOCATIONS WITH FLAGS AND / OR 2" X 2" BLUE PAINT ON EDGE OF PAVING SLAB. PRIOR TO PAVEMENT INSTALLATION, ENSURE THAT ALL IRRIGATION SLEEVES, ELECTRICAL CONDUITS, UTILITY LINES, AND ALL OTHER UNDERGROUND WORK IS COMPLETE. FOR HARDSCAPING LAYOUT, UTILIZE DIMENSIONS PROVIDED ON THE PLANS. DIMENSIONS ARE PERPENDICULAR / PARALLEL TO FACE OF

WALLS AS SHOWN. REFER TO CIVIL DRAWINGS FOR PROPOSED GRADING / ELEVATIONS FOR SIDEWALKS AND VEHICULAR PAVING. CLOSELY COORDINATE

REFER TO CIVIL DRAWINGS FOR PROPOSED GRADING FELEVATIONS FOR SIDEWALKS AND VEHICULAR PAVING. CLOSELY COORDINATE SIDEWALK ELEVATIONS WITH CURBS, DRIVES, WALLS, ETC. REFER TO CIVIL PLANS FOR LOCATIONS OF SIGNS, ETC. THAT ARE LOCATED IN SIDEWALK AREAS. ENSURE THAT ALL FOOTINGS AND UNDERGROUND WORK ARE COMPLETED PRIOR TO NEW SIDEWALK CONSTRUCTION. REFER TO ELECTRICAL DRAWINGS FOR LOCATIONS OF NEW PEDESTRIAN LIGHT POLES. ENSURE THAT FOOTINGS, CONDUITS AND ALL

UNDERGROUND UTILITY WORK IS COMPLETED PRIOR TO NEW SIDEWALK CONSTRUCTION. ELECTRICAL CONDUITS SHOWN ARE APPROXIMATE ONLY - ADJUST AS NEEDED AND PROVIDE ALL OTHER SLEEVES AS REQUIRED FOR ELECTRICAL / LIGHTING WORK. NOT ALL SLEEVES ARE SHOWN - REFER TO ELECTRICAL PLANS/ SPECIFICATIONS.

| | | | EL | M CRE | Eŀ | < WE | EST PON | D | | | |
|----------|-------------------|------|----------------|---|-----------------------|---------------------------|---------------|-------|---|--|--|
| | $\overline{\ }$ | | | PROJE | ECT | ΓNo. | 148150 | | | | |
| NOT FOR | PRELIMINARY PLANS | | | | | HARDSCAPE LAYOUT PLAN - C | | | | | |
| | | | | | OKLAHON DEPARTMENT | 1A | | | | | |
| | | | | ALABACK DESIGN ASSOCIATES 3202 E. 21ST ST, TULSA OK 74114 PH: 918.742.1463 | | | | | | | |
| REVISION | ΒY | DATE | PLAN SCALE: | DRAWN | BC | 4/26/19 | APPROVED: | | | | |
| | | | AS SHOWN | DESIGNED | MP | 4/26/19 | | | | | |
| | | | | SURVEY | | | | | | | |
| | | | PROFILE SCALE: | PROJ. MGR. | | | | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | | | | |
| | | | | FIELD MGR. | | | | | | | |
| | | | VERTICAL | RECOMMEND | ED: | | | | | | |
| | | | | DESIGN MAN | AGER | 1 | CITY ENGINEER | | | | |
| | | | | | | | DATE: | | | | |
| | | | FILE: | DRAWI | NG: | | PAGE NO. L13 | | | | |
| | | | ATLAS PAGE | NO: 01 & 08 | | | SHEET NO. 19 | OF 12 | 3 | | |



2019 2:00:31 PM k∖Elm Creek Detent à,

| R | SCAPE LEGEND | | |
|-------|---------------------------------------|-------|--|
| _ | rem | | |
| С | ONCRETE SIDEWALK | | |
| C | ONCRETE PAVERS WITH CONCRETE SUB-SLAB | | |
| c | ONCRETE EDGE RESTRAINT | | |
| 4 | 2" HT. RAILING | | |
| Р | EDESTRIAN LIGHT | | |
| В | OARDWALK/ DECKING | | |
| C | VERLOOK/ DECKING | | URNISHINGS LEGEND |
| R | AISED PLANTER WALL | SILEF | URNISHINGS LEGEND |
| C | ONCRETE STAIRS | | 6' BENCH (DETAIL A/ SHT. L23) |
|] L | ANDSCAPE BED/ PLANTINGS | | BIKE RACK (DETAIL B/ SHT. L23) |
|] L | AWN AREA | | , , , , , , , , , , , , , , , , , , , |
|] s | ITE RETAINING WALL (SRW) | | LITTER RECEPTACLE (DETAIL C/ SHT. L23) |

HARDSCAPE NOTES

CONTACT 811 PRIOR TO DIGGING. CONTRACTOR SHALL BE RESPONSIBLE FOR ANY DAMAGE CAUSED TO THE UTILITIES (BOTH OVERHEAD AND BURIED) WHICH MAY OCCUR DUE TO HIS ACTION OR LACK THEREOF ON THE PROJECT SITE DURING CONSTRUCTION OPERATIONS. CONTRACTOR SHALL SEEK THE ASSISTANCE OF LOCAL UTILITIES AND THE CITY OF TULSA IN LOCATING THE UTILITIES PRIOR TO PERFORMING DIGGING/TRENCHING OPERATIONS IN ANY AREA.


PROVIDE SCHEDULE 40 PVC IRRIGATION SLEEVES BELOW PAVEMENT AS SHOWN. IRRIGATION SLEEVES ARE TO HAVE 18" MIN. COVER. EXTEND SLEEVES 18" MIN. BEYOND EDGE OF PAVEMENT INTO LANDSCAPE AREAS, AND CAP UNTIL READY FOR IRRIGATION INSTALLATION. MARK LOCATIONS WITH FLAGS AND / OR 2" X 2" BLUE PAINT ON EDGE OF PAVING SLAB. PRIOR TO PAVEMENT INSTALLATION, ENSURE THAT ALL IRRIGATION SLEEVES, ELECTRICAL CONDUITS, UTILITY LINES, AND ALL OTHER UNDERGROUND WORK IS COMPLETE.

FOR HARDSCAPING LAYOUT, UTILIZE DIMENSIONS PROVIDED ON THE PLANS. DIMENSIONS ARE PERPENDICULAR / PARALLEL TO FACE OF WALLS AS SHOWN.


REFER TO CIVIL DRAWINGS FOR PROPOSED GRADING / ELEVATIONS FOR SIDEWALKS AND VEHICULAR PAVING. CLOSELY COORDINATE SIDEWALK ELEVATIONS WITH CURBS, DRIVES, WALLS, ETC.

REFER TO CIVIL PLANS FOR LOCATIONS OF SIGNS, ETC. THAT ARE LOCATED IN SIDEWALK AREAS. ENSURE THAT ALL FOOTINGS AND UNDERGROUND WORK ARE COMPLETED PRIOR TO NEW SIDEWALK CONSTRUCTION. REFER TO ELECTRICAL DRAWINGS FOR LOCATIONS OF NEW PEDESTRIAN LIGHT POLES. ENSURE THAT FOOTINGS, CONDUITS AND ALL UNDERGROUND UTILITY WORK IS COMPLETED PRIOR TO NEW SIDEWALK CONSTRUCTION. ELECTRICAL CONDUITS SHOWN ARE APPROXIMATE ONLY - ADJUST AS NEEDED AND PROVIDE ALL OTHER SLEEVES AS REQUIRED FOR ELECTRICAL / LIGHTING WORK. NOT ALL SLEEVES ARE SHOWN - REFER TO ELECTRICAL PLANS/ SPECIFICATIONS.

| | | EL | M CRE | Eŀ | < WE | ELM CREEK WEST POND | | | | | | |
|--|---|----------------|--|------|--------------|---------------------|--|--|--|--|--|--|
| | | | PROJECT No. 148150 | | | | | | | | | |
| 60% PRELIMINARY PLAN NOT FOR CONSTRUCTION | IS | | HARDSCAPE LAYOUT PLAN - D | | | | | | | | | |
| | | | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | | | | | | |
| | ALABACK DESIGN ASSOCIATES 3202 E. 21ST ST, TULSA OK 74114 PH: 918.742.1463 | | | | | | | | | | | |
| REVISION BY | DATE | PLAN SCALE: | DRAWN | BC | 4/26/19 | APPROVED: | | | | | | |
| | | AS SHOWN | DESIGNED | MP | 4/26/19 | | | | | | | |
| | | | SURVEY | | | | | | | | | |
| | | PROFILE SCALE: | PROJ. MGR. | | | | | | | | | |
| | | HORIZONTAL: | LEAD ENGR. | | | | | | | | | |
| | | 1 | FIELD MGR. | | | | | | | | | |
| | | VERTICAL | RECOMMEND | DED: | | | | | | | | |
| | | | DESIGN MAN | AGER | . | CITY ENGINEER | | | | | | |
| | | | | | | DATE: | | | | | | |
| | | | | NG: | | PAGE NO. L14 | | | | | | |
| | ATLAS PAGE NO: 01 & 08 | | | | SHEET NO. 20 | OF 123 | | | | | | |











ò # COT West ŗ. ŝħ - Ľ Vest 2019 2:00:32 PM CEIm Creek Deter 19, Dark Friday, April Z:\Public & F

| | HAF | RDSCAPE LEGEND |
|--|-----|--|
| | KEY | ITEM |
| | 1 | CONCRETE SIDEWALK |
| | 2 | CONCRETE PAVERS WITH CONCRETE SUB-SLAB |
| | 3 | CONCRETE EDGE RESTRAINT |
| | 4 | 42" HT. RAILING |
| | 5 | PEDESTRIAN LIGHT |
| | 6 | BOARDWALK/ DECKING |
| URNISHINGS LEGEND | 7 | OVERLOOK/ DECKING |
| UKNISHINGS LEGEND | 8 | RAISED PLANTER WALL |
| 6' BENCH (DETAIL A/ SHT. L23) | 9 | CONCRETE STAIRS |
| BIKE RACK (DETAIL B/ SHT. L23) | 10 | LANDSCAPE BED/ PLANTINGS |
| | 11 | LAWN AREA |
| LITTER RECEPTACLE (DETAIL C/ SHT. L23) | 12 | SITE RETAINING WALL (SRW) |

HARDSCAPE NOTES


CONTACT 811 PRIOR TO DIGGING. CONTRACTOR SHALL BE RESPONSIBLE FOR ANY DAMAGE CAUSED TO THE UTILITIES (BOTH OVERHEAD AND BURIED) WHICH MAY OCCUR DUE TO HIS ACTION OR LACK THEREOF ON THE PROJECT SITE DURING CONSTRUCTION OPERATIONS. CONTRACTOR SHALL SEEK THE ASSISTANCE OF LOCAL UTILITIES AND THE CITY OF TULSA IN LOCATING THE UTILITIES PRIOR TO PERFORMING DIGGING/TRENCHING OPERATIONS IN ANY AREA. PROVIDE SCHEDULE 40 PVC IRRIGATION SLEEVES BELOW PAVEMENT AS SHOWN. IRRIGATION SLEEVES ARE TO HAVE 18" MIN. COVER. EXTEND SLEEVES 18" MIN. BEYOND EDGE OF PAVEMENT INTO LANDSCAPE AREAS, AND CAP UNTIL READY FOR IRRIGATION INSTALLATION. MARK LOCATIONS WITH FLAGS AND / OR 2" X 2" BLUE PAINT ON EDGE OF PAVING SLAB. PRIOR TO PAVEMENT INSTALLATION, ENSURE THAT ALL IRRIGATION SLEEVES, ELECTRICAL CONDUITS, UTILITY LINES, AND ALL OTHER UNDERGROUND WORK IS COMPLETE.


FOR HARDSCAPING LAYOUT, UTILIZE DIMENSIONS PROVIDED ON THE PLANS. DIMENSIONS ARE PERPENDICULAR / PARALLEL TO FACE OF WALLS AS SHOWN.


REFER TO CIVIL DRAWINGS FOR PROPOSED GRADING / ELEVATIONS FOR SIDEWALKS AND VEHICULAR PAVING. CLOSELY COORDINATE SIDEWALK ELEVATIONS WITH CURBS, DRIVES, WALLS, ETC. REFER TO CIVIL PLANS FOR LOCATIONS OF SIGNS, ETC. THAT ARE LOCATED IN SIDEWALK AREAS. ENSURE THAT ALL FOOTINGS AND UNDERGROUND WORK ARE COMPLETED PRIOR TO NEW SIDEWALK CONSTRUCTION.

REFER TO ELECTRICAL DRAWINGS FOR LOCATIONS OF NEW PEDESTRIAN LIGHT POLES. ENSURE THAT FOOTINGS, CONDUITS AND ALL UNDERGROUND UTILITY WORK IS COMPLETED PRIOR TO NEW SIDEWALK CONSTRUCTION. ELECTRICAL CONDUITS SHOWN ARE APPROXIMATE ONLY - ADJUST AS NEEDED AND PROVIDE ALL OTHER SLEEVES AS REQUIRED FOR ELECTRICAL / LIGHTING WORK. NOT ALL SLEEVES ARE SHOWN - REFER TO ELECTRICAL PLANS/ SPECIFICATIONS.

| | | | EL | M CRE | Eŀ | < WE | EST PON | ID | | |
|--|---|------------|--|--------------------|------|--------------|---------------|----|--|--|
| | $\overline{\ }$ | | | PROJECT No. 148150 | | | | | | |
| 60% PRELIMINARY PI NOT FOR CONSTRUCTION | | | HARDSCAPE LAYOUT PLAN - E | | | | | | | |
| CONSTRUCTION | / | | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | | | | |
| | ALABACK DESIGN ASSOCIATES 3202 E. 21ST ST, TULSA OK 74114 PH: 918.742.1463 | | | | | | | | | |
| REVISION | BY | DATE | PLAN SCALE: | DRAWN | BC | 4/26/19 | APPROVED: | | | |
| | | | AS SHOWN | DESIGNED | MP | 4/26/19 | | | | |
| | | | | SURVEY | | | | | | |
| | | | PROFILE SCALE: | PROJ. MGR. | | | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | | | |
| | | | | FIELD MGR. | | | | | | |
| | | | VERTICAL | RECOMMEND | ED: | | | | | |
| | | | | DESIGN MAN | AGER | 2 | CITY ENGINEER | | | |
| | | | | | | | DATE: | | | |
| | | | FILE: DRAWING: PAGE NO. L15 | | | | | | | |
| | | ATLAS PAGE | NO: 01 & 08 | | | SHEET NO. 21 | OF 123 | | | |








B FISHING DOCK AREA - LAYOUT PLAN SCALE: 1"=10'-0"

REFER TO SHEET L11 FOR HARDSCAPE NOTES


SITE FURNISHINGS LEGEND


6' BENCH (DETAIL A/ SHT. L23) BIKE RACK (DETAIL B/ SHT. L23) LITTER RECEPTACLE (DETAIL C/ SHT. L23)






gs∖HSP #17001\[сот Vest ÷. Μ. 2:32:34 Creek De 2019 k\Elm 19, Park April lic & Friday,







т. Vest PM 2:00:37 | Creek De 2019 19, April Nic & lay,

| | | | ELM CREEK WEST POND | | | | | | | |
|-----------------------|---------------|------|---------------------|--|-------|---------|-----------------------------------|--|--|--|
| | | | | PROJE | EC | ΓNo. | 148150 | | | |
| PRELIMINARY NOT FC | Y PLANS DR | | SI | TE C | ETAIL | S - C | | | | |
| CONSTRUCTION | | | | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | | | |
| | | | | | | | SSOCIATES 4 PH: 918.742.1463 | | | |
| REVISION | BY | DATE | PLAN SCALE: | DRAWN | BC | 4/26/19 | APPROVED: | | | |
| | | | AS SHOWN | DESIGNED | MP | 4/26/19 | | | | |
| | | | | SURVEY | | | | | | |
| | | | PROFILE SCALE: | PROJ. MGR. | | | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | | | |
| | | | 1 | FIELD MGR. | | | | | | |
| | | | VERTICAL | RECOMMEND | JED: | | | | | |
| | | | | DESIGN MAN | AGEF | 2 | CITY ENGINEER | | | |
| | | | | | | | DATE: | | | |
| | | | FILE: | DRAWI | NG: | | PAGE NO. L22 | | | |
| | | | ATLAS PAGE | NO: 01 & 08 | | | SHEET NO. 28 OF 123 | | | |


- REFER TO STRUCTURAL DRAWINGS (TYP.)

CAST IN PLACE WALL. (PER STRUCTURAL DETAILS)


DRAINAGE (REFER TO GRADING PLAN) 4" THICK CONCRETE SUB-SLAB WITH #3'S. 18" O.C. EACH WAY

CROSS-SLOPE TOWARD POND FOR

- 1/2" EXPANSION JOINT WITH POLYURETHANE SEALANT - 1/2" DIA. X 10" STEEL DOWEL, 24" O.C.



| | | | ELM CREEK WEST POND | | | | | | |
|--|-----------------|----------|---|------------|-----------|---------|---------------|--------|--|
| | $\overline{\ }$ | | | PROJE | ECT | ۲No. | 148150 | | |
| 60% PRELIMINARY PL NOT FOR CONSTRUCTION | | SITE FU | RNIS | SHING | S DETAILS | | | | |
| | | / | CIT | Y OF T | UL | SA, (| OKLAHON | ΛA | |
| | | / | | | | | DEPARTMENT | | |
| | | | ALABACK DESIGN ASSOCIATES 3202 E. 21ST ST, TULSA OK 74114 PH: 918.742.1463 | | | | | | |
| REVISION | BY | DATE | PLAN SCALE: | DRAWN | BC | 4/26/19 | APPROVED: | | |
| | | | AS SHOWN | DESIGNED | MP | 4/26/19 | | | |
| | | | | SURVEY | | | | | |
| | | | PROFILE SCALE: | PROJ. MGR. | | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | | |
| | | | | FIELD MGR. | | | | | |
| | | VERTICAL | RECOMMEND | ED: | | | | | |
| | | | | DESIGN MAN | AGER | | CITY ENGINEER | | |
| | | | | | | | DATE: | | |
| | | | FILE: | DRAWI | NG: | | PAGE NO. L23 | | |
| | | | ATLAS PAGE NO: 01 & 08 | | | | SHEET NO. 29 | OF 123 | |
| | | | | | | | | | |




PM 2:00:39 | Creek De 19, 2019 : Park\Elm (April lic & Ś.

| GPM ONTACT: | |
|----------------|--|
| | |

| | $\overline{\ }$ | | PROJECT No. 148150 | | | | | | | | |
|--|-----------------|------|---|-------------|------|---------|---------------|--------|--|--|--|
| 60% PRELIMINARY PL NOT FOR CONSTRUCTION | | | AERATING FOUNTAIN DETAILS CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | | | | | |
| | | | ALABACK DESIGN ASSOCIATES 3202 E. 21ST ST, TULSA OK 74114 PH: 918.742.1463 | | | | | | | | |
| REVISION | BY | DATE | PLAN SCALE: | DRAWN | BC | 4/26/19 | APPROVED: | | | | |
| | | | AS SHOWN | DESIGNED | MP | 4/26/19 | | | | | |
| | | | | SURVEY | | | | | | | |
| | | | PROFILE SCALE: | PROJ. MGR. | | | | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | | | | |
| | | | | FIELD MGR. | | | | | | | |
| | | | VERTICAL | RECOMMEND | ED: | | | | | | |
| | | | | DESIGN MAN | AGER | 1 | CITY ENGINEER | | | | |
| | | | | | | | DATE: | | | | |
| | | | FILE: | DRAWI | NG: | | PAGE NO. L24 | | | | |
| | | | ATLAS PAGE | NO: 01 & 08 | | | SHEET NO. 30 | OF 123 | | | |
| | | | | | | | | | | | |

ELM CREEK WEST POND



Friday, April 19, 2019 2:00:42 PM Z:\Public & Park\Elm Creek Detention + West Pond\Elm Creek - 6th St. West Pond COT #17001\Drawings\LSP 17\

| PLANT S | PLANT SCHEDULE | | | | | | | | | | | | |
|---------------|------------------|--|-------------------------------|-------------|---------------|--|----------------------------------|--|--|--|--|--|--|
| TREES MSSM | <u>QTY</u> 30 | BOTANICAL NAME Acer truncatum `Main Street` | COMMON NAME Shantung Maple | CONT B&B | CAL 3" CAL | <u>SIZE</u> 12`-14` HT.; 4`-5` SPD. | COMMENTS CENTRAL LEADER, FULL | | | | | | |
| GINKGO | 16 | Ginkgo biloba `Princeton Sentry` | Princeton Sentry Ginkgo | B&B | 3" CAL | 12`-14` HT.; 3`-4` SPD. | CENTRAL LEADER, FULL | | | | | | |
| ECTULIP | 18 | Liriodendron tulipifera `Emerald city` | Emerald City Tulip Tree | B&B | 3" CAL | 12`-14` HT.; 4`-5` SPD. | CENTRAL LEADER, FULL | | | | | | |
| SWOAK | 17 | Quercus bicolor | Swamp White Oak | B&B | 3" CAL | 12`-14` HT.; 4`-5` SPD. | CENTRAL LEADER, FULL | | | | | | |
| NOAK | 22 | Quercus nuttallii | Nuttall Oak | B&B | 3" CAL | 12`-14` HT.; 4`-5` SPD. | CENTRAL LEADER, FULL | | | | | | |
| AGBC | 37 | Taxodium distichum `Autumn Gold` | Autumn Gold Bald Cypress | B&B | 3" CAL | 12`-14` HT.; 4`-5` SPD. | CENTRAL LEADER | | | | | | |
| SBBC | 14 | Taxodium distichum `Shawnee Brave` | Shawnee Brave Bald Cypress | B&B | 3" CAL | 12`-14` HT.; 3`-4` SPD. | FULL CANOPY | | | | | | |
| AELM | 20 | Ulmus parvifolia `Allee` | Allee Lacebark Elm | B&B | 3" CAL | 12`-14` HT.; 4`-5` SPD. | CENTRAL LEADER, FULL | | | | | | |


SHRUBS, GROUNDCOVER, ORNAMENTAL GRASSES, & PERENNIALS

FINAL LANDSCAPE PLANS WILL INCLUDE A DETAILED LAYOUT OF ALL AREAS THAT ARE IDENTIFIED ON 60% PLANS FOR LANDSCAPE PLANTINGS. FINAL PLANS WILL INCLUDE SPECIFIC PLANT VARIETIES, SIZES AND QUANTITIES. THE FOLLOWING LIST DESCRIBES POTENTIAL PLANT VARIETIES THAT MAY BE USED FOR SPECIFIC AREAS:

PLAZA LEVEL PLANTERS: GROUNDCOVER PLANTING: EVERGREEN WINTERCREEPER (EUONYMUS FORTUNEI 'COLORATUS').

RAISED PLANTERS: POTENTIAL PLANT TYPES INCLUDE BLACK HELLERI HOLLY; ROSE CREEK ABELIA; DWARF YAUPON HOLLY; GRAY OWL JUNIPER; GREY GUARDIAN JUNIPER; BUFFALD JUNIPER; KARL FOERSTER FEATHER REED GRASS; PINK MUHLY GRASS; DAYLILLY; BLACK EYED SUSAN; AND LIRIOPE.

MID-LEVEL PLANTING TERRACE: THIS PLANTING AREA WILL BE PLANTED WITH WATER-TOLERANT PLANTS THAT WILL ARE ADAPTED TO POTENTIAL PERIODS OF FLOODING. POTENTIAL PLANT VARIETIES INCLUDE ITEA; SHENANDOAH SWITCH GRASS; AND HEAVY METAL SWITCH GRASS.



LANDSCAPE NOTES

CALL 811 FOR INFORMATION ON THE LOCATION OF UNDERGROUND UTILITIES PRIOR TO DIGGING. CONTRACTOR SHALL BE RESPONSIBLE FOR ANY DAMAGE TO THE UTILITIES (BOTH OVERHEAD AND BURIED) WHICH MAY OCCUR DUE TO HIS ACTION OR LACK OF ACTION ON THE PROJECT SITE DURING CONSTRUCTION. CONTRACTOR SHALL SEEK THE ASSISTANCE OF LOCAL UTILITIES AND THE OWNER IN LOCATING THE UTILITIES PRIOR TO PERFORMING LANDSCAPING OPERATIONS.

LANDSCAPE CONTRACTOR SHALL BE RESPONSIBLE FOR ANY DAMAGE CAUSED TO STRUCTURES, WALLS, PAVING, AND ANY OTHER ITEMS LOCATED WITHIN AND OUTSIDE THE WORK AREA. ANY DAMAGE BY THE CONTRACTOR SHALL BE REPAIRED TO ORIGINAL CONDITION AT HIS OWN EXPENSE.

REFER TO LANDSCAPING SPECIFICATIONS FOR INSTALLATION OF TREES, SHRUBS, AND ALL OTHER PLANTS. PLANT TREES TWO (2) INCHES ABOVE FINISHED GRADE. CUT TWINE FROM AROUND THE TRUNK AND COMPLETELY REMOVE THE TOP 1/3 OF THE WIRE BASKET AND BURLAP FROM THE ROOT BALL. CAREFULLY REMOVE ANY EXCESS SOIL ON TOP OF ROOT BALL TO EXPOSE THE ROOT FLARES. PLANT SHRUBS ONE (1) INCH ABOVE FINISHED GRADE.

CONTRACTOR TO FIELD VERIFY EXISTING CONDITIONS. FIELD ADJUST TREE LOCATIONS FOR, UTILITIES, LIGHTS, SIGNAGE, ETC. CONTRACTOR SHALL FLAG LOCATIONS OF ALL TREES. LANDSCAPE ARCHITECT WILL FIELD REVIEW ALL TREE LOCATIONS PRIOR TO DIGGING TREE PITS.

TREE WELL AND PLANTING BED SOIL PREPARATION:

TREE PLANTING:

EXCAVATE EXISTING SOIL TO THE DEPTH OF THE ROOT BALL AND 24" BEYOND THE EDGE OF ROOTBALL. BACKFILL USING A MIXTURE OF TOPSOIL WITH 4 CUBIC FEET OF BACK TO NATURE AND 15 LBS OF STERLIZED COW MANURE PER TREE. APPLY ROOTS TRANSPLANT 1-STEP AT A RATE OF FOUR (4) OUNCES PER CALIPER INCH PER TREE. INCORPORATE AMENDMENTS INTO THE TOP 3"-4" OF SOIL BACKFILL. STAKE AND GUY TREES PER DETAILS ON PLANS.

PLANTING BEDS

REFER TO DETAILS ON LANDSCAPE PLANS FOR PREPARATION OF ALL LANDSCAPE PLANTING BEDS (RAISED PLANTERS AND AT-GRADE PLANTERS). PROVIDE IMPORTED TOPSOIL (GEMDIRT 50 / 50 TOPMIX OR APPROVED EQUAL) IN DEPTHS INDICATED, AND INSTALL GEOTEXTILE FABRIC AS SHOWN. FOR ALL PLANTING BED AREAS, INCORPORATE ROOTS TRANSPLANT 1-STEP AT A RATE OF 5 POUNDS PER 100 SQUARE FEET INTO TOP 3"-4" OF SOIL.


SOD

ALL SITE AREAS DISTURBED BY CONSTRUCTION SHALL BE REVEGETATED WITH 'PATRIOT' BERMUDA GRASS SOD. REFER TO DRAWINGS FOR LIMITS OF SODDING AND REFER TO SODDING SPECIFICATIONS..


GENERAL CONTRACTOR SHALL BE RESPONSIBLE TO PROVIDE FINISH GRADE (1*±) FOR SODDING. LANDSCAPE CONTRACTOR (LC) SHALL PROVIDE FINE GRADE PRIOR TO SODDING. FINE GRADING OF LAWN AREAS SHALL PROVIDE A SMOOTH TRANSITION TO EXISTING GRADE AND BE FREE OF DEPRESSIONS OR OTHER IRREGULARITIES. SETTLING OF SOIL SHALL BE REPAIRED BY LANDSCAPE CONTRACTOR.


MULCH:


MULCH PLANTING BEDS AND RAISED PLANTERS WITH GRADE A CEDAR MULCH TO A DEPTH OF TWO (2) INCHES. TOP OF MULCH LAYER SHALL BE PLACED 1" BELOW TOP OF CURBS, WALKS, AND STEEL BED EDGING. MULCH ALL TREE WELLS WITH 3" DEPTH CEDAR MULCH. FOR MID-LEVEL PLANTING TERRACE (NORTH EDGE OF POND), MULCH WITH 3" THICK PEA GRAVEL / WEED BARRIER FABRIC PER DETAIL ON PLANS.



Friday, April 19, 2019 2:00:44 PM Z:\Public & Park\Elm Creek Detention + West Pond\Elm Creek - 6th St. West Pond COT #17001\Drawing:







17001 JSZ∕LSP 5 001 #1 COT ۍ. Sth Creek d\Elm Por + West Friday, April 19, 2019 2:00:45 PM Z:\Public & Park\Elm Creek Detention


LANDSCAPE NOTES

REFER TO SHEET L31 FOR PLANT MATERIAL SCHEDULE AND LANDSCAPE NOTES. REFER TO SHEET L32 FOR TYPICAL LANDSCAPE PLANTING DETAILS. REFER TO HARDSCAPE PLANS FOR LAYOUT OF SIDEWALKS AND PEDESTRIAN PAVEMENT (SHEETS L11 - L18). REFER TO SHEETS L38 - L43 FOR SITE IRRIGATION SYSTEM PLANS.

CLOSELY COORDINATE ALL TREE LOCATIONS WITH UTILITIES (EXISTING AND PROPOSED), SITE LIGHTING, AND OTHER SITE CONDITIONS. FIELD ADJUST LOCATIONS FOR PROPOSED TREES AS REQUIRED, AND NOTIFY OWNER IF THERE ARE SIGNIFICANT CONFLICTS.

6. ALL DISTURBED AREAS OF THE SITE THAT ARE NOT SHOWN FOR OTHER PLANTINGS ARE TO BE SODDED WITH 'PATRIOT" BERMUDA SOD, PER NOTES ON SHEET L31.

| | | | ELM CREEK WEST POND | | | | | | | | |
|--|--------------------|------|------------------------|--|---|---------|---------------|------|----|--|--|
| | $\overline{\ }$ | | | PROJECT No. 148150 | | | | | | | |
| 60% PRELIMINARY F NOT FOR CONSTRUCT | LANDSCAPE PLAN - A | | | | | | | | | | |
| | | | | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | | | | |
| | | | | | ALABACK DESIGN ASSOCIATES 3202 E. 21ST ST, TULSA OK 74114 PH: 918.742.1463 | | | | | | |
| REVISION | BY | DATE | PLAN SCALE: | DRAWN | BC | 4/26/19 | APPROVED: | | | | |
| | - | | AS SHOWN | DESIGNED | MP | 4/26/19 | | | | | |
| | | | | SURVEY | | | | | | | |
| | - | | PROFILE SCALE: | PROJ. MGR. | | | | | | | |
| | - | | HORIZONTAL: | LEAD ENGR. | | | | | | | |
| | - | | | FIELD MGR. | | | | | | | |
| | | | VERTICAL | RECOMMENE | DED: | | | | | | |
| | | | | DESIGN MAN | AGEF | 2 | CITY ENGINEER | | - | | |
| | | | | | | | DATE: | | | | |
| | | | FILE: | DRAWI | NG: | | PAGE NO. L33 | | | | |
| | | | ATLAS PAGE NO: 01 & 08 | | | | SHEET NO. 34 | OF 1 | 23 | | |



LANDSCAPE NOTES


REFER TO SHEET L31 FOR PLANT MATERIAL SCHEDULE AND LANDSCAPE NOTES. REFER TO SHEET L32 FOR TYPICAL LANDSCAPE PLANTING DETAILS.

REFER TO SHEET LS2 FOR THICAL CANOSCAPE PLANTING DETAILS. REFER TO HARDSCAPE PLANS FOR LAYOUT OF SIDEWALKS AND PEDESTRIAN PAVEMENT (SHEETS L11 - L18). REFER TO SHEETS L38 - L43 FOR SITE IRRIGATION SYSTEM PLANS. CLOSELY COORDINATE ALL TREE LOCATIONS WITH UTILITIES (EXISTING AND PROPOSED), SITE LIGHTING, AND OTHER SITE CONDITIONS. FIELD ADJUST LOCATIONS FOR PROPOSED TREES AS REQUIRED, AND NOTIFY

OWNER IF THERE ARE SIGNIFICANT CONFLICTS. ALL DISTURBED AREAS OF THE SITE THAT ARE NOT SHOWN FOR OTHER PLANTINGS ARE TO BE SODDED WITH 'PATRIOT' BERMUDA SOD, PER NOTES ON SHEET L31.

| | | ELM CREEK WEST POND | | | | | | | | | | | |
|----------------------------------|--------------|---------------------|----------------|-------------|--------|--------------------|-----------------------------------|--|--|--|--|--|--|
| | | | | | | PROJECT No. 148150 | | | | | | | |
| 60% PRELIMINARY PL NOT FOR | | | LANI | DSC | APE PI | LAN - B | | | | | | | |
| CONSTRUCTIO | CONSTRUCTION | | | | | , | OKLAHOMA S DEPARTMENT | | | | | | |
| | | | | | | | SSOCIATES 4 PH: 918.742.1463 | | | | | | |
| REVISION | ΒY | DATE | PLAN SCALE: | DRAWN | BC | 4/26/19 | APPROVED: | | | | | | |
| | | | AS SHOWN | DESIGNED | MP | 4/26/19 | | | | | | | |
| | | | | SURVEY | | | | | | | | | |
| | | | PROFILE SCALE: | PROJ. MGR. | | | | | | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | | | | | | |
| | | | | FIELD MGR. | | | | | | | | | |
| | | | VERTICAL | RECOMMEND | DED: | | | | | | | | |
| | | | 1 | DESIGN MAN | AGEF | 2 | CITY ENGINEER | | | | | | |
| | | | | | | | DATE: | | | | | | |
| | | | FILE: | DRAWI | NG: | | PAGE NO. L34 | | | | | | |
| | | | ATLAS PAGE | NO: 01 & 08 | | | SHEET NO. 35 OF 123 | | | | | | |






7001 ngs/LSP 7001\Draw #1 сот Vest ŗ. 6th 1 Creek West + Friday, April 19, 2019 2:00:47 PM Z:\Public & Park\Elm Creek Deten


LANDSCAPE NOTES

REFER TO SHEET L31 FOR PLANT MATERIAL SCHEDULE AND LANDSCAPE NOTES. REFER TO SHEET L32 FOR TYPICAL LANDSCAPE PLANTING DETAILS. REFER TO HARDSCAPE PLANS FOR LAYOUT OF SIDEWALKS AND PEDESTRIAN PAVEMENT (SHEETS L11 - L18). REFER TO SHEETS L38 - L43 FOR SITE IRRIGATION SYSTEM PLANS.

CLOSELY COORDINATE ALL TREE LOCATIONS WITH UTILITIES (EXISTING AND PROPOSED), SITE LIGHTING, AND OTHER SITE CONDITIONS. FIELD ADJUST LOCATIONS WITH UTILITIES (EXISTING AND PROPOSED), SITE LIGHTING, AND OWNER IF THERE ARE SIGNIFICANT CONFLICTS. ALL DISTURBED AREAS OF THE SITE THAT ARE NOT SHOWN FOR OTHER PLANTINGS ARE TO BE SODDED WITH 'PATRIOT' BERMUDA SOD, PER NOTES ON SHEET L31.

| | | | ELM CREEK WEST POND | | | | | | | | |
|--|-----------------|--|------------------------|--------------------|---|---------|--------------|--------|--|--|--|
| | $\overline{\ }$ | | | PROJECT No. 148150 | | | | | | | |
| 60% PRELIMINARY F NOT FOR CONSTRUCT | | LAN | DSC | APE PL | LAN - C | | | | | | |
| CONSTRUCT | | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | | | | | | |
| | | | | | ALABACK DESIGN ASSOCIATES 3202 E. 21ST ST, TULSA OK 74114 PH: 918.742.1463 | | | | | | |
| REVISION | BY | DATE | PLAN SCALE: | DRAWN | BC | 4/26/19 | APPROVED: | | | | |
| | | | AS SHOWN | DESIGNED | MP | 4/26/19 | | | | | |
| | - | | | SURVEY | | | | | | | |
| | - | | PROFILE SCALE: | PROJ. MGR. | | | | | | | |
| | - | | HORIZONTAL · | LEAD ENGR. | | | | | | | |
| | - | | | FIELD MGR. | | | | | | | |
| | | | VERTICAL | VERTICAL | | | | | | | |
| | | DESIGN MAN | AGEF | 2 | CITY ENGINEER | | | | | | |
| | | | | | | | DATE: | | | | |
| | | | FILE: | DRAWI | NG: | | PAGE NO. L35 | | | | |
| | | | ATLAS PAGE NO: 01 & 08 | | | | SHEET NO. 36 | OF 123 | | | |








LANDSCAPE NOTES

REFER TO SHEET L31 FOR PLANT MATERIAL SCHEDULE AND LANDSCAPE NOTES. REFER TO SHEET L32 FOR TYPICAL LANDSCAPE PLANTING DETAILS. REFER TO HARDSCAPE PLANS FOR LAYOUT OF SIDEWALKS AND PEDESTRIAN PAVEMENT (SHEETS L11 - L18). REFER TO SHEETS L38 - L43 FOR SITE IRRIGATION SYSTEM PLANS. CLOSELY COORDINATE ALL TREE LOCATIONS WITH UTILITIES (EXISTING AND PROPOSED), SITE LIGHTING, AND OTHER SITE CONDITIONS. FIELD ADJUST LOCATIONS FOR PROPOSED TREES AS REQUIRED, AND NOTIFY OWNER IF THERE ARE SIGNIFICANT CONFLICTS. ALL DISTURBED AREAS OF THE SITE THAT ARE NOT SHOWN FOR OTHER PLANTINGS ARE TO BE SODDED WITH 'PATRIOT' BERMUDA SOD, PER NOTES ON SHEET L31.

| | | | ELM CREEK WEST POND | | | | | | | | | | |
|--------------------------|--------------|------|------------------------|--|---|--------------------|---------------------|--|--|--|--|--|--|
| | | | | | | PROJECT No. 148150 | | | | | | | |
| PRELIMINARY P NOT FOR | | | | | DSC | APE PL | .AN - D | | | | | | |
| CONSTRUCTI | CONSTRUCTION | | | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | | | | | | |
| | | | | | ALABACK DESIGN ASSOCIATES 3202 E. 21ST ST, TULSA OK 74114 PH: 918.742.1463 | | | | | | | | |
| REVISION | BY | DATE | PLAN SCALE: | DRAWN | BC | 4/26/19 | APPROVED: | | | | | | |
| | | | AS SHOWN | DESIGNED | MP | 4/26/19 | | | | | | | |
| | | | | SURVEY | | | | | | | | | |
| | | | PROFILE SCALE: | PROJ. MGR. | | | | | | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | | | | | | |
| | | | | FIELD MGR. | | | | | | | | | |
| | | | VERTICAL | VERTICAL | | | | | | | | | |
| | | | | DESIGN MAN | AGEF | 2 | CITY ENGINEER | | | | | | |
| | | | | | | | DATE: | | | | | | |
| | | | FILE: | DRAWI | NG: | | PAGE NO. L36 | | | | | | |
| | | | ATLAS PAGE NO: 01 & 08 | | | | SHEET NO. 37 OF 123 | | | | | | |



COT #17001\Drawings\LSP 17001.dwg puoc West st. 6th 1 Creek Pond\Elm West + Friday, April 19, 2019 2:00:49 PM Z:\Public & Park\Elm Creek Detention


LANDSCAPE NOTES

REFER TO SHEET L31 FOR PLANT MATERIAL SCHEDULE AND LANDSCAPE NOTES.
 REFER TO SHEET L32 FOR TYPICAL LANDSCAPE PLANTING DETAILS.
 REFER TO HARDSCAPE PLANS FOR LAYOUT OF SIDEWALKS AND PEDESTRIAN PAVEMENT (SHEETS L11 - L18).
 REFER TO SHEETS L38 - L43 FOR SITE IRRIGATION SYSTEM PLANS.
 CLOSELY COORDINATE ALL TREE LOCATIONS WITH UTILITIES (EXISTING AND PROPOSED), SITE LIGHTING, AND
 DOTE OUTDOING FOR LAYOUT OF UP UP DROPORED PLANS.

OTHER SITE CONDITIONS. FIELD ADJUST LOCATIONS FOR PROPOSED TREES AS REQUIRED, AND NOTIFY

OWNER IF THERE ARE SIGNIFICANT CONFLICTS. ALL DISTURBED AREAS OF THE SITE THAT ARE NOT SHOWN FOR OTHER PLANTINGS ARE TO BE SODDED WITH 'PATRIOT' BERMUDA SOD, PER NOTES ON SHEET L31.

| | EL | ELM CREEK WEST POND | | | | | | |
|---|--------------------|---|------------------------|--------------|-----|----------------|---------------|--|
| | PROJECT No. 148150 | | | | | | | |
| 60% PRELIMINARY PLANS NOT FOR CONSTRUCTION | | | LANDSCAPE PLAN - E | | | | | |
| | | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | | | |
| | | ALABACK DESIGN ASSOCIATES 3202 E. 21ST ST, TULSA OK 74114 PH: 918.742.1463 | | | | | | |
| REVISION | BY | DATE | PLAN SCALE: | DRAWN | BC | 4/26/19 | APPROVED: | |
| | | | AS SHOWN | DESIGNED | MP | 4/26/19 | | |
| | | | | SURVEY | | | | |
| | | | PROFILE SCALE: | PROJ. MGR. | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | |
| | | | | FIELD MGR. | | | | |
| | | | VERTICAL | RECOMMENDED: | | | | |
| | | | | | | | CITY ENGINEER | |
| | | | | | | | DATE: | |
| | | | FILE: | DRAWI | NG: | | PAGE NO. L37 | |
| | | | ATLAS PAGE NO: 01 & 08 | | | SHEET NO. 38 C | DF 123 | |
| | | | | | | | | |




THE FOLLOWING NOTES ARE A PARTIAL SUMMARY ONLY OF IRRIGATION SPECIFICATIONS. REFER ALSO TO WRITTEN SPECIFICATIONS SECTIONS FOR THE IRRIGATION SYSTEM.

GENERAL IRRIGATION NOTES

- 1. CALL 811 FOR INFORMATION ON THE LOCATION OF ALL UNDERGROUND UTILITIES. CONTACT PRIOR TO DIGGING. CONTRACTOR SHALL BE RESPONSIBLE FOR ANY DAMAGE CAUSED TO THE UTILITIES (BOTH OVERHEAD AND BURIED) WHICH MAY OCCUR DUE TO HIS ACTION OR LACK OF ACTION ON THE PROJECT SITE DURING LANDSCAPE OR IRRIGATION INSTALLATION. CONTRACTOR SHALL SEEK THE ASSISTANCE OF LOCAL UTILITIES AND THE OWNER IN LOCATING THE UTILITIES PRIOR TO PERFORMING TRENCHING OPERATIONS IN ANY AREA.
- 2. CONTRACTOR SHALL CAREFULLY VERIFY A MINIMUM DYNAMIC WATER PRESSURE OF 70PSI @50GPM ADJACENT TO THE WATER METER LOCATION. IF THE MINIMUM WATER PRESSURE IS LESS THAN 70 PSI, CONTRACTOR SHALL NOTIFY THE OWNER OF SUCH AND SHALL RECEIVE OWNER'S APPROVAL PRIOR TO BEGINNING INSTALLATION OPERATIONS.
- CONTRACTOR IS RESPONSIBLE FOR INSTALLATION OF SCHEDULE 40 PVC SLEEVES 3. AS INDICATED ON THE DRAWING. EXTEND SLEEVES 2' BEYOND BACK OF CURB AND CAP UNTIL CONTRACTOR IS READY TO BEGIN INSTALLATION OF SYSTEM. STAKE LOCATION OF SLEEVE WITH T-POSTS AND FLAGS.
- 4. CONTRACTOR SHALL SUPPLY A 2" CONDUIT FROM CONTROLLER LOCATION TO THE ANDSCAPE AREA AS SHOWN FOR VALVE WIRE
- 5. CONTRACTOR IS RESPONSIBLE FOR PROVIDING A J-BOX WITH 115VAC: 1PHASE POWER TO THE CONTROLLER AND BACKFLOW PREVENTER LOCATIONS IRRIGATION CONTRACTOR SHALL HARD WIRE CONTROLLER TO J-BOX.
- 6. GENERAL CONTRACTOR SHALL SUPPLY WATER METER.
- THE IRRIGATION DESIGN IS DIAGRAMMATIC. THE INTENT OF THE DRAWINGS IS TO SHOW THE GENERAL LAYOUT AND LOGIC OF THE SYSTEM SCALED. MEASUREMENTS MAY NOT BE ACCURATE. ACTUAL LOCATIONS AND QUANTITIES OF PIPE AND FITTINGS MAY VARY DUE TO FIELD ADJUSTMENTS FOR EXISTING AND NEW TREES AND OTHER OBSTRUCTIONS TO PROVIDE THE PROPER AND INTENDED COVERAGE
- 8. CONTRACTOR SHALL INSURE THAT THE IRRIGATION MAIN LINE AND VALVES ARE INSTALLED WITHIN THE PROPERTY LINES. ANY LINES SHOWN OUTSIDE OF NORMAL INSTALLATION CORRIDORS ARE FOR PRESENTATION PURPOSES ONLY
- 9. CONTRACTOR SHALL INSTALL SPECIFIED BACKFLOW PREVENTER AND PROTECTIVE HOUSING (IF SPECIFIED) AT THE LOCATION SHOWN ON THE DRAWINGS. CONTRACTOR SHALL CLOSELY FOLLOWING THESE CONTRACT DRAWINGS, THE IRRIGATION SPECIFICATIONS, AND THE SPECIFIED RECOMMENDATIONS OF THE EQUIPMENT MANUFACTURES TO INSURE PROPER INSTALLATION OF THE IRRIGATION SYSTEM. CONTRACTOR SHALL IMMEDIATELY CONSULT WITH THE OWNER WHENEVER THERE APPEARS TO BE A CONFLICT BETWEEN ANY OF THE ABOVE STATED DOCUMENTS
- 10. PROVIDE WINTERIZING FOR THE SYSTEM BY USING A COMBINATION OF AUTOMATIC FILTER DRAIN VALVES IN THE LATERAL LINES. MANUAL DRAIN VALVES IN THE LOW POINTS OF THE MAINLINE AND PROVIDE PIPE HEATING CABLE TO PROTECT BACKFLOW PREVENTER FROM FREEZING.
- 11. CONTRACTOR SHALL INSTALL AN AUTOMATIC FILL VALVE. FROM THE IRRIGATION ANNLINE, TO MAINTAIN A MINIMUM WATER LEVEL IN THE POND.

| | ELM CREEK WEST POND | | | | | | | | |
|---------------------------------|---------------------|------------|------------------------------|--|--------------|---------|-----------------------------------|------|----|
| | $\overline{\ }$ | | | PROJE | EC | ΓNo. | 148150 | | |
| 60% PRELIMINARY F NOT FOR | IRF | RIGATION L | EGE | ND, NO | DTES & DETAI | LS | | | |
| CONSTRUCTION | | | | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | | |
| | | | 3 | | | | SSOCIATES 4 PH: 918.742.1463 | | |
| REVISION | BY | DATE | PLAN SCALE: | DRAWN | BC | 4/26/19 | APPROVED: | | |
| | | | AS SHOWN | DESIGNED | MP | 4/26/19 | | | |
| | | | | SURVEY | | | | | |
| | | | PROFILE SCALE: | PROJ. MGR. | | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | | |
| | | | 1 | FIELD MGR. | | | | | |
| | | | VERTICAL | RECOMMENDED: | | | | | |
| | | | | DESIGN MAN | AGEF | ۲ | CITY ENGINEER | | • |
| | | | | | | | DATE: | | |
| | | | FILE: | DRAW | NG: | | PAGE NO. L38 | | |
| | | | ATLAS PAGE NO: 01 & 08 SHEET | | | | SHEET NO. 39 | OF 1 | 23 |




Friday, April 19, 2019 2:14:54 PM Z:\Public & Park\Elm Creek Detention + West Pond\Elm Creek - 6th St. West Pond COT #17001\Drawings\IRP 17001.dr

| IRRIGATION EQUIPMENT LEGEND |
|---|
| 1-1/2" IRRIGATION WATER METER (50gpm @ 70psi RQD) |
| ➡ WILKINS 1-1/2" #975XL RP-TYPE BACKFLOW PREVENTER |
| • 1" AIR / VACUUM RELIEF VALVE |
| ⊗ WEATHERMATIC #11024FCR-15 1-1/2" ZONE VALVE |
| RAINBIRD ESP-24LXME IRRIGATION CONTROLLER |
| RAINBIRD WR2-RFC WIRELESS RAIN / FREEZE SENSOR |
| RAINBIRD 3RC QUICK COUPLING VALVE (PROVIDE 2 KEYS) |
| ③ RAINBIRD 1804-PRS POP-UP TURE SPRAY with 8-HE-VAN NOZZLE |
| RAINBIRD 1804-PRS POP-UP TURF SPRAY with 10-HE-VAN_NOZZLE |
| RAINBIRD 1804-PRS POP-UP TURF SPRAY with 12-HE-VAN NOZZLE |
| IN RAINBIRD 1804-PRS POP-UP TURF SPRAY with 15-HE-VAN NOZZLE |
| ® RAINBIRD 1804-PRS POP-UP TURF SPRAY with 18VAN NOZZLE |
| |
| B RAINBIRD 1804-SAM-P45 4" POP-UP - MP1000-360 NOZZLE C |
| © RAINBIRD 1804-SAM-P45 4" POP-UP - MP2000-90-210 NOZZLE |
| RAINBIRD 1804-SAM-P45 4" POP-UP - MP2000-360 NOZZLE |
| C RAINBIRD 1804-SAM-P45 4" POP-UP - MP3000-90-210 NOZZLE |
| ⑦ RAINBIRD 1804-SAM-P45 4" POP-UP - MP3000-360 NOZZLE |
| © RAINBIRD 1804-SAM-P45 4" POP-UP - MPCORNER NOZZLE |
| RAINBIRD 1804-SAM-P45 4" POP-UP - MPSS-530 NOZZLE |
| RAINBIRD 1804-SAM-P45 4" POP-UP - MPRC-515 NOZZLE |
| RAINBIRD 1804-SAM-P45 4" POP-UP - MPLC-515 NOZZLE |
| 3 RAINBIRD 1812-PRS POP-UP SHRUB SPRAY with 8-HE-VAN NOZZLE |
| I RAINBIRD 1812-PRS POP-UP SHRUB SPRAY with 10-HE-VAN NOZZLE |
| RAINBIRD 1812-PRS POP-UP SHRUB SPRAY with 12-HE-VAN NOZZLE |
| IS RAINBIRD 1812-PRS POP-UP SHRUB SPRAY with 15-HE-VAN NOZZLE |
| RAINBIRD 1812 PRS POP-UP SHRUB SPRAY with 15SST NOZZLE |
| 🖾 RAINBIRD 1812-PRS POP-UP SHRUB SPRAY with 15RCS NOZZLE |
| RAINBIRD 1812-PRS POP-UP SHRUB SPRAY with 15LCS NOZZLE |
| |
| SCH40 PVC MAINLINE PIPING |
| 4" SCHEDULE 40 PVC SLEEVING |
| 6" SCHEDULE 40 PVC SLEEVING |
| |

IRRIGATION NOTE

FOR THE 60% SUBMITTAL, IRRIGATION DRAWINGS INCLUDE A LAYOUT FOR IRRIGATION HEADS, MAINLINE ROUTING, SLEEVES, AND SOME LATERAL LINES. (NOT ALL LATERAL LINES ARE SHOWN.) ITEMS THAT WILL BE PROVIDED ON FINAL IRRIGATION PLANS, BUT ARE NOT INCLUDED FOR 60% LEVEL, INCLUDE: AUTOMATIC ZONE VALVES, ADDITIONAL LATERAL LINES, SIZES FOR MAINS AND LATERAL PIPING, CONNECTION POINT TO CITY WATER LINE, BACKFLOW PREVENTER, METER, CONTROLLER, QUICK COUPLER VALVES, AND ALL OTHER SYSTEM COMPONENTS.

| _ | ELM CREEK WEST POND | | | | | | | |
|----------------------------------|---------------------|--------|---|--|----------|---------|---------------|--------|
| | $\overline{\ }$ | | | PROJE | ECT | ۲No. | 148150 | |
| 60% PRELIMINARY PI NOT FOR | | IRRIGA | TION | I PLAN | - AREA A | | | |
| CONSTRUCTION | | | | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | |
| | | | ALABACK DESIGN ASSOCIATES 3202 E. 21ST ST, TULSA OK 74114 PH: 918.742.1463 | | | | | |
| REVISION | BY | DATE | PLAN SCALE: | DRAWN | BC | 4/26/19 | APPROVED: | |
| | | | AS SHOWN | DESIGNED | MP | 4/26/19 | | |
| | | | | SURVEY | | | | |
| | | | PROFILE SCALE: | PROJ. MGR. | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | |
| | | | | FIELD MGR. | | | | |
| | | | VERTICAL | RECOMMEN | DED: | | | |
| | | | | DESIGN MAN | AGER | | CITY ENGINEER | |
| | | | | | | | DATE: | |
| | | | FILE: | DRAWI | NG: | | PAGE NO. L39 | |
| | | | ATLAS PAGE | NO: 01 & 08 | | | SHEET NO. 40 | OF 123 |






| IR | RIGATION EQUIPMENT LEGEND |
|-----------|--|
| | 1-1/2" IRRIGATION WATER METER (50gpm @ 70psi RQD) |
| ₩ | WILKINS 1-1/2" #975XL RP-TYPE BACKFLOW PREVENTER |
| ۲ | 1" AIR / VACUUM RELIEF VALVE |
| \otimes | WEATHERMATIC #11024FCR-15 1-1/2" ZONE VALVE |
| Ø | RAINBIRD ESP-24LXME IRRIGATION CONTROLLER |
| ∞ | RAINBIRD WR2-RFC WIRELESS RAIN / FREEZE SENSOR |
| Ø | RAINBIRD 3RC QUICK COUPLING VALVE (PROVIDE 2 KEYS) |
| 8 | RAINBIRD 1804-PRS POP-UP TURF SPRAY with 8-HE-VAN NOZZLE |
| | RAINBIRD 1804-PRS POP-UP TURF SPRAY with 10-HE-VAN NOZZLE |
| - | RAINBIRD 1804-PRS POP-UP TURF SPRAY with 12-HE-VAN NOZZLE |
| - | RAINBIRD 1804-PRS POP-UP TURF SPRAY with 15-HE-VAN NOZZLE |
| 13 | RAINBIRD 1804-PRS POP-UP TURF SPRAY with 18VAN NOZZLE |
| Ø | RAINBIRD 1804-SAM-P45 4" POP-UP - MP1000-90-210 NOZZLE |
| ₿ | RAINBIRD 1804-SAM-P45 4" POP-UP - MP1000-360 NOZZLE |
| © | RAINBIRD 1804-SAM-P45 4" POP-UP - MP2000-90-210 NOZZLE |
| 0 | RAINBIRD 1804-SAM-P45 4" POP-UP - MP2000-360 NOZZLE |
| - | RAINBIRD 1804-SAM-P45 4" POP-UP - MP3000-90-210 NOZZLE |
| | RAINBIRD 1804-SAM-P45 4" POP-UP - MP3000-360 NOZZLE |
| - | RAINBIRD 1804-SAM-P45 4" POP-UP - MPCORNER NOZZLE |
| - | RAINBIRD 1804-SAM-P45 4" POP-UP - MPSS-530 NOZZLE |
| - | RAINBIRD 1804-SAM-P45 4" POP-UP - MPRC-515 NOZZLE |
| Ø | RAINBIRD 1804-SAM-P45 4" POP-UP - MPLC-515 NOZZLE |
| 8 | RAINBIRD 1812-PRS POP-UP SHRUB SPRAY with 8-HE-VAN NOZZLE |
| _ | RAINBIRD 1812-PRS POP-UP SHRUB SPRAY with 10-HE-VAN NOZZLE |
| _ | RAINBIRD 1812-PRS POP-UP SHRUB SPRAY with 12-HE-VAN NOZZLE |
| _ | RAINBIRD 1812-PRS POP-UP SHRUB SPRAY with 15-HE-VAN NOZZLE |
| | RAINBIRD 1812-PRS POP-UP SHRUB SPRAY with 15SST NOZZLE |
| _ | RAINBIRD 1812-PRS POP-UP SHRUB SPRAY with 15RCS NOZZLE |
| LC | RAINBIRD 1812-PRS POP-UP SHRUB SPRAY with 15LCS NOZZLE |
| | CLASS 200 PVC LATERAL PIPING |
| _ | SCH40 PVC MAINLINE PIPING |
| 1000 | |
| 2 | NA N |

FOR THE 60% SUBMITTAL, IRRIGATION DRAWINGS INCLUDE A LAYOUT FOR IRRIGATION HEADS, MAINLINE ROUTING, SLEEVES, AND SOME LATERAL LINES. (NOT ALL LATERAL LINES ARE SHOWN.) ITEMS THAT WILL BE PROVIDED ON FINAL IRRIGATION PLANS, BUT ARE NOT INCLUDED FOR 60% LEVEL, INCLUDE: AUTOMATIC ZONE VALVES, ADDITIONAL LEVEL, INCLODE: AUTOMATIC ZONE VALVES, ADDITIONG, CONNECTION POINT TO CITY WATER LINE, BACKFLOW PREVENTER, METER, CONTROLLER, QUICK COUPLER VALVES, AND ALL OTHER SYSTEM COMPONENTS.

| | ELM CREEK WEST POND | | | | | | | | |
|----------------------------------|---|---------------------|----------------|--|----------|---------------|--------------|--------|--|
| | $\overline{\ }$ | | | PROJE | ECT | ۲No. | 148150 | | |
| 60% PRELIMINARY PL NOT FOR | | IRRIGA ⁻ | TION | PLAN | - AREA B | | | | |
| CONSTRUCTION | | | | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | | |
| | ALABACK DESIGN ASSOCIATES 3202 E. 21ST ST, TULSA OK 74114 PH: 918.742.1463 | | | | | | | | |
| REVISION | BY | DATE | PLAN SCALE: | DRAWN | BC | 4/26/19 | APPROVED: | | |
| | | | AS SHOWN | DESIGNED | MP | 4/26/19 | | | |
| | | | | SURVEY | | | | | |
| | | | PROFILE SCALE: | PROJ. MGR. | | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | | |
| | | | | FIELD MGR. | | | | | |
| | | | VERTICAL | RECOMMENDED: | | | | | |
| | | | DESIGN MANAGER | | | CITY ENGINEER | | | |
| | | | | | | | DATE: | | |
| | | | FILE: | DRAW | NG: | | PAGE NO. L40 | | |
| | | | ATLAS PAGE | NO: 01 & 08 | | | SHEET NO. 41 | OF 123 | |
| | | | | | | | | | |






| IRRIGATION EQUIPMENT LEGEND |
|---|
| 1-1/2" IRRIGATION WATER METER (50gpm @ 70psi RQD) WILKINS 1-1/2" #375XL RP-TYPE BACKFLOW PREVENTER 1" AIR / VACUUM RELIEF VALVE |
| ⊗ WEATHERMATIC #11024FCR-15 1-1/2" ZONE VALVE |
| RAINBIRD ESP-24LXME IRRIGATION CONTROLLER |
| RAINBIRD WR2-RFC WIRELESS RAIN / FREEZE SENSOR |
| RAINBIRD 3RC QUICK COUPLING VALVE (PROVIDE 2 KEYS) |
| ③ RAINBIRD 1804-PRS POP-UP TURF SPRAY with 8-HE-VAN NOZZLE ④ RAINBIRD 1804-PRS POP-UP TURF SPRAY with 10-HE-VAN NOZZLE |
| ② RAINBIRD 1804-PRS POP-UP TURF SPRAY with 12-HE-VAN NOZZLE |
| ③ RAINBIRD 1804-PRS POP-UP TURF SPRAY with 15-HE-VAN NOZZLE |
| RAINBIRD 1804-PRS POP-UP TURF SPRAY with 18VAN NOZZLE |
| ③ RAINBIRD 1804-SAM-P45 4" POP-UP - MP1000-90-210 NOZZLE |
| ③ RAINBIRD 1804-SAM-P45 4" POP-UP - MP1000-360 NOZZLE |
| © RAINBIRD 1804-SAM-P45 4" POP-UP - MP2000-90-210 NOZZLE |
| RAINBIRD 1804-SAM-P45 4" POP-UP - MP2000-360 NOZZLE |
| © RAINBIRD 1804-SAM-P45 4" POP-UP - MP3000-90-210 NOZZLE |
| ⑦ RAINBIRD 1804-SAM-P45 4" POP-UP - MP3000-360 NOZZLE |
| © RAINBIRD 1804-SAM-P45 4" POP-UP - MPCORNER NOZZLE |
| RAINBIRD 1804-SAM-P45 4" POP-UP - MPSS-530 NOZZLE DAMNDIDD 4994 CAM D45 4" DOD UD - MDD0 545 NOZZLE |
| RAINBIRD 1804-SAM-P45 4" POP-UP - MPRC-515 NOZZLE RAINBIRD 1804-SAM-P45 4" POP-UP - MPLC-515 NOZZLE |
| CAINDIRD 1804-3AM-F434 FOF-OF-MIPLO-313 NOZZLE |
| RAINBIRD 1812-PRS POP-UP SHRUB SPRAY with 8-HE-VAN NOZZLE |
| RAINBIRD 1812-PRS POP-UP SHRUB SPRAY with 10-HE-VAN NOZZL |
| RAINBIRD 1812-PRS POP-UP SHRUB SPRAY with 12-HE-VAN NOZZL |
| RAINBIRD 1812-PRS POP-UP SHRUB SPRAY with 15-HE-VAN NOZZL |
| RAINBIRD 1812-PRS POP-UP SHRUB SPRAY with 15SST NOZZLE |
| RAINBIRD 1812-PRS POP-UP SHRUB SPRAY with 15RCS NOZZLE |
| RAINBIRD 1812-PRS POP-UP SHRUB SPRAY with 15LCS NOZZLE |
| CLASS 200 PVC LATERAL PIPING |
| SCH40 PVC MAINLINE PIPING |
| 4" SCHEDULE 40 PVC SLEEVING |
| 🗖 🗖 🗖 🗖 🗖 🗖 6" SCHEDULE 40 PVC SLEEVING |
| |

IRRIGATION NOTE

FOR THE 60% SUBMITTAL, IRRIGATION DRAWINGS INCLUDE A LAYOUT FOR IRRIGATION HEADS, MAINLINE ROUTING, SLEEVES, AND SOME LATERAL LINES. (NOT ALL LATERAL LINES ARE SHOWN.) ITEMS THAT WILL BE PROVIDED ON FINAL IRRIGATION PLANS, BUT ARE NOT INCLUDED FOR 60% LEVEL, INCLUDE: AUTOMATIC ZONE VALVES, ADDITIONAL LATERAL LINES, SIZES FOR MAINS AND LATERAL PIPING, CONNECTION POINT TO CITY WATER LINE, BACKFLOW PREVENTER, METER, CONTROLLER, QUICK COUPLER VALVES, AND ALL OTHER SYSTEM COMPONENTS.

| | | | ELM CREEK WEST POND | | | | | |
|--|---|--|---------------------|------------------------|----------|---------|---------------|--------|
| | $\overline{\ }$ | | | PROJE | ECT | ۲No. | 148150 | |
| 60% PRELIMINARY PL NOT FOR CONSTRUCTION | | IRRIGA | TION | PLAN | - AREA C | | | |
| | | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | | | |
| | ALABACK DESIGN ASSOCIATES 3202 E. 21ST ST, TULSA OK 74114 PH: 918.742.1463 | | | | | | | |
| REVISION | BY | DATE | PLAN SCALE: | DRAWN | вС | 4/26/19 | APPROVED: | |
| | | | AS SHOWN | DESIGNED | MP | 4/26/19 | | |
| | | | | SURVEY | | | | |
| | | | PROFILE SCALE: | PROJ. MGR. | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | |
| | | | | FIELD MGR. | | | | |
| | | | VERTICAL | RECOMMENT | DED: | | | |
| | | | | DESIGN MAN | AGER | | CITY ENGINEER | |
| | | | | | | | DATE: | |
| | | | FILE: | DRAW | NG: | | PAGE NO. L41 | |
| | | | ATLAS PAGE | ATLAS PAGE NO: 01 & 08 | | | | OF 123 |
| | | | | | | | | |






| 1-1/2" IRRIGATION WATER METER (50gpm @ 70psi RQD) |
|---|
| |
| WILKINS 1-1/2" #975XL RP-TYPE BACKFLOW PREVENTER |
| O 1" AIR / VACUUM RELIEF VALVE |
| WEATHERMATIC #11024FCR-15 1-1/2" ZONE VALVE |
| RAINBIRD ESP-24LXME IRRIGATION CONTROLLER |
| RAINBIRD WR2-RFC WIRELESS RAIN / FREEZE SENSOR |
| RAINBIRD 3RC QUICK COUPLING VALVE (PROVIDE 2 KEYS) |
| ③ RAINBIRD 1804-PRS POP-UP TURE SPRAY with 8-HE-VAN NOZZLE |
| RAINBIRD 1804-PRS POP-UP TURF SPRAY with 10-HE-VAN NOZZLE |
| RAINBIRD 1804-PRS POP-UP TURF SPRAY with 12-HE-VAN NOZZLE |
| I RAINBIRD 1804-PRS POP-UP TURF SPRAY with 15-HE-VAN NOZZLE |
| ® RAINBIRD 1804-PRS POP-UP TURF SPRAY with 18VAN NOZZLE |
| @ RAINBIRD 1804-SAM-P45 4" POP-UP - MP1000-90-210 NOZZLE |
| RAINBIRD 1804-SAM-P45 4" POP-UP - MP1000-360 NOZZLE |
| © RAINBIRD 1804-SAM-P45 4" POP-UP - MP2000-90-210 NOZZLE |
| © RAINBIRD 1804-SAM-P45 4" POP-UP - MP2000-360 NOZZLE |
| © RAINBIRD 1804-SAM-P45 4" POP-UP - MP3000-90-210 NOZZLE |
| © RAINBIRD 1804-SAM-P45 4" POP-UP - MP3000-360 NOZZLE |
| © RAINBIRD 1804-SAM-P45 4" POP-UP - MPCORNER NOZZLE |
| © RAINBIRD 1804-SAM-P45 4" POP-UP - MPSS-530 NOZZLE |
| © RAINBIRD 1804-SAM-P45 4" POP-UP - MPRC-515 NOZZLE |
| © RAINBIRD 1804-SAM-P45 4" POP-UP - MPLC-515 NOZZLE |
| |
| RAINBIRD 1812-PRS POP-UP SHRUB SPRAY with 8-HE-VAN NOZZLE |
| RAINBIRD 1812-PRS POP-UP SHRUB SPRAY with 10-HE-VAN NOZZLE |
| RAINBIRD 1812-PRS POP-UP SHRUB SPRAY with 12-HE-VAN NOZZLE |
| RAINBIRD 1812-PRS POP-UP SHRUB SPRAY with 15-HE-VAN NOZZLE |
| RAINBIRD 1812-PRS POP-UP SHRUB SPRAY with 15SST NOZZLE |
| RAINBIRD 1812-PRS POP-UP SHRUB SPRAY with 15RCS NOZZLE |
| RAINBIRD 1812-PRS POP-UP SHRUB SPRAY with 15LCS NOZZLE |
| |
| SCH40 PVC MAINLINE PIPING |
| 4" SCHEDULE 40 PVC SLEEVING |
| 📾 📾 📾 📾 📾 📾 6" SCHEDULE 40 PVC SLEEVING |
| |

IRRIGATION NOTE

FOR THE 60% SUBMITTAL, IRRIGATION DRAWINGS INCLUDE A LAYOUT FOR IRRIGATION HEADS, MAINLINE ROUTING, SLEEVES, AND SOME LATERAL LINES. (NOT ALL LATERAL LINES ARE SHOWN.) ITEMS THAT WILL BE PROVIDED ON FINAL IRRIGATION PLANS, BUT ARE NOT INCLUDED FOR 60% LEVEL, INCLUDE: AUTOMATIC ZONE VALVES, ADDITIONAL LATERAL LINES, SIZES FOR MAINS AND LATERAL PIPING, CONNECTION POINT TO CITY WATER LINE, BACKFLOW PREVENTER, METER, CONTROLLER, QUICK COUPLER VALVES, AND ALL OTHER SYSTEM COMPONENTS.

| | | | ELM CREEK WEST POND | | | | | |
|--|---|--|---------------------|-------------|----------|---------|---------------|--------|
| | | PROJE | ECT | ۲No. | 148150 | | | |
| 60% PRELIMINARY PL NOT FOR CONSTRUCTION | | IRRIGA | TION | PLAN | - AREA D | | | |
| | | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | | | |
| | ALABACK DESIGN ASSOCIATES 3202 E. 21ST ST, TULSA OK 74114 PH: 918.742.1463 | | | | | | | |
| REVISION | ΒY | DATE | PLAN SCALE: | DRAWN | BC | 4/26/19 | APPROVED: | |
| | | | AS SHOWN | DESIGNED | MP | 4/26/19 | | |
| | | | | SURVEY | | | | |
| | | | PROFILE SCALE | PROJ. MGR. | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | |
| | | | | FIELD MGR. | | | | |
| | | | VERTICAL | RECOMMENT | DED: | | | |
| | | | | DESIGN MAN | AGER | | CITY ENGINEER | |
| | | | | | | | DATE: | |
| | | | FILE: | DRAW | NG: | | PAGE NO. L42 | |
| | | | ATLAS PAGE | NO: 01 & 08 | | | SHEET NO. 43 | OF 123 |
| | | | | | | | | |




÷ 6th 1 Creek Pond\Elm + West Friday, April 19, 2019 2:16:23 PM Z:\Public & Park\Elm Creek Detention



IRRIGATION NOTE

FOR THE 60% SUBMITTAL, IRRIGATION DRAWINGS INCLUDE A LAYOUT FOR IRRIGATION HEADS, MAINLINE ROUTING, SLEEVES, AND SOME LATERAL LINES. (NOT ALL LATERAL LINES ARE SHOWN.) ITEMS THAT WILL BE PROVIDED ON LINES ARE SHOWN.) THEMS THAT WILL BE PROVIDED ON FINAL IRRIGATION PLANS, BUT ARE NOT INCLUDED FOR 60% LEVEL, INCLUDE: AUTOMATIC ZONE VALVES, ADDITIONAL LATERAL LINES, SIZES FOR MAINS AND LATERAL PIPING, CONNECTION POINT TO CITY WATER LINE, BACKFLOW PREVENTER, METER, CONTROLLER, QUICK COUPLER VALVES, AND ALL OTHER SYSTEM COMPONENTS.

| | ELM CREEK WEST POND | | | | | | | |
|--|-------------------------------------|--|---|------------|--------|---------|---------------|--|
| | $\overline{\ }$ | | | PROJE | ECT | ۲No. | 148150 | |
| 60% PRELIMINARY PLA NOT FOR CONSTRUCTIO | IRRIGATION PLAN - AREA E | | | | | | | |
| CONSTRUCTION | | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | | | |
| | | | ALABACK DESIGN ASSOCIATES 3202 E. 21ST ST, TULSA OK 74114 PH: 918.742.1463 | | | | | |
| REVISION | ΒY | DATE | PLAN SCALE: | DRAWN | вС | 4/26/19 | APPROVED: | |
| | | | AS SHOWN | DESIGNED | MP | 4/26/19 | | |
| | | | | SURVEY | | | | |
| | | | PROFILE SCALE | PROJ. MGR. | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | |
| | | | | FIELD MGR. | | | | |
| | | | VERTICAL | RECOMMEND | DED: | | | |
| | | | | DESIGN MAN | AGER | | CITY ENGINEER | |
| | | | | | | | DATE: | |
| | | | FILE: | DRAW | NG: | | PAGE NO. L43 | |
| | ATLAS PAGE NO: 01 & 08 SHEET NO. 44 | | | | OF 123 | | | |



4:25:34 LIRRFNT 2019 23, Ver April

NOTES:









Jay. April 23, 2019 4:26:13 PM vGSVR\Server\©©©©CURRENT JOBS\WEST POND\RECORD DWG'S\E−2 SITE OVERALL ELECTRICAL 2

NOTES:



ELECTRICAL DEMOLITION FOR THIS PROJECT IS BASED UPON THE ASSUMPTION THAT PSO WILL REMOVE THEIR ELECTRICAL INFRASTRUCTURE WITHIN THE CONSTRUCTION AREA AND MODIFY THEIR DISTRIBUTION TO ALLOW THE REMAINING PROPERTIES TO BE SERVICED. AFTER PROPERTY HAS BEEN ACQUIRED, POLES, OVERHEAD WIRE, ETC. WILL BE REMOVED BY PSO.



BECAUSE THERE ARE NO HIGH VOLTAGE FEEDERS IN THE LOCATION AND THE INFRASTRUCTURE HAS BEEN PAID FOR AND UTILIZED, THE COST FOR REMOVAL IS ASSUMED TO BE COVERED BY PSO AND WILL NOT BE EXPENSED TO THE PROJECT. THIS IS PER DISCUSSIONS WITH PSO IN 2018. IF POLICIES CHANGE, THIS WILL NEED TO BE RE-VISITED.


ELECTRICAL LEGEND




EXISTING OVERHEAD ELECTRIC LINE TO BE REMOVED

S ← EXISTING OVERHEAD ELECTRIC LINE TO REMAIN

| | | | ELM CREEK WEST POND | | | | | | |
|--|----|--|---------------------|-----------------------|------|--------------------------|--|--|--|
| 60% | | PROJECT No. 148150 | | | | | | | |
| PRELIMINARY PLAN NOT FOR CONSTRUCTION 4-25-19 | | | | EXISTING ELECTRICAL 2 | | | | | |
| | | | | | , | OKLAHOMA S DEPARTMENT | | | |
| | | GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 918.437.0282 / WWW.GUYENGR.COM | | | | | | | |
| | ΒY | DATE | PLAN SCALE: | ALE: DRAWN DJB | | APPROVED: | | | |
| | | | | DESIGNED | DWG | | | | |
| | | | | SURVEY | | | | | |
| | | | PROFILE SCALE: | PROJ. MGR. | | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | | |
| | | | | FIELD MGR. | | | | | |
| | | | VERTICAL | RECOMMENDED: | | | | | |
| | | | | DESIGN MAN | AGER | CITY ENGINEER | | | |
| | | | | | | DATE: | | | |
| | | | FILE: | DRAW | NG: | PAGE NO. E-2 | | | |
| | | | ATLAS PAGE | NO: 01 & 08 | | SHEET NO. 46 OF 123 | | | |
| | | | | | | | | | |



ELECTRICAL LEGEND



NOTES:

2

(5)

ANY PULL BOXES USED ARE TO CONTAIN A 6" CONCRETE APRON IF THEY ARE NOT INSTALLED IN A PAVED AREA. (1)


MAXIMUM DISTANCE FOR PULLING WIRE (BETWEEN POLES AND PULL BOXES) IS 180'. 3 CONDUITS WITH OPENINGS EXTENDING IN POLE BASES OR PULL BOXES ARE TO HAVE

PLASTIC BUSHINGS INSTALLED (INCLUDING PVC CONDUITS) TO PROTECT WIRE.

4 LIGHTING AND RECEPTACLE CIRCUITS ARE TO BE IN SEPARATE CONDUIT SYSTEMS AND ARE TO BE FED FROM DIFFERENT SERVICES.


ALL LIGHTING CONTROLLERS ARE TO HAVE SURGE PROTECTORS INSTALLED.

| 60% PROJECT No. 148150 PRELIMINARY PLANS NOT FOR CONSTRUCTION 4-25-19 SITE PLAN 1 CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT |
|---|
| PRELIMINARY PLANS NOT FOR CONSTRUCTION 4-25-19 CITY OF TULSA, OKLAHOMA |
| NOT FOR CONSTRUCTION 4-25-19 CITY OF TULSA, OKLAHOMA |
| |
| ENGINEERING SERVICES DEPARTMENT |
| GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 918.437.0282 / WWW.GUYENGR.COM |
| BY DATE PLAN SCALE: DRAWN DJB APPROVED: |
| DESIGNED DWG |
| SURVEY |
| PROFILE SCALE: PROJ. MGR. |
| HORIZONTAL: LEAD ENGR. |
| FIELD MGR. |
| VERTICAL RECOMMENDED: |
| DESIGN MANAGER CITY ENGINEER |
| DATE: |
| FILE: DRAWING: PAGE NO. E-3 |
| ATLAS PAGE NO: 01 & 08 SHEET NO. 47 OF 123 |



day, April 23, 2019 4:27:38 PM WSSPR'Server) @@@OURFENT JOBS/WEST POND\RECORD DWG'S\E-4 SITE PLAN 2.

ELECTRICAL LEGEND



NOTES:




(2)

ALL CONDUIT TO BE BURIED UNDERGROUND A MINIMUM OF 30".


COORDINATE LOCATION OF CONDUIT WITH OTHER UNDERGROUND INFRASTRUCTURE.

| 000/ | ELM CREEK WEST POND | | | | | | | | |
|--------------------------|---------------------|------|--|--------------------|--------------------------|--|---------------------|--|--|
| 60% PRELIMINARY PLANS | | | | PROJECT No. 148150 | | | | | |
| CONSTRUCTION 4-25-19 | SITE PLAN 2 | | | | | | | | |
| | | | | | OKLAHOMA S DEPARTMENT | | | | |
| | | | GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 918.437.0282 / WWW.GUYENGR.COM | | | | | | |
| | ΒY | DATE | PLAN SCALE: | DRAWN DJB | | | APPROVED: | | |
| | | | | DESIGNED | DWG | | | | |
| | | | | SURVEY | | | | | |
| | | | PROFILE SCALE: | PROJ. MGR. | | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | | |
| | | | | FIELD MGR. | | | | | |
| | | | VERTICAL | RECOMMENDED: | | | | | |
| | | | | DESIGN MANAGER | | | CITY ENGINEER | | |
| | | | | DESIGN MANAGER | | | DATE: | | |
| | | | FILE: | DRAW | NG: | | PAGE NO. E-4 | | |
| | | | ATLAS PAGE | NO: 01 & 08 | | | SHEET NO. 48 OF 123 | | |



iay. April 23, 2019 4:28:16 PM vGSVR\Server\@@@CURRENT JOBS\WEST POND\RECORD DWG'S\E−5 SITE

ELECTRICAL LEGEND



NOTES:

ALL CONDUIT TO BE BURIED UNDERGROUND A MINIMUM OF 30".

COORDINATE LOCATION OF CONDUIT WITH OTHER UNDERGROUND INFRASTRUCTURE.

SEPARATE BURIED CONDUITS TO BE USED FOR LIGHTING, RECEPTACLES AND AERATORS.

DISCONNECT FOR AERATOR TO BE LOCATED WHERE IT IS ACCESSIBLE AND CAPABLE OF BEING LOCKED OUT. DISCONNECT TO BE IN NEMA 4X STAINLESS STEEL ENCLOSURE.



6

(1)

2

3


4

LIGHTING CONTROLLER AND AERATOR CONTROLLERS TO BE IN TWO SEPARATE STAINLESS STEEL CONTROL PANELS.

LIGHT POLES ARE TO BE MOUNTED ON CONCRETE POLE BASES, 24"D AND EXTENDING 5' INTO THE GROUND. ANCHOR BOLTS TO BE A MINIMUM OF 36".


NEMA 4X - DISCONNECT FOR AERATOR REFER TO DETAIL

| 60% PRELIMINARY PLANS NOT FOR CONSTRUCTION 4-25-19 CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST. TULSA OK 74112 / PH: 918.437.0282 / WWW.GUVENGR.COM BY DATE PLAN SCALE: DRAWN DESIGNED DWG SURVEY DWG | | | | | | | | | |
|---|-------------------------|---------------------|--------------------|---------------|----------------|-----|---------------------|--|--|
| PREJIMINARY PLANS NOT FOR CONSTRUCTION 4-25-19 CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST. TULSA OK 74112 / PH: 918.437.0282 / WWW.GUYENGR.COM BY DATE BY DATE PLAN SCALE: DRAWN DJB DESIGNED DWG SURVEY PROFILE SCALE: PROJ. MGR. | C00/ | ELM CREEK WEST POND | | | | | | | |
| NOT FOR CONSTRUCTION 4-25-19 CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 916.437.0282 / WWW.GUYENGR.COM BY DATE PLAN SCALE: DRAWN DJB DESIGNED DWG SURVEY PROFILE SCALE: PROJ. MGR. | | | PROJECT No. 148150 | | | | | | |
| ENGINEERING SERVICES DEPARTMENT GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 918.437.0282 / WWW.GUYENGR.COM BY DATE PLAN SCALE: DRAWN DJB APPROVED: 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 | NOT FOR CONSTRUCTION | | | | SITE PLAN 3 | | | | |
| 6910 E. 14TH ST, TULSA OK 74112 / PH: 918.437.0282 / WWW.GUYENGR.COM BY DATE PLAN SCALE: DRAWN DESIGNED DWG SURVEY SURVEY PROFILE SCALE: PROJ. MGR. | | | | | | | , | | |
| Diff Diff Diff Designed Dwg SURVEY SURVEY Diff PROFILE SCALE PROJ. MGR. SURVEY SURVEY | | | | | | | | | |
| PROFILE SCALE: PROJ. MGR. | | BY | DATE | PLAN SCALE: | DRAWN DJB | | APPROVED: | | |
| PROFILE SCALE: PROJ. MGR. | | | | 1 | DESIGNED | DWG | | | |
| | | | | | | | | | |
| | | | | PROFILE SCALE | PROJ. MGR. | | | | |
| HORIZONTAL LEAD ENGR. | | | | HORIZONTAL: | LEAD ENGR. | | | | |
| FIELD MGR. | | | | 1 | | | | | |
| VERTICAL RECOMMENDED: | | | | VERTICAL | RECOMMENDED: | | | | |
| DESIGN MANAGER CITY ENGINEER | | | | | DESIGN MANAGER | | CITY ENGINEER | | |
| DATE: | | | | | | | DATE: | | |
| FILE: DRAWING: PAGE NO. E-5 | | | | FILE: | DRAW | NG: | PAGE NO. E-5 | | |
| ATLAS PAGE NO: 01 & 08 SHEET NO. 49 OF 123 | | | | ATLAS PAGE | NO: 01 & 08 | | SHEET NO. 49 OF 123 | | |



saday, April 23, 2019 4:29:06 PM DWGSVR\Server\@@@CURRENT JOBS\WEST POND\RECORD DWG'S\E-6 SITE PLAN 4

ELECTRICAL LEGEND



NOTES:

(1)

2

3

(4)

(5)

6

ALL CONDUIT TO BE BURIED UNDERGROUND A MINIMUM OF 30".

COORDINATE LOCATION OF CONDUIT WITH OTHER UNDERGROUND INFRASTRUCTURE.


SEPARATE BURIED CONDUITS TO BE USED FOR LIGHTING, RECEPTACLES AND AERATORS.

DISCONNECT FOR AERATOR TO BE LOCATED WHERE IT IS ACCESSIBLE AND CAPABLE OF BEING LOCKED OUT. DISCONNECT TO BE IN NEMA 4X STAINLESS STEEL ENCLOSURE.

LIGHTING CONTROLLER AND AERATOR CONTROLLERS TO BE IN TWO SEPARATE STAINLESS STEEL CONTROL PANELS.


LIGHT POLES ARE TO BE MOUNTED ON CONCRETE POLE BASES, 24"D AND EXTENDING 5' INTO THE GROUND. ANCHOR BOLTS TO BE A MINIMUM OF 36".

| C00/ | ELM CREEK WEST POND | | | | | | |
|------------------------------------|--|---------------------------|------|--------------------------|--|--|--|
| 60% | PROJECT No. 148150 | | | | | | |
| NOT FOR CONSTRUCTION 4-25-19 | SITE PLAN 4 | | | | | | |
| | | | , | OKLAHOMA S DEPARTMENT | | | |
| 691 | GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 918.437.0282 / WWW.GUYENGR.COM | | | | | | |
| BY DATE PLAN | SCALE: DR. | DRAWN DJB DESIGNED DWG | | APPROVED: | | | |
| | DE | | | | | | |
| | | JRVEY | | | | | |
| PROF | ILE SCALE: PR | OJ. MGR. | | | | | |
| HORIZ | CONTAL: LEA | AD ENGR. | | | | | |
| | | ELD MGR. | | | | | |
| VERT | ICAL RE | RECOMMENDED: | | | | | |
| | DE | ESIGN MANA | AGER | CITY ENGINEER | | | |
| | | | | DATE: | | | |
| FILE: | : | DRAWIN | IG: | PAGE NO. E-6 | | | |
| ATLA | AS PAGE NO: | 01 & 08 | | SHEET NO. 50 OF 123 | | | |



PM JOB 4:29:47 URRENT 23, 2019 . rver\@@@Cl April a,

ELECTRICAL LEGEND



NOTES:

2

3

4

(6)

(1)ALL CONDUIT TO BE BURIED UNDERGROUND A MINIMUM OF 30".

COORDINATE LOCATION OF CONDUIT WITH OTHER UNDERGROUND INFRASTRUCTURE.


SEPARATE BURIED CONDUITS TO BE USED FOR LIGHTING, RECEPTACLES AND AERATORS.

DISCONNECT FOR AERATOR TO BE LOCATED WHERE IT IS ACCESSIBLE AND CAPABLE OF BEING LOCKED OUT. DISCONNECT TO BE IN NEMA 4X STAINLESS STEEL ENCLOSURE.

5 LIGHTING CONTROLLER AND AERATOR CONTROLLERS TO BE IN TWO SEPARATE STAINLESS STEEL CONTROL PANELS.

LIGHT POLES ARE TO BE MOUNTED ON CONCRETE POLE BASES, 24"D AND EXTENDING 5' INTO THE GROUND. ANCHOR BOLTS TO BE A MINIMUM OF 36".

| C00/ | ELM CREEK WEST POND | | | | | | | |
|------------------------------------|---------------------|--------------------|--|--------------|------|--------------------------|--|--|
| 60% | | PROJECT No. 148150 | | | | | | |
| NOT FOR CONSTRUCTION 4-25-19 | | SITE PLAN 5 | | | | | | |
| | | | | | , | OKLAHOMA S DEPARTMENT | | |
| | | | GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 918.437.0282 / WWW.GUYENGR.COM | | | | | |
| | ΒY | DATE | PLAN SCALE: | DRAWN DJB | | APPROVED: | | |
| | | | | DESIGNED | DWG | | | |
| | | | | SURVEY | | | | |
| | | | PROFILE SCALE: | PROJ. MGR. | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | |
| | | | | FIELD MGR. | | | | |
| | | | VERTICAL | RECOMMENDED: | | | | |
| | | | | DESIGN MAN | AGER | CITY ENGINEER | | |
| | | | | | | DATE: | | |
| | | | FILE: | DRAW | NG: | PAGE NO. E-7 | | |
| | | | ATLAS PAGE | NO: 01 & 08 | | SHEET NO. 51 OF 123 | | |
| | | | | | | | | |



NOTES:

PROVIDE AND INSTALL ALL EQUIPMENT SHOWN FOR LIGHTING CONTROL.

COORDINATE WITH PSO SERVICE POLE FOR CONTROLLER AND SERVICE. PROVIDE ALL ASSOCIATED CONDUIT, TRENCHING AND CONCRETE SURFACE REPAIR. PAY ANY REQUIRED SERVICE CHARGES TO AEP/PSO FOR ELECTRICAL SERVICE.


ALL CIRCUIT WIRES TO BE (2)#4, (1)#8G. CONDUIT FROM CONTROLLERS TO LIGHT POLES TO BE 2" PVC BURIED 24" BELOW GRADE.

ALL WIRE FROM POLE BASES TO FIXTURES TO BE #12 THHN/THWN UNLESS SHOWN OTHERWISE. PROVIDE GROUND FOR ALL LIGHTS (SEPARATE FROM NEUTRAL).

MOUNT LIGHTING CONTROLLER ON 4" THICK CONCRETE PAD WITH BOTTOM EXITING

ELM CREEK WEST POND PROJECT No. 148150 LIGHTING CONTROLLER SCHEMATIC 1 CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 918.437.0282 / WWW.GUYENGR.COM PLAN SCALE: DRAWN DJB APPROVED: BY DATE DESIGNED DWG SURVEY PROFILE SCALE: PROJ. MGR. LEAD ENGR. HOR ZONTAL FIELD MGR. RECOMMENDED /ERTICAL DESIGN MANAGER CITY ENGINEER DATE: DRAWING: PAGE NO. E-8 FILE: ATLAS PAGE NO: 01 & 08 SHEET NO. 52 OF 123






sday, . WGSVI

NOTES:

- (1) PROVIDE AND INSTALL ALL EQUIPMENT SHOWN FOR LIGHTING CONTROL.
 - COORDINATE WITH PSO SERVICE POLE FOR CONTROLLER AND SERVICE. PROVIDE ALL ASSOCIATED CONDUIT, TRENCHING AND CONCRETE SURFACE REPAIR. PAY ANY REQUIRED SERVICE CHARGES TO AEP/PSO FOR ELECTRICAL SERVICE.
- (3) ALL CIRCUIT WIRES TO BE (2)#4, (1)#8G. CONDUIT FROM CONTROLLERS TO LIGHT POLES TO BE 2" PVC BURIED 24" BELOW GRADE.
 - ALL WIRE FROM POLE BASES TO FIXTURES TO BE #12 THHN/THWN UNLESS SHOWN OTHERWISE. PROVIDE GROUND FOR ALL LIGHTS (SEPARATE FROM NEUTRAL).
 - MOUNT LIGHTING CONTROLLER ON 4" THICK CONCRETE PAD WITH BOTTOM EXITING CONDUITS.

| C00/ | E | ELM CREEK WEST POND | | | | | | | |
|------------------------------------|--------------|--|--------------|------|--------------------------|--|--|--|--|
| 60% PRELIMINARY PLANS | | PROJECT No. 148150 | | | | | | | |
| NOT FOR CONSTRUCTION 4-25-19 | LI | GHTING CO | NTR | OLLE | R SCHEMATIC 2 | | | | |
| | С | | | | OKLAHOMA S DEPARTMENT | | | | |
| | 6910 E. 14 | GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 918.437.0282 / WWW.GUYENGR.COM | | | | | | | |
| BY DA | TE PLAN SCAI | E: DRAWN | DJB | | APPROVED: | | | | |
| | | DESIGNED | DWG | | | | | | |
| | | SURVEY | SURVEY | | | | | | |
| | PROFILE SCA | LE PROJ. MGR. | | | | | | | |
| | HORIZONTAL | LEAD ENGR. | | | | | | | |
| | | FIELD MGR. | | | | | | | |
| | VERTICAL | RECOMMENT | RECOMMENDED: | | | | | | |
| | | DESIGN MAN | IAGER | | CITY ENGINEER | | | | |
| | | | | | DATE: | | | | |
| | FILE: | DRAW | NG: | | PAGE NO. E-9 | | | | |
| | ATLAS PAG | GE NO: 01 & 08 | | | SHEET NO. 53 OF 123 | | | | |



PM 23, 2019 4:32:54 ver\@@@CURRENT April ay,

PROVIDE AND INSTALL ALL EQUIPMENT SHOWN FOR LIGHTING CONTROL.


COORDINATE WITH PSO SERVICE POLE FOR CONTROLLER AND SERVICE. PROVIDE ALL ASSOCIATED CONDUIT, TRENCHING AND CONCRETE SURFACE REPAIR. PAY ANY REQUIRED SERVICE CHARGES TO AEP/PSO FOR ELECTRICAL SERVICE.

ALL CIRCUIT WIRES TO BE (2)#4, (1)#8G. CONDUIT FROM CONTROLLERS TO LIGHT POLES TO BE 2" PVC BURIED 24" BELOW GRADE.

ALL WIRE FROM POLE BASES TO FIXTURES TO BE #12 THHN/THWN UNLESS SHOWN OTHERWISE. PROVIDE GROUND FOR ALL LIGHTS (SEPARATE FROM NEUTRAL).


MOUNT LIGHTING CONTROLLER ON 4" THICK CONCRETE PAD WITH BOTTOM EXITING CONDUITS.


| 600/ | EL | ELM CREEK WEST POND | | | | | | |
|------------------------------------|----------------|--|-----|--------------------------|--|--|--|--|
| 60% | | PROJECT No. 148150 | | | | | | |
| NOT FOR CONSTRUCTION 4-25-19 | AEI | AERATOR CONTROLLER SCHEMATIC | | | | | | |
| | | | , | OKLAHOMA S DEPARTMENT | | | | |
| | | GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 918.437.0282 / WWW.GUYENGR.COM | | | | | | |
| BY DATE | PLAN SCALE: | DRAWN DJB DESIGNED DWG | | APPROVED: | | | | |
| | | | | _ | | | | |
| | | SURVEY | | | | | | |
| | PROFILE SCALE: | PROJ. MGR. | | | | | | |
| | HORIZONTAL: | LEAD ENGR. | | _ | | | | |
| | | FIELD MGR. RECOMMENDED: | | | | | | |
| | VERTICAL | | | | | | | |
| | | | | CITY ENGINEER | | | | |
| | | | | DATE: | | | | |
| | FILE: | DRAW | NG: | PAGE NO. E-10 | | | | |
| | ATLAS PAGE | NO: 01 & 08 | | SHEET NO. 54 OF 123 | | | | |



AE YOU ALL OF

POND BOTTOM -







FOUNTAIN AERATOR SCHEMATIC NOTES

- CIRCUIT BREAKER TO BE GROUND FAULT INTERRUPTING BREAKER, SIZED PER VENDOR REQUIREMENTS.
- SIZE MOTOR STARTER AND OVERLOADS PER MOTOR SPECIFICATIONS FROM AERATOR SUPPLIER.
- POWER MONITOR TO HAVE VISIBLE FAULT INDICATOR LIGHT AND MANUAL RESET BUTTON.
- 4. TIMER TO BE ASTRONOMIC TIMER WITH BATTERY BACKUP FOR PROGRAM.
- LABEL PANEL "FOUNTAIN CONTROL PANEL" WITH ENGRAVED NAMEPLATE. LETTERS TO BE WHITE, 5/6" TALL MINIMUM ON BLACK BACKGROUND. LABEL TO BE PLASTIC.
- LOCAL DISCONNECTS ARE TO BE STAINLESS STEEL NEMA 4X 3R.
- PROVIDE MOORING CABLES TO ANCHOR AERATOR AND PREVENT IT FROM DRIFTING.
- AERATOR EQUIPMENT COVERED IN LANDSCAPE DESIGN SCOPE OF WORK, AERATOR CONTROL PANEL, WIRING AND INSTALLATION TO BE COVERED IN ELECTRICAL SCOPE OF WORK.
- 9. WIRE TO BE SIZED TO ACCOUNT FOR VOLTAGE DROP AND MULTIPLE CIRCUITS IN A CONDUIT.
- 10. ALL WIRE TO BE COPPER.


| 600/ | ELM CREEK WEST POND | | | | | | | |
|------------------------------------|---------------------|----------------|--|---------|------------|------|------|----|
| 60% | PROJECT No. 148150 | | | | | | | |
| NOT FOR CONSTRUCTION 4-25-19 | | POND EL | ECTRICAL | DETAIL | S 2 | | | |
| | | | | ULSA, O | | | /IA | |
| | | | GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 918.437.0282 / WWW.GUYENGR.COM | | | | | |
| BY | DATE | PLAN SCALE: | | | APPROVED: | | | |
| | | | DESIGNED DWG SURVEY | | - | | | |
| | | | | | - | | | |
| | | PROFILE SCALE: | PROJ. MGR. | | | | | |
| | | HORIZONTAL: | LEAD ENGR. | | | | | |
| | | | FIELD MGR. | | | | | |
| | | VERTICAL | RECOMMENDED: | | | | | |
| | | | DESIGN MANAGER | | CITY ENGIN | IEER | | - |
| | | | | | DATE: | | | |
| | | FILE: | DRAW | NG: | PAGE NO. | E-12 | | |
| | | ATLAS PAGE | NO: 01 & 08 | | SHEET NO. | 56 | OF 1 | 23 |



HOLOPHANE - PTUE2 - LATERN POST TOP LED SERIES




HOLOPHANE - GPDRETRO2 - GRANVILLE II LED PRISMATIC ACORN GLASS SERIES



HOLOPHANE - COLORADO DECORATIVE CAST ALUMINUM POLES SERIES








HOLOPHANE - DUNWOODY DECORATIVE CAST ALUMINUM POLES SERIES



luesday, April 23, 2019 4:18:46 PM \\DwGSVR\Server\@@@CURRENT JOBS\ HOLOPHANE - AUCL2 - POST TOP FULL CUTOFF LED SERIES





HOLOPHANE - CHARLESTON DECORATIVE CAST ALUMINUM POLES SERIES



NOTES:

(1)
 (2)
 (3)
 (4)

(5)

LIGHTING DESIGN UTILIZES A STANDARD LED FIXTURE OF 139W, OUTPUTTING APPROXIMATELY 12,800 LUMENS .


LIGHTS ARE FOR THE SIDEWALK AND PEDESTRIAN AREAS (NOT STREET LIGHTING). FOR THIS REASON, POLES ARE 12' TALL.

LIGHT FIXTURE ARE TO BE DARK SKY COMPATIBLE WITH LIGHT DIRECTED TO THE GRADE LEVEL. DESIGN ASSUMES STANDARD TYPE III DISTRIBUTION.

MULTIPLE FIXTURES AND POLES ARE AVAILABLE WITHIN THESE SPECIFICATIONS IN VARIOUS STYLES (BOTH POLES AND LUMINAIRES). EXACT LOOK CAN BE DETERMINED LATER AFTER GETTING INPUT FROM COMMUNITY STAKEHOLDERS.

ALL DESIGN IS BASED ON UNDERGROUND CONDUIT AND WIRE. CONDUIT TO BE SCHEDULE 40 PVC. WIRE TO BE COPPER.

| 60% | EL | ELM CREEK WEST POND | | | | | | |
|------------------------------------|-----------------------|--|-----|-------|------------|------|-----------|-----|
| | | PROJE | EC | Γ No | . 14815 | 0 | | |
| NOT FOR CONSTRUCTION 4-25-19 | LIG | HTING & F | POL | e Mol | JNTING D |)ET4 | NL | |
| | | Y OF T | | , | | | 1A | |
| | | GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 918.437.0282 / WWW.GUYENGR.COM | | | | | | |
| BY DATE | PLAN SCALE: DRAWN DJB | | | | APPROVED: | | | |
| | | DESIGNED DWG | | | | | | |
| | | SURVEY | | | | | | |
| | PROFILE SCALE: | | | | | | | |
| | HORIZONTAL: | LEAD ENGR. | | | | | | |
| | | FIELD MGR. | | | | | | |
| | VERTICAL | RECOMMENDED: | | | | | | |
| | | DESIGN MANAGER | | | CITY ENGIN | IEER | | - |
| | | | | | DATE: | | | |
| | FILE: | DRAW | NG: | | PAGE NO. | E-13 | | |
| | ATLAS PAGE | NO: 01 & 08 | | | SHEET NO. | 57 | OF 1 | 123 |



CALONIE

PHOTOMETRIC READINGS:

(1) THE FOLLOWING READINGS ARE BASED OFF OF A TOTAL LLF OF .95.

> AVERAGE - 1.75 FC MAXIMUM - 5.5 FC MINIMUM - 0.25 FC MAX/MIN - 35.15 AVERAGE/MIN - 7.0:1

NOTES:

1


2

(3)

THE FOLLOWING READINGS ARE BASED OFF A TOTAL OF 96 FIXTURES DISTRIBUTED AS SHOWN ON THE PLANS.

READINGS ARE TAKEN 36" ABOVE THE GRADE LEVEL.

| 000/ | EL | ELM CREEK WEST POND | | | | | | |
|------------------------------------|--------|--|----------------|-----------|--------------------------|---------------------|--|--|
| 60% | | PROJECT No. 148150 | | | | | | |
| NOT FOR CONSTRUCTION 4-25-19 | | PHOTOMETRIC 1 | | | | | | |
| | | | | | OKLAHOMA S DEPARTMENT | | | |
| | | GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 918.437.0282 / WWW.GUYENGR.COM | | | | | | |
| B | Y DATE | PLAN SCALE: DRAWN DJB | | APPROVED: | | | | |
| | |] | DESIGNED | DWG | | | | |
| | | | SURVEY | | | | | |
| | | PROFILE SCALE: | PROJ. MGR. | | | | | |
| | | HORIZONTAL: | LEAD ENGR. | | | | | |
| | | 1 | FIELD MGR. | | | | | |
| | | VERTICAL | RECOMMENDED: | | | | | |
| | | 1 | DESIGN MANAGER | | | CITY ENGINEER | | |
| | | 1 | | | | DATE: | | |
| | | FILE: | DRAW | NG: | | PAGE NO. E-14 | | |
| | | ATLAS PAGE | NO: 01 & 08 | | | SHEET NO. 58 OF 123 | | |



lay, April 23, 2019 4:21:59 PM (6SVR) Server @@@CURRENT JOBS/ WEST POND/ RECORD DWG'S/E-15 PHOTOMETRIC

PHOTOMETRIC READINGS:

1 THE FOLLOWING READINGS ARE BASED OFF OF A TOTAL LLF OF .95.

> AVERAGE - 1.75 FC MAXIMUM - 5.5 FC MINIMUM - 0.25 FC MAX/MIN - 35.15 AVERAGE/MIN - 7.0:1

NOTES:

1


2

(3)

THE FOLLOWING READINGS ARE BASED OFF A TOTAL OF 96 FIXTURES DISTRIBUTED AS SHOWN ON THE PLANS.

READINGS ARE TAKEN 36" ABOVE THE GRADE LEVEL.

| 60% | | | ELM CREEK WEST POND | | | | | | |
|------------------------------------|----|------|--|----------------|--------------------------|-------|---------------------|--|--|
| | | | PROJECT No. 148150 | | | | | | |
| NOT FOR CONSTRUCTION 4-25-19 | | | | PH | ото | OMETI | RIC 2 | | |
| | | | | | OKLAHOMA S DEPARTMENT | | | | |
| | | | GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 918.437.0282 / WWW.GUYENGR.COM | | | | | | |
| B | 3Y | DATE | PLAN SCALE: DRAWN DJB | | APPROVED: | | | | |
| | | | | DESIGNED | DWG | | | | |
| | | | | SURVEY | | | | | |
| | | | PROFILE SCALE: | PROJ. MGR. | | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | | |
| | | | | FIELD MGR. | | | | | |
| | | | VERTICAL | RECOMMENDED: | | | | | |
| | | | | DESIGN MANAGER | | | CITY ENGINEER | | |
| | | | I | | | | DATE: | | |
| | | | FILE: | DRAW | NG: | | PAGE NO. E-15 | | |
| | | | ATLAS PAGE | NO: 01 & 08 | | | SHEET NO. 59 OF 123 | | |



tuesday, April 23, 2019 4:22:47 PM \\ DWGSVR'Server\ @@@@CIREENT_IORS\ WEST_POND\ RECORD_DWG'S\ E-1.6_PHOTOMETRIC_3.

PHOTOMETRIC READINGS:

1 THE FOLLOWING READINGS ARE BASED OFF OF A TOTAL LLF OF .95.

> AVERAGE - 1.75 FC MAXIMUM - 5.5 FC MINIMUM - 0.25 FC MAX/MIN - 35.15 AVERAGE/MIN - 7.0:1

NOTES:

1


2

(3)

THE FOLLOWING READINGS ARE BASED OFF A TOTAL OF 96 FIXTURES DISTRIBUTED AS SHOWN ON THE PLANS.

READINGS ARE TAKEN 36" ABOVE THE GRADE LEVEL.

| C00/ | ELM CREEK WEST POND | | | | | | | | |
|------------------------------------|---------------------|--------------|--|------------|------------------------|--|---------------|--|--|
| 60% | PROJECT No. 148150 | | | | | | | | |
| NOT FOR CONSTRUCTION 4-25-19 | PHOTOMETRIC 3 | | | | | | | | |
| | | | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | | | |
| | | | GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 918.437.0282 / WWW.GUYENGR.COM | | | | | | |
| E | вү | DATE | PLAN SCALE: | DRAWN | DJB | | APPROVED: | | |
| | | | | DESIGNED | DWG | | | | |
| | | | | SURVEY | | | | | |
| | | | PROFILE SCALE: | PROJ. MGR. | | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | | |
| | | | | | | | | | |
| | VERTICAL | RECOMMENDED: | | | | | | | |
| | | | | | AGER | | CITY ENGINEER | | |
| | | | | | | | DATE: | | |
| | | | FILE: | DRAW | NG: | | PAGE NO. E-16 | | |
| | | | | | ATLAS PAGE NO: 01 & 08 | | | | |



sday, April 23, 2019 4:23:34 PM WGSVR\Ssever\@@@@CURRENT_JOBS\WEST_POND\RECORD_DWG'S\E-17_PHOTOMETRIC_4.c

ROPE VOL 9 BLI OKIE

PHOTOMETRIC READINGS:

(1) THE FOLLOWING READINGS ARE BASED OFF OF A TOTAL LLF OF .95.

> AVERAGE - 1.75 FC MAXIMUM - 5.5 FC MINIMUM - 0.25 FC MAX/MIN - 35.15 AVERAGE/MIN - 7.0:1

NOTES:

1


2

(3)

THE FOLLOWING READINGS ARE BASED OFF A TOTAL OF 96 FIXTURES DISTRIBUTED AS SHOWN ON THE PLANS.

READINGS ARE TAKEN 36" ABOVE THE GRADE LEVEL.

| 000/ | ELM CREEK WEST POND | | | | | | | |
|------------------------------------|---------------------|----------------|--|------------|------------------------|--|---------------|--|
| 60% | PROJECT No. 148150 | | | | | | | |
| NOT FOR CONSTRUCTION 4-25-19 | PHOTOMETRIC 4 | | | | | | | |
| | | | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | | |
| | | | GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 918.437.0282 / WWW.GUYENGR.COM | | | | | |
| B | Y DA | ATE | PLAN SCALE: | DRAWN | DJB | | APPROVED: | |
| | | | | DESIGNED | DWG | | | |
| | | | | SURVEY | | | | |
| | | | PROFILE SCALE: | PROJ. MGR. | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | |
| | | | | FIELD MGR. | | | | |
| | VERTICAL | RECOMMENDED: | | | | | | |
| | | DESIGN MANAGER | | | CITY ENGINEER | | | |
| | | | I | | | | DATE: | |
| | | | FILE: | DRAW | NG: | | PAGE NO. E-17 | |
| | | | | | ATLAS PAGE NO: 01 & 08 | | | |



isday, April 23, 2019 4:24:25 PM DWSSYR, Server, @@@CURRENT JOBS/ WEST POND/ RECORD DWG'S/ E-18 PHOTOMETRIC 5.c

PHOTOMETRIC READINGS:

(1) THE FOLLOWING READINGS ARE BASED OFF OF A TOTAL LLF OF .95.

> AVERAGE - 1.75 FC MAXIMUM - 5.5 FC MINIMUM - 0.25 FC MAX/MIN - 35.15 AVERAGE/MIN - 7.0:1

NOTES:

1

2

(3)

THE FOLLOWING READINGS ARE BASED OFF A TOTAL OF 96 FIXTURES DISTRIBUTED AS SHOWN ON THE PLANS.

READINGS ARE TAKEN 36" ABOVE THE GRADE LEVEL.

| C00/ | ELM CREEK WEST POND | | | | | | |
|------------------------------------|--|----------------|------------|-----|---------------------|---------------|--|
| 60% | PROJECT No. 148150 | | | | | | |
| NOT FOR CONSTRUCTION 4-25-19 | PHOTOMETRIC 5 | | | | | | |
| | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | | | |
| | GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 918.437.0282 / WWW.GUYENGR.COM | | | | | | |
| BY | BY DATE | | | DJB | | APPROVED: | |
| | | | DESIGNED | DWG | | | |
| | | | SURVEY | | | | |
| | | | PROJ. MGR. | | | | |
| | | | LEAD ENGR. | | | | |
| | | | | | | | |
| | VERTICAL | RECOMMENDED: | | | | | |
| | 1 | DESIGN MANAGER | | | CITY ENGINEER | | |
| | | | | | | DATE: | |
| | | FILE: | DRAW | NG: | | PAGE NO. E-18 | |
| | ATLAS PAGE NO: 01 & 08 | | | | SHEET NO. 62 OF 123 | | |

RETAINING WALL NOTES

RETAINING WALL NOTES:

SPECIFICATIONS:

COMPLY WITH THE REQUIREMENTS OF THE 2009 OKLAHOMA DEPARTMENT OF TRANSPORTATION (ODOT) STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION, EXCEPT AS MODIFIED BY THE PLANS.

GENERAL NOTES:

THE DOUBLE CASING METHOD OF DRILLED SHAFT CONSTRUCTION SHALL NOT BE ALLOWED. TEMPORARY MAY BE USED AS NECESSARY.

THE GEOTECHNICAL REPORTS WERE PREPARED BY TERRACON FOR THIS PROJECT.

| TERRACON PROJECT NO. | DATE | DESCRIPTION |
|-------------------------|------------------|---|
| 04175021 | March 21, 2017 | 6th Street / Elm Creek West Pond |
| 04175021 | October 11, 2018 | 6th Street / Elm Creek West Pond Addendum |
| | | |

LOCATIONS OF SOIL BORINGS ARE SHOWN ON THE PLANS. THE GEOTECHNICAL REPORTS ARE AVAILABLE FOR REVIEW AT THE OFFICE OF BENHAM DESIGN, ONE WEST 3RD ST., SUITE 200, TULSA, OK 74103. ANY INFORMATION CONTAINED IN THE GEOTECHNICAL REPORTS SHOULD NOT BE CONSTRUED AS REPRESENTATIVE OF ALL FIELD CONDITIONS.

EXCAVATIONS ARE ANTICIPATED TO EXTEND THROUGH SAND, CLAY, SOFT ROCK, AND HARD ROCK. EXCAVATIONS IN HARD ROCK WILL REQUIRE PNEUMATIC RAM HOES.

DRILLED SHAFTS WILL BEAR EITHER IN SAND OR SHALE/SANDSTONE BEDROCK. CONSTRUCTING PIERS IN THE SAND WILL REQUIRE THE USE OF MUD SLURRY. CONSTRUCTING DRILLED SHAFTS IN BEDROCK WILL REQUIRE THE USE OF A HEAVY-DUTY DRILLING RIG EQUIPPED WITH A ROCK AUGER OR CORE BARREL.

SPECIAL PROVISIONS:

REFER TO ODOT SPECIAL PROVISION 516-3(a-s)09 FOR CROSS-HOLE SONIC LOGGING (CSL) TUBES AND TESTING.

DESIGN DATA:

DESIGN RETAINING WALLS HAVE BEEN DESIGNED IN ACCORDANCE WITH THE REQUIREMENTS OF AASHTO STANDARD SPECIFICATIONS FOR HIGHWAY BRIDGES 17TH EDITION.


MATERIAL CONCRETE IN RETAINING WALL STEMS, FOOTINGS, AND GRADE BEAMS SHALL BE CLASS A, F'C = 3,000 PSI.

CONCRETE IN DRILLED SHAFTS SHALL BE CLASS AA, F'C = 4,0000 PSI.

REINFORCING STEEL FOR RETAINING WALLS SHALL BE GRADE 60.


BACKFILL FOR RETAINING WALLS MAY BE ON-SITE NATIVE MATERIAL, EXISTING FILL OR IMPORTED FILL AND SHALL CLASSIFY AS A-1, A-2-4 AND A-3 SOILS, PER THE AASHTO SOIL CLASSIFICATION. IN ADDITION, ON-SITE NATIVE MATERIAL, EXISTING FILL OR IMPORTED FILL SHALL MEET THE REQUIREMENTS OF ODOT SECTION 705, SELECT BORROW.

| 60% PRELIMINARY PLANS NOT FOR | | | | ۱o. | 148150 | l | | | | |
|-------------------------------------|--|------------|---------------|-----|----------|----|-----|--|--|--|
| PRELIMINARY PLANS NOT FOR | | GF | | | | | | | | |
| CONSTRUCTION | | 01 | GENERAL NOTES | | | | | | | |
| 4-26-19 | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | | | | | | |
| e | GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 918.437.0282 / WWW.GUYENGR.COM | | | | | | | | | |
| REVISION BY DATE PL | PLAN SCALE: DRAWN JT APPROVED: | | | | | | | | | |
| | | DESIGNED | KSJ | | | | | | | |
| | | SURVEY | | | | | | | | |
| PRI | ROFILE SCALE | PROJ. MGR. | | | | | | | | |
| но | DRIZONTAL: | LEAD ENGR. | 2. | | | | | | | |
| | L | FIELD MGR. | | | 7 | | | | | |
| VE | VERTICAL RECOMMENDED: | | | | | | | | | |
| | DESIGN MANAGER | | | | | ER | _ | | | |
| | DATE: | | | | | | | | | |
| FIL | LE: | DRAWIN | 1G: | 1 | PAGE NO. | | S01 | | | |
| AT | ATLAS PAGE NO: 01 & 08 SHEET NO. 63 OF | | | | 123 | | | | | |




PLAN SCALE: 1" = 50'


| | ELM CREEK WEST POND | | | | | | | | | |
|--|---------------------|--|--|----------------|--------------|--|---------------|------|-------|--|
| 60% PRELIMINARY PLANS NOT FOR CONSTRUCTION 4-26-19 | | | PROJECT No. 148150 | | | | | | | |
| | | | RETAINING WALL LOCATIONS | | | | | | | |
| | | | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | | | | |
| | | | GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 918.437.0282 / WWW.GUYENGR.COM | | | | | | | |
| REVISION | REVISION BY DATE | | | | JT | | APPROVED: | | | |
| | | | | DESIGNED | KSJ | | | | | |
| | | | | SURVEY | | | | | | |
| | | | | PROJ. MGR. | | | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | | | |
| | | | | FIELD MGR. | | | | | | |
| | | | | | RECOMMENDED: | | | | | |
| | | | | DESIGN MANAGER | | | CITY ENGINEER | | | |
| | | | | | | | DATE: | | | |
| | | | FILE: | DRAW | NG: | | PAGE NO. | | S02 | |
| | | | ATLAS PAGE | NO: 01 & 08 | | | SHEET NO. | 64 O | F 123 | |
































STA. 60+35 END RETAINING


















































LEGEND




RETAINING WALL **RETAINING WALL FOOTING** BORING LOCATION






| | | | EL | M CRE | Εŀ | K WI | EST PO | ND | | | | |
|--|--|------|----------------|--------------------|-------|------|---------------------------------|----|-------|--|--|--|
| 60% | $\overline{\ }$ | | | PROJECT No. 148150 | | | | | | | | |
| PRELIMINARY PL NOT FOR CONSTRUCTIO | | 5 | | TYPICAL SECTIONS | | | | | | | | |
| 4-26-19 | | / | | | | | OKLAHC 5 DEPARTME | | L. | | | |
| | | | | | | | ERVICES, IN 137.0282 / WWW.G | | R.COM | | | |
| REVISION | BY | DATE | PLAN SCALE: | DRAWN | JT | | APPROVED: | | | | | |
| | | | | DESIGNED | KSJ | | | | | | | |
| | | | | SURVEY | | | | | | | | |
| | | | PROFILE SCALE: | PROJ. MGR. | | | | | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | | | | | |
| | | | | FIELD MGR. | | | | | | | | |
| | | | | | DED: | | | | | | | |
| | | | | | AGER | | CITY ENGINEE | ER | - | | | |
| | | | | | DATE: | | | | | | | |
| | | | | | | | PAGE NO. | | S14 | | | |
| | ATLAS PAGE NO: 01 & 08 SHEET NO. 76 OF | | | | | 123 | | | | | | |




<u>RCB PENETRATION DETAIL</u> <u>AT WALL B-1</u>




NOTES:


- SEE ODOT STD LECS-4 FOR SEALED EXPANSION JOINT DETAIL DOWEL DETAILS, DIMENSIONS AND NOTES, EXCEPT AS SHOWN OTHERWISE. BACKER ROD & SEALER TYP. BOTH SIDES OF WALL AND TOP SIDE OF FOOTING.
- 2. DOWEL, WATERSTOP, EXPANSION JOINT MATERIAL, BACKER ROD, SEALER, WATERLINE WALL PENETRATION SEAL, AND ALL COST OF LABOR, MATERIALS, TOOLS, AND OTHER INCIDENTALS SHALL BE INCLUDED IN THE PRICE BID FOR CLASS A CONCRETE.
- 3. WHERE A SAWCUT LINE IS DESIGNATED, THE USE OF A CONSTRUCTION JOINT IS PERMITTED IF THE CONTRACTOR PREFERS OR FINDS IT NECESSARY.

<u>TYPICAL EXPANSION JOINT</u> <u>RETAINING WALL</u> SEE GP&E FOR LOCATIONS








ładnesday, April 24, 2019 9:09:46 AM 2.16-1050E Elm Ck West Pond, 148150-1, COT/CIV3D/PLANS/1050-DEM





| | | DEMOLITION LE | GEND |
|--|---------|---------------|--------------------------------------|
| REMOVE ROADWAY PAVEMENT REMOVE EXISTING BUILDING (BY OTHERS) REMOVE EXISTING SIDEWALK REMOVE EXISTING TRAIL SAW CUT FULL DEPTH E DONE BY | | | REMOVE CONCRETE DRIVEWAY/PARKING |
| REMOVE EXISTING BUILDING (BY OTHERS) REMOVE EXISTING SIDEWALK REMOVE EXISTING TRAIL SAW CUT FULL DEPTH E DONE BY | | | REMOVE ASPHALT DRIVEWAY/PARKING |
| E REMOVED REMOVE EXISTING SIDEWALK REMOVE EXISTING TRAIL SAW CUT FULL DEPTH E DONE BY E DONE BY | N | | REMOVE ROADWAY PAVEMENT |
| E REMOVED E DONE BY E DONE | J | | REMOVE EXISTING BUILDING (BY OTHERS) |
| E REMOVED SAW CUT FULL DEPTH | | | REMOVE EXISTING SIDEWALK |
| E DONE BY SAW CUT FULL DEPTH EXISTING RIGHT OF WAY | | | REMOVE EXISTING TRAIL |
| DONE BY | | | SAW CUT FULL DEPTH |
| | DONE BY | | EXISTING RIGHT OF WAY |
| | BONE BT | | CONSTRUCTION REFERENCE LINE (CRL) |
















SECTIC




THIS DOCUMENT IS PRELIMINARY IN NATURE AND IS NOT A FINAL, SIGNED AND SEALED DOCUMENT

| LEI | NGTH OF DRIVE ON SUM | MARY | ' THIS SHEI | T | | | | |
|------------|--|-------|-------------|--|--|---|--|---|
| N PL 4 | CTION ANS, TRANSITION D 0° ON RETURNS | | | | RIES | | | 1 |
| | | 6" 6" | | JC | CR EXISTING DINT SS SECTION | | | |
| | 4'-0" ITION FROM 12" TO 6" GGREGATE BASE | | NC AG | E SEPARATO RMALLY WF GREGATE IS E DRIVEWA | RAPS THE 12 S TO BE LAID | ") UNDE | ĒR | |
| | | | | | | | | |
| <u>10</u> | N A-A | | | EL | | | | EST POND |
|) | N A-A Scale | | | EL | PROJE | ЕСТ | No | EST POND . 148150 DETAIL |
| <u>10</u> | | | | CII | PROJE DRIV TY OF T | ECT VEW TULS | AY C | . 148150 DETAIL OKLAHOMA S DEPARTMENT |
| <u>10</u> | | | | | PROJE DRIV TY OF T NGINEERIN UY ENGIN | ECT VEW TULS | AY D | . 148150 DETAIL OKLAHOMA |
| 1C | | BY | DATE | CIT E 6910 E. 14TH PLAN SCALE: | PROJE DRIV TY OF T INGINEERIN UY ENGIN IST, TULSA OK DRAWN | ECT VEW IG SEF | AY D SA, 0 RVICES NG SI PH: 918.4 01/19 | . 148150 DETAIL OKLAHOMA S DEPARTMENT ERVICES, INC. |
| 1 C | Scale | BY | DATE | CI7 E 6910 E. 14TH | PROJE DRIV TY OF T INGINEERIN UY ENGIN IST, TULSA OK | ECT VEW IG SEF IEERI 74112/1 DGD MZV | AY D SA, C RVICES NG SI PH: 918-4 | DETAIL OKLAHOMA S DEPARTMENT ERVICES, INC. 137.0282 / WWW,GUYENGR.COM |
| 1C ••• | Scale | BY | DATE | CIT E 6910 E. 14TH PLAN SCALE: | PROJE DRIV TY OF T INGINEERIN UY ENGIN IST, TULSA OK DRAWN DESIGNED SURVEY | ECT VEW IG SEF IEERI 74112/1 DGD MZV | AY C SA, C NG SI PH: 918.4 01/19 01/19 | DETAIL OKLAHOMA S DEPARTMENT ERVICES, INC. 137.0282 / WWW,GUYENGR.COM |
| | Scale | BY | DATE | CIT E 6910 E. 14TH PLAN SCALE: N/A | PROJE DRIV NGINEERIN UY ENGIN UY ENGIN UY ENGIN DESIGNED SURVEY PROJ. MGR. LEAD ENGR. | ECT VEW IG SEF IEERI 74112/I DGD MZV | AY C SA, C NG SI PH: 918.4 01/19 01/19 | DETAIL OKLAHOMA S DEPARTMENT ERVICES, INC. 137.0282 / WWW,GUYENGR.COM |
| | Scale | BY | DATE | CIT E G910 E. 14TH PLAN SCALE: N/A PROFILE SCALE: HORIZONTAL: N/A | PROJE DRIV NGINEERIN UY ENGIN IST, TULSA OK DRAWN DESIGNED SURVEY PROJ. MGR. LEAD ENGR. FIELD MGR. | ECT VEW G SEF EERI DGD MZV DMM | AY C SA, C NG SI PH: 918.4 01/19 01/19 | DETAIL OKLAHOMA S DEPARTMENT ERVICES, INC. 137.0282 / WWW,GUYENGR.COM |
| | Scale | BY | DATE | CIT E G910 E. 14TH PLAN SCALE: N/A PROFILE SCALE: HORIZONTAL: N/A VERTICAL | PROJE DRIV TY OF T INGINEERIN UY ENGIN ST. TULSA OK DRAWN DESIGNED SURVEY PROJ. MGR. LEAD ENGR. FIELD MGR. RECOMMENTE | ECT VEW FULS IG SEF EERI 74112/1 DGD MZV DMM | AY C SA, C NG SI PH: 918.4 01/19 01/19 | APPROVED: |
| | Scale | BY | DATE | CIT E G910 E. 14TH PLAN SCALE: N/A PROFILE SCALE: HORIZONTAL: N/A | PROJE DRIV NGINEERIN UY ENGIN IST, TULSA OK DRAWN DESIGNED SURVEY PROJ. MGR. LEAD ENGR. FIELD MGR. | ECT VEW FULS IG SEF EERI 74112/1 DGD MZV DMM | AY C SA, C NG SI PH: 918.4 01/19 01/19 | CITY ENGINEER |
| | Scale | BY | DATE | CIT E G910 E. 14TH PLAN SCALE: N/A PROFILE SCALE: N/A VERTICAL N/A | PROJE DRIV NGINEERIN UY ENGIN ST, TULSA OK DRAWN DESIGNED SURVEY PROJ. MGR. LEAD ENGR. FIELD MGR. RECOMMENT DESIGN MAN | ECT VEW G SEF IG | AY C SA, C NG SI PH: 918.4 01/19 01/19 | CITY ENGINEER DATE: |
| | Scale | BY | DATE | CIT E G910 E. 14TH PLAN SCALE: N/A PROFILE SCALE: HORIZONTAL: N/A VERTICAL | PROJE DRIV NGINEERIN UY ENGIN ST, TULSA OK DRAWN DESIGNED SURVEY PROJ. MGR. LEAD ENGR. FIELD MGR. RECOMMENT DESIGN MAN | ECT VEW G SEF IG | AY C SA, C NG SI PH: 918.4 01/19 01/19 | CITY ENGINEER |












24, CK



















| POSED 18" SANITAF SHEET 101 18" RCP | RY SEWER | 47H 47H 57H 57H 57H 57H 6 7 6 7 KEY MAP NOT TO SCALE |
|---|----------|--|
| | | GRAPHIC SCALE (HORIZ.) 1 inch = 20' ft. 20' 0 20' 40' 5' 0 5' 10' (VERT) 1 inch = 5' ft. |
| | | THIS DOCUMENT IS PRELIMINARY IN NATURE AND IS NOT A FINAL, SIGNED AND SEALED DOCUMENT ELM CREEK WEST POND |
| ORE OKE O | 2 010 | PROJECT No. 148150 PLAN & PROFILE |
| | olc | S. NORFOLK AVE. & E. 5TH PLACE SHEET NO. 1 OF 2 |
| | .4 | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT |
| ALL ON | | GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 918.437.0282 / WWW.GUYENGR.COM |
| REVISION | BY DATE | PLAN SCALE: DRAWN DGD 01/19 APPROVED: 1"=20' DESIGNED MZV 01/19 |
| | | SURVEY DMM 09/18 PROFILE SCALE PROJ. MGR. |
| | | HORIZONTAL: LEAD ENGR. 1"=20' FIELD MGR. |
| | | VERTICAL RECOMMENDED: 1"=5" DESIGN MANAGER CITY ENGINEER |
| | | DATE: FILE: DRAWING: PAGE NO. C20 |
| | | FILE. DRAWING. PAGE NO. 020 ATLAS PAGE NO: 01 & 08 SHEET NO. 87 0F 123 |











Wednesday, April 24, 2019 9:53:14 AM V:\16-1050F Flm Ck West Pond: 148150-1.

STORM WATER MANAGEMENT PLAN

SITE DESCRIPTION

PROJECT LIMITS: SOUTH OF 4TH STREET, NORTH OF 6TH STREET, EAST OF S.MADISON AVE. AND WEST OF S. OWASSO AVE.

PROJECT DESCRIPTION: THE PURPOSE IS TO HELP WITH FLOOD CONTROL TO ALLOW FOR REDEVELOPMENT AND TO REVITALIZE THE PEARL DISTRICT BY CONSTRUCTING THE WEST POND.

SUGGESTED SEQUENCE OF EROSION CONTROL ACTIVITIES:

PRIOR TO INITIATING SOIL DISTURBING ACTIVITIES, THE CONTRACTOR WILL INSTALL ALL PERIMETER TEMPORARY SEDIMENT CONTROLS SPECIFIED. STRIP, STOCKPILE AND STABILIZE TOPSOIL. CLEAR AND GRUB ONLY IN NECESSARY AREAS, PRESERVING AS MUCH NATIVE VEGETATION AS POSSIBLE. INSTALL, MAINTAIN AND/OR MOVE TEMPORARY SEDIMENT ITEMS WITH CONSTRUCTION OPERATIONS AS PRACTICAL, IF DIRECTED BY THE ENGINEER, PLANT TEMPORARY SEEDING, REPLACE SALVAGED TOPSOIL AND DEVICES WHEN AN ACCEPTABLE VEGETATIVE COVER (AT LEAST 70%) HAS BEEN ATTAINED. AS SITE CONDITIONS WARRANT, THE CONTRACTOR MAY CHOOSE TO MODIFY THE TYPE OR ARRANGEMENT OF SPECIFIED PRACTICES TO IMPROVE THEIR EFFECTIVENESS AS APPROVED BY THE ENGINEER. THE CONTRACTOR WILL MAINTAIN A LOG OF MAJOR SOIL DISTURBANCE ACTIVITIES, AND ALSO THE DATES OF INSTALLATION OF EROSION CONTROL MEASURES.

| | SOIL TYPE: _ | URBAN LAND-DENNIS COMPLEX |
|---|--|---|
| | TOTAL AREA OF THE CONSTRUCTION SITE: $-$ | 14.58 ACRES (635,300 SF) |
| | ESTIMATED AREA TO BE DISTURBED: | 14.58 ACRES (635,300 SF) |
| | OFFSITE AREA TO BE DISTURBED: - (FOR CONTRACTOR USE) | |
| N.dwg | TOTAL IMPERVIOUS AREA PRE-CONSTRUCTION: - | 12.45 ACRES (542,304 SF) |
| MENT PLA | TOTAL IMPERVIOUS AREA POST-CONSTRUCTION: - | 5.53 ACRES (240,887 SF) |
| am 148150-1, COT\CIV3D\PLANS\1050-STORMWATER MANAGEMENT PLAN.dwg | POST-CONSTRUCTION RUNOFF COEFFICIENT OF THE SITE: - | 0.59 |
| RMWATER | LATITUDE & LONGITUDE OF CENTER OF PROJECT: _ | 36.1542° N, 95.9786° E |
| 0-ST0 | PROJECT | WILL DISCHARGE TO: |
| IS\ 105 | NAME OF RECEIVING WATERS: _ | ARKANSAS RIVER |
| \ PLAN | SENSITIVE WATERS OR WATERSHEDS: | YES NO X |
| \cıv3[| 303(D) IMPAIRED WATERS: | YES NO X |
| , cor | IF YES, LIST IMPAIRMENT: _ | |
| 50-1 | LOCATED IN A TMDL: | YES NO X |
| AM 1481 | LAKE THUNDERBIRD TMDL: | YES NO X |
| 9:11:06 AM ist Pond, 14 | MS4 ENTITY | YES X NO |
| 19 9:1 West | IF YES, LOCATION: _ | CITY OF TULSA |
| uesday, April 23, 2019 :\16-1050E Elm Ck We: | NOTE: THIS SHEET SHOULD BE USED IN CONJU THAT ILLUSTRATES THE DRAINAGE PATTE FOR THIS PROJECT. THIS SHEET SHOUL CONTROL SUMMARIES, PAY ITEMS, & NO | RNS/PATHWAYS AND RECEIVING WATERS LD ALSO BE USED WITH THE EROSION |

AM .

EROSION AND SEDIMENT CONTROLS

SOIL STABILIZATION PRACTICES:

- X TEMPORARY SEEDING
- X PERMANENT SODDING, SPRIGGING OR SEEDING
- X VEGETATIVE MULCHING
- SOIL RETENTION BLANKET
- X PRESERVATION OF EXISTING VEGETATION

NOTE: TEMPORARY EROSION CONTROL METHODS MUST BE USED ON ALL DISTURBED AREAS WHERE CONSTRUCTION ACTIVITIES HAVE CEASED FOR OVER 14 DAYS. METHODS USED WILL BE AS SHOWN ON PLANS, OR AS DIRECTED BY THE ENGINEER.


STRUCTURAL PRACTICES:

- X STABILIZED CONSTRUCTION EXIT
- X TEMPORARY SILT FENCE
- X TEMPORARY SILT DIKES
- X TEMPORARY FIBER LOG
- DIVERSION, INTERCEPTOR OR PERIMETER DIKES
- DIVERSION, INTERCEPTOR OR PERIMETER SWALES
- ROCK FILTER DAMS
- TEMPORARY SLOPE DRAIN PAVED DITCH W/ DITCH LINER PROTECTION
- TEMPORARY DIVERSION CHANNELS
- TEMPORARY SEDIMENT BASINS TEMPORARY SEDIMENT TRAPS
- TEMPORARY SEDIMENT FILTERS
- _____ TEMPORARY SEDIMENT REMOVAL
- RIP RAF
- _ INLET SEDIMENT FILTER
- ___ TEMPORARY BRUSH SEDIMENT BARRIERS
- SANDBAG BERMS
- TEMPORARY STREAM CROSSINGS

OFFSITE VEHICLE TRACKING:

- X HAUL ROADS DAMPENED FOR DUST CONTROL
- ____X__ LOADED HAUL TRUCKS TO BE COVERED WITH TARPAULIN
- _____ EXCESS DIRT ON ROAD REMOVED DAILY

NOTES:



THE CONTRACTOR SHALL ALSO BE RESPONSIBLE FOR THE FOLLOWING:

MAINTENANCE AND INSPECTION:

ALL EROSION AND SEDIMENT CONTROLS WILL BE MAINTAINED IN GOOD WORKING ORDER FROM THE BEGINNING OF CONSTRUCTION UNTIL AN ACCEPTABLE VEGETATIVE COVER IS ESTABLISHED. INSPECTION BY THE CONTRACTOR AND ANY NECESSARY REPAIRS SHALL BE PERFORMED ONCE EVERY INSPECTION BY THE CONTRACTOR AND ANY NECESSARY REPAIRS SHALL BE PERFORMED ONCE EVERY 7 CALENDAR DAYS AND WITHIN 24 HOURS AFTER ANY STORM EVENT GREATER THAN 0.5 INCH AS RECORDED BY A NON-FREEZING RAIN GAUGE TO BE LOCATED ON SITE. POTENTIALLY ERODIBLE AREAS, DRAINAGEWAYS, MATERIAL STORAGE, STRUCTURAL DEVICES, CONSTRUCTION ENTRANCES AND EXITS ALONG WITH EROSION AND SEDIMENT CONTROL LOCATIONS ARE EXAMPLES OF SITES THAT NEED TO BE INSPECTED.

WASTE MATERIALS:

PROPER MANAGEMENT AND DISPOSAL OF CONSTRUCTION WASTE MATERIAL IS REQUIRED BY THE CONTRACTOR. MATERIALS INCLUDE STOCKPILES, SURPLUS, DEBRIS AND ALL OTHER BY-PRODUCTS FROM THE CONSTRUCTION PROCESS. PRACTICES INCLUDE DISPOSAL, PROPER MATERIALS HANDLING, SPILL PREVENTION AND CLEANUP MEASURES. CONTROLS AND PRACTICES SHALL MEET THE REQUIREMENTS OF ALL FEDERAL, STATE AND LOCAL AGENCIES.

HAZARDOUS MATERIALS:

PROPER MANAGEMENT AND DISPOSAL OF HAZARDOUS WASTE MATERIALS IS REQUIRED. CONTRACTOR IS RESPONSIBLE FOR FOLLOWING MANUFACTURER'S RECOMMENDATIONS, STATE AND FEDERAL REGULATIONS TO ENSURE CORRECT HANDLING, DISPOSAL, SPILL PREVENTION AND CLEANUP MEASURES. EXAMPLES INCLUDE BUT ARE NOT LIMITED TO: PAINTS, ACIDS, CLEANING SOLVENTS, CHEMICAL ADDITIVES, CONCRETE CURING COMPOUNDS AND CONTAMINATED SOILS.

GENERAL NOTES:

A STORM WATER POLLUTION PREVENTION PLAN (SWPPP) IS REQUIRED TO COMPLY WITH THE OKLAHOMA POLLUTION DISCHARGE ELIMINATION SYSTEM (OPDES) REGULATIONS. THIS PLAN IS INITIATED DURING THE DESIGN PHASE, CONFIRMED IN THE PRE-WORK MEETINGS AND AVAILABLE ON THE JOB SITE ALONG WITH COPIES OF THE NOTICE OF INTENT (NOI) FORM AND PERMIT CERTIFICATE THAT HAVE BEEN FILED WITH THE OKLAHOMA DEPARTMENT OF ENVIRONMENTAL CERTIFICATE THAT HAVE BEEN FILED WITH THE OKLAHOMA DEPARTMENT OF ENVIRONMENTAL QUALITY (ODEQ). THE PLAN MUST BE KEPT CURRENT WITH UP-TO-DATE AMENDMENTS DURING THE PROGRESSION OF THE PROJECT. ALL CONTRACTOR OFF-SITE OPERATIONS ASSOCIATED WITH THE PROJECT MUST BE DOCUMENTED IN THE SWPPP, I.E., BORROW PITS, WORK ROADS, DISPOSAL SITES, ASPHALT/CONCRETE PLANTS, ETC. THE BASIC GOAL OF STORM WATER MANAGEMENT IS TO IMPROVE WATER QUALITY BY REDUCING POLLUTANTS IN STORM WATER DISCHARGES. RUNOFF FROM CONSTRUCTION SITES HAS A POTENTIAL FOR POLLUTION DUE TO EXPOSED SOILS AND THE PRESENCE OF HAZARDOUS MATERIALS USED IN THE CONSTRUCTION PROCESS. THE PREVENTION OF SOIL EROSION, CONTAINMENT OF HAZARDOUS MATERIALS AND/OR THE INTERCEPTION OF THESE POLLUTANTS BEFORE LEAVING THE CONSTRUCTION SITE ARE THE BEST PRACTICES FOR CONTROLING STORM WATER POLLUTION PRACTICES FOR CONTROLLING STORM WATER POLLUTION.

BE NOTED:

- 103.05 BONDING REQUIREMENTS
- 104.10 FINAL CLEANING UP 104.12 CONTRACTOR'S RESPONSIBILITY FOR
- 104.13 ENVIRONMENTAL PROTECTION 106.08 STORAGE AND HANDLING OF MATER
- 107.01 LAWS, RULES AND REGULATIONS T
- 107.20 STORM WATER MANAGEMENT 220 MANAGEMENT OF EROSION, SEDIME
- 221 POLLUTION PREVENTION AND CONT


IN ADDITION:

"ODEQ GENERAL PERMIT (OKR10) FOR STO CONSTRUCTION ACTIVITIES WITHIN THE STAT WATER QUALITY DIVISION, SEPTEMBER 13,




THE FOLLOWING SECTIONS OF THE 2009 ODOT STANDARD SPECIFICATIONS SHOULD

| W | ORK | | | | | | | | | | |
|----------|--|----|--------|-------------------|----------------------------|----------------|---------------------|--------------------------|------|-------|-----|
| IAL B | E OBSERVED | | | | | | | | | | |
| | TION AND STORM WAT TEMPORARY SEDIMEN | | ONTROL | | | | | | | | |
| | | | | EL | M CRE | Eŀ | < WI | EST PO | ЛС | D | |
| | | | | | PROJE | ECT | ۲No. | . 14815 | 0 | | |
| ΓE (| WATER DISCHARGES F OF OKLAHOMA." ODEQ | | 1 | STO | RMWATE | ER N | /IANA | GEMEN | T PI | LAN | 1 |
| 201 | 7. | | | | Y OF T | | , | | | | |
| | | | | G 6910 E. 14TH | UY ENGIN ST, TULSA OK 3 | EER 74112 / | ING SI PH: 918.4 | ERVICES, 137.0282/WWW | | ENGR. | сом |
| | REVISION | BY | DATE | PLAN SCALE: | DRAWN | DGD | 01/19 | APPROVED | | | |
| | | | | | DESIGNED | MZV | 01/19 | | | | |
| | | | | | SURVEY | DMM | 09/18 | | | | |
| | | | | PROFILE SCALE: | PROJ. MGR. | | | | | | |
| | | | | HORIZONTAL: | LEAD ENGR. | | | | | | |
| | | | | | FIELD MGR. | | | | | | |
| | | | | VERTICAL | RECOMMEND | DED: | | | | | |
| | | | | | DESIGN MAN | AGER | | CITY ENGIN | EER | | - |
| | | | | | | | | DATE: | | | |
| | | | | FILE: | DRAWI | NG: | | PAGE NO. | | S | T11 |
| | | | | ATLAS PAGE | NO: 01 & 08 | | | SHEET NO. | 91 | OF | 123 |



uesday, April 23, 2019 9:13:16 AM 1.\16-1050E Elm Ck West Pond, 148150-1, COT\CIV3D\PLANS\1050-Drainage Area Map.c






| | | | EL | M CRE | CREEK WEST POND | | | | | | | |
|----------|----|--|--|--------------------------------------|-----------------|---------|-----------|----|----|------|--|--|
| | | | | PROJE | ECT | ۲No. | 14815 | 0 | | | | |
| | | | | DRAINAGE SHEETS DRAINAGE AREA MAP | | | | | | | | |
| | | | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | | | | | | |
| | | GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 918.437.0282 / WWW.GUYENGR.COM | | | | | | | | | | |
| REVISION | BY | DATE | PLAN SCALE: | DRAWN | DGD | 4/17/19 | APPROVED | : | | | | |
| | | | 1''=60' | DESIGNED | MZV | 4/17/19 | | | | | | |
| | | | | SURVEY | DMM | 09/18 | | | | | | |
| | | | PROFILE SCALE: | TROJ. WOR. | | | | | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | | | | | |
| | | | N/A | FIELD MGR. | | | | | | | | |
| | | | VERTICAL | RECOMMEND | DED: | | | | | | | |
| | | | N/A DESIGN MANAGER CITY ENGINEER | | | | | | | | | |
| | | | | | | | DATE: | | | | | |
| | | | FILE: | DRAWI | NG: | | PAGE NO. | | S | ST12 | | |
| | | | ATLAS PAGE | NO: 01 & 08 | | | SHEET NO. | 92 | OF | 123 | | |
| | | | | | | | | | | | | |

| | | | | | | | SUMM | ARY OF PR | OPOSE | D INLET I | DESIC | <u>SN</u> | | | | | | | |
|---------|----------------------|------------------------|-------------------------------|----------------|-----------------|----------|------------------------|-----------------------------------|----------------------------|--------------------|------------------|------------|-------------------|--------------------|-------------------|------------|--------|-------------------------|---------------------|
| STR NO. | DESIGN | NUMBER OF GRATES | NUMBER OF ADD'L THROATS | TOP OF CURB | TOP OF GRATE | FLOWLINE | INNER STR HEIGHT | LONGITUDINAL SLOPE AT INLET | CROSS SLOPE AT INLET | CLOGGING FACTOR | Q ₁₀₀ | QCARRYOVER | SUM Q AT INLET | SPREAD AT INLET | DEPTH AT INLET | QINTERCEPT | BYPASS | BYPASS TO STR NO. | INLET EFFICIENCY |
| | | | | ELEV | ELEV | ELEV | VF | % | % | | CFS | CFS | CFS | FT | FT | CFS | % | | % |
| В | INLET CI DES. 4(STD) | 4 | 0 | 682.98 | 682.44 | 678.72 | 3.72 | 0.57% | 3.13% | 1.0 | 3.38 | 0.63 | 4.01 | 10.0 | 0.31 | 4.01 | 0% | н | 100.0% |
| С | INLET CI DES. 4(STD) | 4 | 0 | 691.79 | 691.25 | 683.73 | 7.52 | 1.48% | 3.13% | 1.0 | 3.13 | - | 3.13 | 7.6 | 0.24 | 3.13 | 0% | A | 100.0% |
| D | INLET CI DES. 2(STD) | 2 | 0 | 691.79 | 691.25 | 688.64 | 2.61 | 1.40% | 3.13% | 1.0 | 2.40 | 0.69 | 3.10 | 7.7 | 0.24 | 2.47 | 20% | В | 79.8% |
| E | INLET CI DES. 4(STD) | 4 | 0 | 695.61 | 695.07 | 687.28 | 7.79 | 2.35% | 3.13% | 1.0 | 5.22 | - | 5.22 | 8.5 | 0.26 | 5.22 | 0% | С | 100.0% |
| F | INLET CI DES. 2(STD) | 2 | 0 | 695.61 | 695.07 | 692.40 | 2.67 | 1.83% | 3.13% | 1.0 | 3.49 | - | 3.49 | 7.6 | 0.24 | 2.79 | 20% | D | 80.1% |
| G | INLET CI DES. 4B | 4 | 2 | 692.12 | 691.58 | 683.63 | 7.95 | 2.04% | 3.13% | 1.0 | 5.87 | - | 5.87 | 8.3 | 0.26 | 5.87 | 0% | V | 100.0% |
| Н | INLET CI DES. 4B | 4 | 2 | 683.83 | 683.29 | 680.31 | 2.98 | 0.65% | 3.13% | 1.0 | 7.11 | - | 7.11 | 10.8 | 0.34 | 7.11 | 0% | A | 100.0% |
| Ι | | | | | | | | • | NOT U | SED | • | | | • | | | | | |
| J | INLET CI DES. 2(STD) | 2 | 0 | 684.67 | 684.13 | 681.02 | 3.11 | SUMP | 3.13% | 0.7 | 1.53 | - | 1.53 | 0.7 | 0.02 | 1.53 | 0% | - | 100.0% |
| К | INLET CI DES. 4(STD) | 4 | 0 | 686.03 | 685.49 | 681.60 | 3.89 | 1.76% | 3.13% | 1.0 | 4.33 | - | 4.33 | 8.3 | 0.26 | 4.33 | 0% | I | 100.0% |
| L | INLET CI DES. 2B | 2 | 2 | 686.23 | 685.69 | 681.97 | 3.72 | 2.27% | 3.13% | 1.0 | 1.50 | - | 1.50 | 4.6 | 0.14 | 1.50 | 0% | J | 100.0% |
| М | INLET CI DES. 2B | 2 | 2 | 692.72 | 692.18 | 688.52 | 3.66 | 0.99% | 3.13% | 1.0 | 2.99 | - | 2.99 | 7.0 | 0.22 | 2.71 | 9% | 0 | 90.9% |
| Ν | INLET CI DES. 2D | 2 | 4 | 692.64 | 692.10 | 688.67 | 3.43 | 1.29% | 3.13% | 1.0 | 6.69 | - | 6.69 | 8.5 | 0.27 | 5.64 | 16% | 0 | 84.3% |
| 0 | INLET CI DES. 2B | 2 | 2 | 690.20 | 689.66 | 685.95 | 3.71 | 2.36% | 3.13% | 1.0 | 4.12 | 1.32 | 5.44 | 7.9 | 0.25 | 4.48 | 18% | P | 82.3% |
| Р | INLET CI DES. 2D | 2 | 4 | 689.19 | 688.65 | 684.94 | 3.71 | 2.93% | 3.13% | 1.0 | 5.61 | 0.96 | 6.57 | 7.6 | 0.24 | 5.72 | 13% | Q | 87.0% |
| Q | INLET CI DES. 2B | 2 | 2 | 687.91 | 687.37 | 683.61 | 3.76 | 3.71% | 3.13% | 1.0 | 4.74 | 0.85 | 5.59 | 7.4 | 0.23 | 4.76 | 15% | U | 85.2% |
| R | INLET CI DES. 2D | 2 | 4 | 687.91 | 687.37 | 683.64 | 3.73 | 0.54% | 3.13% | 1.0 | 2.29 | - | 2.29 | 4.9 | 0.15 | 2.29 | 0% | V | 100.0% |
| S | INLET CI DES. 4D | 4 | 4 | 688.65 | 688.11 | 683.42 | 4.69 | 7.67% | 3.13% | 1.0 | 7.98 | - | 7.98 | 7.2 | 0.22 | 7.98 | 0% | U | 100.0% |
| Т | INLET CI DES. 4D | 4 | 4 | 688.50 | 687.96 | 683.94 | 4.02 | 3.39% | 3.13% | 1.0 | 3.05 | - | 3.05 | 5.2 | 0.16 | 3.05 | 0% | U | 100.0% |
| U | INLET CI DES. 2(STD) | 2 | 0 | 686.72 | 686.18 | 683.66 | 2.52 | SUMP | 3.13% | 0.7 | 5.23 | 0.83 | 6.06 | 11.5 | 0.36 | 6.06 | 0% | - | 100.0% |
| V | INLET CI DES. 4(STD) | 4 | 0 | 686.72 | 686.18 | 683.74 | 2.45 | SUMP | 3.13% | 0.7 | 3.91 | - | 3.91 | 1.2 | 0.04 | 3.91 | 0% | - | 99.9% |
| W | INLET CI DES. 4(STD) | 4 | 0 | 687.47 | 686.93 | 684.23 | 2.70 | 1.16% | 3.13% | 1.0 | 7.95 | - | 7.95 | 11.3 | 0.35 | 7.95 | 0% | U | 100.0% |
| Х | INLET CI DES. 4B | 4 | 2 | 690.13 | 689.59 | 686.02 | 3.57 | 2.23% | 3.13% | 1.0 | 13.91 | - | 13.91 | 11.7 | 0.36 | 13.91 | 0% | W | 100.0% |
| Y | INLET CI DES. 4D | 4 | 4 | 691.72 | 691.18 | 685.04 | 6.14 | 2.94% | 3.13% | 1.0 | 7.96 | - | 7.96 | 8.3 | 0.26 | 7.96 | 0% | Т | 100.0% |


| | | | | | | IARY OF | PROPO | SED PIF | PE DESIG | <u>N</u> | | | | | |
|--------------------------|---------------------|---------|--------|-------|--------|---------|-------------------|-------------------|----------|----------|--------|--------|------------------|-----------|---------|
| START NODE STR NO. | END NODE STR NO. | DIA | LENGTH | SLOPE | INV UP | INV DN | T/R UP/ T/G UP | T/R DN/ T/G DN | HGL UP | HGL DN | EGL UP | EGL DN | Q ₁₀₀ | QCAPACITY | VELOCIT |
| NU. | | INCH | LF | % | FT | FT | FT | FT | FT | FT | FT | FT | CFS | CFS | FPS |
| В | 1 | 24" RCP | 10.00 | 2.00% | 678.72 | 678.52 | 682.44 | 683.25 | 681.72 | 681.52 | 683.42 | 683.22 | 11.12 | 31.96 | 10.48 |
| С | 2 | 24" RCP | 51.00 | 1.00% | 683.73 | 683.22 | 691.25 | 691.06 | 685.38 | 684.87 | 686.42 | 685.91 | 19.21 | 22.60 | 8.20 |
| D | 3 | 18" RCP | 8.00 | 5.00% | 688.64 | 688.24 | 691.25 | 691.54 | 689.47 | 689.07 | 690.59 | 690.19 | 2.47 | 23.48 | 8.50 |
| Е | 4 | 18" RCP | 28.00 | 1.00% | 687.28 | 687.00 | 695.07 | 695.36 | 688.86 | 688.58 | 689.45 | 689.17 | 5.22 | 10.50 | 6.18 |
| F | 4 | 18" RCP | 8.00 | 5.00% | 692.40 | 692.00 | 695.07 | 695.36 | 693.36 | 692.96 | 694.55 | 694.15 | 2.79 | 23.48 | 8.77 |
| G | 17 | 18" RCP | 39.00 | 0.50% | 683.63 | 683.44 | 691.58 | 691.72 | 685.15 | 684.95 | 685.50 | 685.30 | 5.87 | 7.42 | 4.75 |
| Н | В | 18" RCP | 109.00 | 1.00% | 680.31 | 679.22 | 683.29 | 682.44 | 682.23 | 681.14 | 682.92 | 681.83 | 7.11 | 10.50 | 6.66 |
| J | 5 | 24" RCP | 19.00 | 0.50% | 681.02 | 680.93 | 684.13 | 684.40 | 682.70 | 682.61 | 683.22 | 683.13 | 10.23 | 15.98 | 5.80 |
| к | 7 | 18" RCP | 14.00 | 1.00% | 681.60 | 681.46 | 685.49 | 686.09 | 683.18 | 683.04 | 683.79 | 683.65 | 5.83 | 10.50 | 6.30 |
| L | к | 18" RCP | 37.00 | 1.00% | 681.97 | 681.60 | 685.69 | 685.49 | 682.72 | 682.35 | 683.02 | 682.65 | 1.50 | 10.50 | 4.40 |
| м | 8 | 18" RCP | 35.00 | 1.00% | 688.52 | 688.17 | 692.18 | 692.69 | 689.53 | 689.18 | 690.00 | 689.65 | 2.71 | 10.50 | 5.53 |
| N | 8 | 18" RCP | 10.00 | 5.00% | 688.67 | 688.17 | 692.10 | 692.69 | 690.29 | 689.79 | 692.18 | 691.68 | 5.64 | 23.48 | 11.03 |
| 0 | 10 | 18" RCP | 7.00 | 5.00% | 685.95 | 685.60 | 689.66 | 689.92 | 687.14 | 686.79 | 688.89 | 688.54 | 4.48 | 23.48 | 10.63 |
| P | 11 | 18" RCP | 7.00 | 5.00% | 684.94 | 684.59 | 688.65 | 688.91 | 686.52 | 686.17 | 688.40 | 688.05 | 5.72 | 23.48 | 11.03 |
| Q | 12 | 18" RCP | 7.00 | 5.00% | 683.61 | 683.26 | 687.37 | 687.63 | 685.02 | 684.67 | 686.65 | 686.30 | 4.76 | 23.48 | 10.23 |
| R | 12 | 18" RCP | 19.00 | 2.00% | 683.64 | 683.26 | 687.37 | 687.63 | 684.51 | 684.13 | 685.11 | 684.73 | 2.29 | 14.85 | 6.22 |
| S | 13 | 24" RCP | 49.00 | 1.00% | 683.42 | 682.93 | 688.11 | 686.88 | 686.32 | 685.83 | 687.31 | 686.82 | 18.99 | 22.60 | 7.98 |
| Т | S | 24" RCP | 26.00 | 2.00% | 683.94 | 683.42 | 687.96 | 688.11 | 685.74 | 685.22 | 687.04 | 686.52 | 11.01 | 31.96 | 9.16 |
| U | 14 | 18" RCP | 7.00 | 0.30% | 683.66 | 683.64 | 686.18 | 686.44 | 685.46 | 685.44 | 685.66 | 685.64 | 6.06 | 5.75 | 3.61 |
| V | 14 | 18" RCP | 19.00 | 0.50% | 683.74 | 683.64 | 686.18 | 686.44 | 684.67 | 684.57 | 684.87 | 684.77 | 3.91 | 7.42 | 3.61 |
| W | 15 | 18" RCP | 7.00 | 2.00% | 684.23 | 684.09 | 686.93 | 687.19 | 686.48 | 686.34 | 687.74 | 687.60 | 7.95 | 14.85 | 8.99 |
| Х | 16 | 24" RCP | 63.00 | 1.00% | 686.02 | 685.39 | 689.59 | 690.02 | 688.34 | 687.71 | 689.26 | 688.63 | 13.91 | 22.60 | 7.70 |
| Y | Т | 18" RCP | 110.00 | 0.55% | 685.04 | 684.44 | 691.18 | 687.96 | 686.84 | 686.24 | 687.20 | 686.60 | 7.96 | 7.75 | 4.83 |
| 3 | С | 18" RCP | 28.00 | 1.50% | 684.65 | 684.23 | 691.54 | 691.25 | 687.50 | 687.08 | 688.55 | 688.13 | 10.48 | 12.86 | 8.22 |
| 4 | 3 | 18" RCP | 294.00 | 0.80% | 687.00 | 684.65 | 695.36 | 691.54 | 689.25 | 686.90 | 689.82 | 687.47 | 8.01 | 9.39 | 6.06 |
| 5 | 6 | 24" RCP | 71.00 | 0.44% | 680.93 | 680.62 | 684.40 | 685.08 | 683.25 | 682.94 | 683.55 | 683.24 | 10.23 | 14.93 | 4.37 |
| 6 | JCT BOX 1 | 48" RCP | 10.00 | 0.50% | 678.62 | 678.57 | 685.08 | 685.08 | 683.82 | 683.77 | 685.12 | 685.07 | 78.57 | 101.54 | 9.13 |
| 7 | 6 | 48" RCP | 113.50 | 0.30% | 678.96 | 678.62 | 686.09 | 685.08 | 683.36 | 683.02 | 684.15 | 683.81 | 68.34 | 78.65 | 7.14 |
| 8 | 9 | 18" RCP | 49.00 | 2.00% | 688.17 | 687.19 | 692.69 | 691.19 | 690.98 | 690.00 | 692.18 | 691.20 | 8.35 | 14.85 | 8.82 |
| 9 | 7 | 48" RCP | 260.00 | 0.30% | 679.74 | 678.96 | 691.19 | 686.09 | 683.86 | 683.08 | 684.65 | 683.87 | 62.51 | 78.65 | 7.14 |
| 10 | 9 | 42" RCP | 115.00 | 0.35% | 680.65 | 680.24 | 689.92 | 691.19 | 684.74 | 684.34 | 688.09 | 687.69 | 54.16 | 59.52 | 14.68 |
| 11 | 10 | 42" RCP | 70.00 | 0.30% | 680.86 | 680.65 | 688.91 | 689.92 | 684.67 | 684.46 | 687.54 | 687.33 | 49.68 | 55.10 | 13.59 |
| 12 | 11 | 36" RCP | 80.00 | 0.50% | 681.76 | 681.36 | 687.63 | 688.91 | 685.75 | 685.35 | 686.64 | 686.24 | 43.96 | 47.09 | 7.59 |
| 13 | 12 | 36" RCP | 49.00 | 0.35% | 681.93 | 681.76 | 686.88 | 687.63 | 685.38 | 685.21 | 686.00 | 685.83 | 36.91 | 39.40 | 6.35 |
| 14 | 13 | 36" RCP | 71.00 | 0.30% | 682.14 | 681.93 | 686.44 | 686.88 | 684.36 | 684.15 | 684.82 | 684.60 | 17.92 | 36.48 | 5.42 |
| 15 | 14 | 24" RCP | 90.00 | 0.50% | 683.59 | 683.14 | 687.19 | 686.44 | 685.29 | 684.84 | 685.73 | 685.28 | 7.95 | 15.98 | 5.34 |
| 16 | JCT BOX 2 | 24" RCP | 35.00 | 0.50% | 685.39 | 685.22 | 690.02 | 690.49 | 687.71 | 687.54 | 688.23 | 688.06 | 13.91 | 15.98 | 5.80 |
| 17 | JCT BOX 2 | 18" RCP | 76.00 | 0.50% | 683.44 | 683.06 | 691.72 | 690.49 | 684.96 | 684.58 | 685.31 | 684.93 | 5.87 | 7.42 | 4.75 |


| | | EL | M CRE | < WE | EST PO | ЛС | D | | | |
|----------|--------|--|-------------|------------------|-----------|-----------|----|------|----|--|
| | | | PROJE | ۲No. | o. 148150 | | | | | |
| | | | | HEETS GN TABL | E | | | | | |
| | | | Y OF T | | | | 1A | | | |
| | | GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 918.437.0282 / WWW.GUYENGR.COM | | | | | | | | |
| REVISION | Y DATE | PLAN SCALE: | DRAWN | DGD | 4/3/19 | APPROVED: | | | | |
| | | N/A | DESIGNED | MZV | 4/3/19 | | | | | |
| | | | SURVEY | DMM | 09/18 | | | | | |
| | | PROFILE SCALE: | PROJ. MGR. | | | | | | | |
| | | HORIZONTAL: | LEAD ENGR. | | | | | | | |
| | | N/A | FIELD MGR. | | | | | | | |
| | | VERTICAL | RECOMMEND | DED: | | | | | | |
| | | N/A DESIGN MANAGER CITY ENGINEER | | | | | | | | |
| | | | | | | DATE: | | | | |
| | | FILE: | DRAWI | NG: | | PAGE NO. | | ST | 13 | |
| | | ATLAS PAGE | NO: 01 & 08 | | | SHEET NO. | 93 | OF 1 | 23 | |




dnesday. April 24, 2019 9:57:03 AM (16-1050E Elm Ck West Pond, 148150-1, COT/CIV3D/PLANS/1050-SITE PLAN- STORM WATER SE


| | | ×××. | | EX EX PR PR 20 PR | | ft. 60' RMWATER P RMWATER P RMWATER P ORMWATER RUCTURE LA ET LABEL ORY FLOOD DODPLAIN W | PIPE ABEL PLAIN | |
|--------------------|---|-----------------------------------|--------|----------------------------------|--------------------|--|--|------------------------|
| 8) 9) V V | THIS DOCUMEN PRELIMINA NATURE A NOT A FII SIGNED A SEALEI DOCUME | RY II ND I: NAL, ND D | N S | Ξ | | PROJE ST OV Y OF T NGINEERIN UY ENGIN ST, TULSA OK I DRAWN DESIGNED | CT NO ORM SE ER-ALL I ULSA, G SERVICES EERING SI 74112 / PH: 918.4 DGD 01/19 MZV 01/19 | |
| | | | | | PROFILE SCALE: | | DMM 09/18 | |
| | | | | | HORIZONTAL: N/A | LEAD ENGR. FIELD MGR. | | |
| | | | | | VERTICAL N/A | RECOMMENT | | CITY ENGINEER |
| | | | | | FILE: | DEGIGINIMAN | | DATE: PAGE NO. ST14 |
| | | | | | ATLAS PAGE | | | SHEET NO. 94 OF 12 |





dnesday, April 24, 2019 9:59:17 AM (16-1050E Elm Ck West Pond, 148150-1, COT\CIV3D\PLANS\1050-MISC STORM.dwg





₹ F 40:38 Pond, 2019 5:4 Ck West 23, El m April




LEGEND

'** — W —— ___w___


XXXXXXXX EXISTING WATERLINE TO BE REMOVED/ABANDONED EXISTING WATERLINE TO REMAIN EXISTING WATERLINE PROPOSED WATERLINE




| | | | | EL | M CRE | Εŀ | K WE | EST PO | ЛС | D | | |
|----|------------------------------------|----------------|------|---|----------------------------|----------|-------|-------------|-----|----|-----|--|
| Г | THIS | | - | | PROJE | ECT | No. | . 14815 | 0 | | | |
| | DOCUMEN PRELIMINAI NATURE AN | RY II ND IS | N | | WATERLINE OVER-ALL PLAN | | | | | | | |
| | NOT A FIN SIGNED A SEALEI | ND | | | Y OF T | | , | | | 1A | | |
| | DOCUME | NT | | | UY ENGIN ST, TULSA OK | | | | | | СОМ | |
| RE | VISION | ΒY | DATE | PLAN SCALE: | DRAWN | DGD | 01/19 | APPROVED: | | | | |
| | | | | 1''=60' | DESIGNED | MZV | 01/19 |] | | | | |
| | | | | | SURVEY | DMM | 09/18 |] | | | | |
| | | | | PROFILE SCALE: | PROJ. MGR. | | |] | | | | |
| | | | | HORIZONTAL: | LEAD ENGR. | | |] | | | | |
| | | | | N/A | FIELD MGR. | | | | | | | |
| | | | | VERTICAL | RECOMMEND | DED: | | | | | | |
| | | | | N/A | DESIGN MAN | AGER | | CITY ENGINE | ER | | - | |
| | | | | | | | | DATE: | | | | |
| | | | | FILE: | DRAWI | PAGE NO. | | ٧ | V10 | | | |
| | | | | ATLAS PAGE NO: 01 & 08 SHEET NO. 96 OF 12 | | | | 123 | | | | |




esday, April 24, 2019 1:00:56 PM 5-1050E Elm Ck West Pond, 148150-1, COT\CIV3D\PLANS\1050-Water P&




nesdoy, April 24, 2019 8:39:27 AM 6-1050E Elim Ck West Pond, 148150-1, COT\CIV3D\PLANS\105



rednesday, April 24, 2019 8:48:47 AM 1.16-1050E Elim Ck West Pond, 148150-1, COT/CIV3D/PLANS/1050-Water P&



¥ é 2019 West న్ల్ రై



LEGEND


'*444*\$\$*4444. -----SS--

XXXXXXX EXISTING SANITARY SEWER PIPE TO BE REMOVED EXISTING SANITARY SEWER PIPE TO REMAIN PROPOSED SANITARY SEWER PIPE

| STR | NORTHING | EASTING |
|-----|--------------|----------------|
| A | 425,886.52 | 2,564,887.27 |
| В | 426, 156.46 | 2,564,881.31 |
| С | 426,240.09 | 2,565,294.07 |
| D | 426,246.04 | 2,565,564.00 |
| E | 426,381.71 | 2,565,561.01 |
| F | 426,635.95 | 2,565,555.39 |
| G | 426,656.34 | 2,565,572.95 |
| н | 426,896.49 | 2,565,567.65 |
| | 426,888.40 | 2,565,201.24 |
| J | 426,738.44 | 2,565,204.55 |
| 1 | 425,827.49 | 2, 564, 913.20 |
| 27 | 426, 186.99 | 2, 564, 868.87 |
| 106 | 426, 920. 53 | 2, 565, 580.97 |
| 343 | 425,843.06 | 2, 564, 929.62 |




| | THIS | | | | ELM CREEK WEST POND | | | | | |
|--|------|---------------------------------|--|------|---------------------|------------|-------|---------|--|--|
| THIC | | | | | PROJECT No. 148150 | | | | | |
| DOCUMENT IS PRELIMINARY IN NATURE AND IS | N | SANITARY SEWER OVER-ALL PLAN | | | | | | | | |
| NOT A FINAL, SIGNED AND SEALED | | | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | | A | | |
| DOCUMENT | | | UY ENGIN ST, TULSA OK | | | | | IGR.COM | | |
| REVISION BY | DATE | PLAN SCALE: | DRAWN | | | APPROVED | : | | | |
| | | 1''=60' | DESIGNED | DGD | 4/3/19 | | | | | |
| | | | SURVEY | MZV | 4/3/19 | | | | | |
| | | PROFILE SCALE: | PROJ. MGR. | DMM | 09/18 | | | | | |
| | | HORIZONTAL: | LEAD ENGR. | | | | | | | |
| | | N/A | FIELD MGR. | | | | | | | |
| | | VERTICAL | RECOMMENT | DED: | | | | | | |
| | | N/A | DESIGN MAN | AGER | | CITY ENGIN | EER | | | |
| | | | | | | DATE: | | | | |
| | | FILE: | DRAWI | NG: | | PAGE NO. | | SS10 | | |
| | | ATLAS PAGE | NO: 01 & 08 | | | SHEET NO. | 100 (| DF 123 | | |



day, April 24, 2019 1:06:08 PM 1050E Elm Ck West Pond, 148150-1, COT/CIV3D/PLANS/1050-Sa

| | _ | | | | | |
|---|---|-----|----------------------------------|------------------------|-------------------------------------|---|
| | _ | | | | | |
| | = | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| - | — | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | THIS DOCUMENT IS | | | | | |
| 5 | PRELIMINARY IN NATURE AND IS NOT A FINAL, | | | | GRAPHIC SCA | LE |
| | SIGNED AND SEALED | | : | 1 inch 20' | (HORIZ.) = ft.20' 0 | 20' 40' |
| D | DOCUMENT | I | | | | EST POND |
| | 2ENYO | | | | | . 148150 |
| | | | | | RY SEWI EET NO. | ER PLANS 1 OF 3 |
| | | | | | | OKLAHOMA S DEPARTMENT |
| г | | TE | G 6910 E. 14TH PLAN SCALE: | ST, TULSA OK | 74112 / PH: 918.4 | ERVICES, INC. 137.0282 / WWW.GUYENGR.COM |
| | REVISION BY D/ | ATE | 1"=20' | DESIGNED SURVEY | DGD 01/19 MZV 01/19 DMM 09/18 | |
| ŀ | | | PROFILE SCALE: HORIZONTAL: | | | |
| | | | N/A VERTICAL | FIELD MGR. RECOMMEN | DED: | |
| ŀ | | | N/A | DESIGN MAN | IAGER | CITY ENGINEER DATE: |
| Ì | | | FILE: ATLAS PAGE | DRAW | NG: | PAGE NO. SS11 SHEET NO. 101 OF 123 |
| _ | | | ATENO FAGE | | | |



2019 10:33:16 AM West Pond, 14815(April 24, E Elm Ck







Pres.R/W



| THIS DOCUMEN PRELIMINAI NATURE AN NOT A FIN SIGNED A SEALED DOCUME | RY IN ND IS IAL, ND | | : | (1 inch 20' | (H | IIC SCA ORIZ.) ft.20' | LE 20' | 40' | |
|---|------------------------------|------|---|--------------------------|------|-----------------------------|------------|------|------|
| | | | EL | M CRE | ΞEŀ | < WI | EST P | ON | D |
| REAL | 0. | | | PROJE | ECT | ⁻ No | . 14815 | 50 | |
| 811 | | 'n | SANITARY SEWER PLANS SHEET NO. 2 OF 3 | | | | | | |
| CA | | | | Y OF T | | | | | 1A |
| ·4L O | | | | UY ENGIN ST, TULSA OK | | | | | |
| REVISION | BY | DATE | PLAN SCALE: | DRAWN | DGD | 01/19 | APPROVED | D: | |
| | | | 1"=20' | DESIGNED | MZV | 01/19 | 1 | | |
| | | | | SURVEY | DMM | 09/18 |] | | |
| | | | PROFILE SCALE: | PROJ. MGR. | | |] | | |
| | - | | HORIZONTAL: | LEAD ENGR. | | | | | |
| | | | N/A | FIELD MGR. | | | | | |
| | | | | RECOMMENT | DED: | | | | |
| | | | N/A DESIGN MANAGER | | | | CITY ENGIN | IEER | |
| | | | DATE: | | | | | | |
| | | | FILE: DRAWING: PAGE NO. | | | | | | SS12 |
| | | | ATLAS PAGE NO: 01 & 08 SHEET NO. 102 OF 123 | | | | | | |
| | | | | | | | | | |



| (106) STA 47+23.94, 7.85' RT. EXISTING 4' I.D. MANHOLE TR = 690.70 FL = 681.76 | | |
|---|---|----------------------------|
| – | | |
| _ | | |
| STA 47+23.95, 6' LT. (| | |
| ← ← H ← CONSTRUCT 4' I.D. M TR = 690.80 FL = 681.61 (N,S) FL = 686.80 (W) | IANHOLE | |
| | RACTOR TO INSTALL WATER-TIGHT OR THIS MANHOLE. | |
| 1 | | |
| PROPOSED FLOODPLAIN WITH WEST POND | | |
| | | |
| 2017 REGULATORY FLOODPLAIN | | |
| _ | | |
| - | J | |
| THIS DOCUMENT IS | | |
| PRELIMINARY IN NATURE AND IS NOT A FINAL, ** SIGNED AND | GRAPHIC SCA (HORIZ.) | LE |
| SEALED DOCUMENT | 1 inch = ft.20' 20' 0 | 20' 40' |
| | ELM CREEK W | |
| OREOKE | PROJECT No | . 148150 |
| | SANITARY SEW SHEET NO. 3 | - |
| CALL ON IN | | S DEPARTMENT |
| | GUY ENGINEERING S 6910 E. 14TH ST, TULSA OK 74112 / PH: 918. | 437 0282 / WWW GUYENGR COM |
| REVISION BY DATE | PLAN SCALE: DRAWN DGD 01/19 1"=20' DESIGNED MZV 01/19 | APPROVED: |
| | PROFILE SCALE: PROJ. MGR. 09/18 | - |
| | HORIZONTAL: LEAD ENGR. | |
| | VERTICAL RECOMMENDED: | |
| | N/A DESIGN MANAGER | CITY ENGINEER DATE: |
| | FILE: DRAWING: | PAGE NO. SS13 |
| | ATLAS PAGE NO: 01 & 08 | SHEET NO. 103 OF 123 |



dnesday, April 24, 2019 10:46:27 AM 16-1050E Elm Ck West Pond, 148150-1, COT\CIV3D\PLANS\1050-EROSION CONTROL S




LEGEND

×××××××


TEMPORARY FIBER LOG TEMPORARY SILT FENCE




| | | | | ELM CREEK WEST POND | | | | | | | |
|--|---------------------------------|----------|----------------------------|-----------------------|--|-----|---------------|------------|-----|---------|---|
| r | тше | | | | PROJECT No. 148150 | | | | | | |
| THIS DOCUMENT IS PRELIMINARY IN NATURE AND IS | | | | EROSION CONTROL SHEET | | | | | | | |
| | NOT A FIN SIGNED A SEALEI | ND | | | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | | | |
| | DOCUME | NT | | | | | | ERVICES, I | | IGR.COM | л |
| RE | VISION | BY | DATE | PLAN SCALE: | DRAWN | DGD | 01/19 | APPROVED: | | | |
| | | | | 1''=60' | DESIGNED | MZV | 01/19 | | | | |
| | | | | | SURVEY | DMM | 09/18 | | | | |
| | | | | PROFILE SCALE: | PROJ. MGR. | | | | | | |
| | | | | HORIZONTAL: | LEAD ENGR. | | | | | | |
| | | | | N/A | FIELD MGR. | | | | | | |
| | | VERTICAL | VERTICAL RECOMMENDED: | | | | | | | | |
| | | | N/A | N/A DESIGN MANAGER | | | CITY ENGINEER | | | | |
| | | | | | | | | DATE: | | | _ |
| | | | FILE: DRAWING: PAGE NO. C2 | | | | C24 | ŧ | | | |
| | | | | ATLAS PAGE | NO: 01 & 08 | | | SHEET NO. | 104 | OF 123 | 3 |



AM 815 10:59 2019 Waat 5⁴,




Vednesdoy, April 24, 2019 11:25:03 AM Y:\16-1050E Elm Ck West Pond, 148150-1, COT\CIV3D\PLANS\1050-BlockWall P&P.dw
















| | | | ELM CREEK WEST POND | | | | | | | | | | |
|-------|-----|----------|--|-------------|------|-------|---|--|--|--|--|--|--|
| | 0 | | PROJECT No. 148150 | | | | | | | | | | |
| L ARK | 0U | 016 | BLOCK WALL DETAILS SHEET NO. 1 OF 1 | | | | | | | | | | |
| | in. | W | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | | | | | | | |
| | W. | | | | | | ERVICES, INC. 437.0282 / WWW.GUYENGR.COM | | | | | | |
| | BY | DATE | PLAN SCALE: | DRAWN | DGD | 01/19 | APPROVED: | | | | | | |
| | | | N/A | DESIGNED | MZV | 01/19 | | | | | | | |
| | | | 14/7 | SURVEY | DMM | 09/18 | | | | | | | |
| | | | PROFILE SCALE: | PROJ. MGR. | | | | | | | | | |
| | | | HORIZONTAL: | LEAD ENGR. | | | | | | | | | |
| | | | N/A | FIELD MGR. | | | | | | | | | |
| | | | VERTICAL | RECOMMEND | DED: | | | | | | | | |
| | | | N/A | DESIGN MAN | AGER | | CITY ENGINEER | | | | | | |
| | | | | | | | DATE: | | | | | | |
| | | | FILE: | DRAWI | NG: | | PAGE NO. C27 | | | | | | |
| | | | ATLAS PAGE | NO: 01 & 08 | | | SHEET NO. 107 OF 123 | | | | | | |




Wednesday, April 24, 2019 11:53:36 AM v:\16-1050E Eim Ck West Pond, 148150-1, COT\CIV3D\PLANS\1050-PAVEMENT MARKING AND SIGNING PLAN.





| | | | | ELM CREEK WEST POND | | | | | |
|---|--------------------------------------|-------|------|--------------------------------------|--|----------------------|---------------|--------------|--|
| I | THIS | | | | PROJE | ECT | ۲ No | . 148150 | |
| | DOCUMEN PRELIMINA NATURE AI | N | | PAVEMENT MARKING AND SIGNING PLAN | | | | | |
| | NOT A FINAL, SIGNED AND SEALED | | | | CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT | | | | |
| | DOCUME | NT | | | GUY ENGINEERING SERVICES, INC. 6910 E. 14TH ST, TULSA OK 74112 / PH: 918.437.0282 / WWW.GUYENGR.COM | | | | |
| R | EVISION | BY | DATE | PLAN SCALE: | DRAWN | DGD | 01/19 | APPROVED: | |
| | | | | 1''=60' | DESIGNED | MZV | 01/19 | | |
| | | | | | SURVEY | DMM | 09/18 | | |
| | | | | PROFILE SCALE: | PROJ. MGR. | | | | |
| | | | | HORIZONTAL: | LEAD ENGR. | | | | |
| | | | | N/A | FIELD MGR. | | | | |
| | | | | VERTICAL | RECOMMEND | DED: | | | |
| | | | N/A | DESIGN MANAGER | | | CITY ENGINEER | | |
| | | | | | | | | DATE: | |
| | | FILE: | | | DRAWING: PAGE NO. C | | | PAGE NO. C28 | |
| | | | | ATLAS PAGE | NO: 01 & 08 | SHEET NO. 108 OF 123 | | | |



NOTES:

1. Park USA's proprietary TrashTrooper unit uses a floatable collection bar screen to capture unwanted floatable pollutants from the 10'x10' RCB before outflow into the pond. Separated effluent exits the TrashTrooper and enters the wet pond, leaving debris behind inside the TrashTrooper.

CAPACITY NOTES:

- 2. The TrashTrooper was sized based on the existing 108" pipe capacity of 858 cfs per September 2018 correspondence with Swift Water Resources Engineering.
- 3. The TrashTrooper's rim elevation is 689.50, approximately 0.50 ft above the peak 100-year WSE of 689.0 in the downstream pond. Because of the downstream WSE in the pond, stormwater will overflow the rim of the TrashTrooper during storms larger than the 100-year event and enter Owasso Avenue, which has a pavement elevation of approximately 687.3 adjacent to the TrashTrooper.
- 4. The grate capacity for a range of clogging percentages is shown in Table 1 and Figure 1. The grate's capacity is defined as the flow producing an HGL at ground inside the TrashTrooper. The TrashTrooper is not expected to limit the existing system capacity below 858 cfs until it becomes approximately 60% clogged. At this point, further clogging of the grate will gradually reduce flow capacity through the TrashTrooper and increase the risk of flooding in the upstream storm drain system.

MAINTENANCE NOTES:

- 5. A detailed TrashTrooper operations and maintenance plan is on SHT TS3. This system will be maintained by City staff. The manufacturer recommends a visual inspection 2-3 days after major storm events (over 1" of rainfall) in addition to regular monthly inspections, and recommends removal of trash and sediment after it reaches 25% of the box diameter.
- 6. The TrashTrooper is located adjacent to the Owasso Ave curb. Per correspondence between Guy Engineering and the City of Tulsa, this location allows for convenient access by the City's vacuum truck hose for cleaning out sediment and trash. If needed, City staff can enter the TrashTrooper through the hatchway and stand on the horizontal walkway and grate to remove larger debris.

Table 1. TrachTrachan Conneity Coloulations

| Table 1: TrashTrooper Capacity Calculations | | | | | | | | |
|---|-------------------------|----------|-----------|--------------|----------|-----------|----------------|--|
| Grate | Front Orifice Top Orifi | | | | | | TrashTrooper | |
| Clogging | Area (sq ft) | Centroid | Head (ft) | Area (sq ft) | Centroid | Head (ft) | Capacity (cfs) | |
| 0% | 138.9 | 679.5 | 10.0 | 71.5 | 684.4 | 5.1 | 858 | |
| 10% | 125.1 | 680.0 | 9.5 | 64.4 | 684.4 | 5.1 | 858 | |
| 20% | 111.2 | 680.5 | 9.0 | 57.2 | 684.4 | 5.1 | 858 | |
| 30% | 97.3 | 681.0 | 8.5 | 50.1 | 684.4 | 5.1 | 858 | |
| 40% | 83.4 | 681.5 | 8.0 | 42.9 | 684.4 | 5.1 | 858 | |
| 50% | 69.5 | 682.0 | 7.5 | 35.8 | 684.4 | 5.1 | 858 | |
| 60% | 55.6 | 682.5 | 7.0 | 28.6 | 684.4 | 5.1 | 858 | |
| 70% | 41.7 | 683.0 | 6.5 | 21.5 | 684.4 | 5.1 | 745 | |
| 80% | 27.8 | 683.5 | 6.0 | 14.3 | 684.4 | 5.1 | 483 | |
| 90% | 13.9 | 684.0 | 5.5 | 7.2 | 684.4 | 5.1 | 235 | |
| 100% | 0.0 | 684.5 | 5.0 | 0.0 | 684.4 | 5.1 | 0 | |




Figure 1: TrashTrooper Capacity vs. Clogging

| | ELM CREEK WEST POND | | | | | | | |
|--|---------------------|--------------------------|------|----------|-----------------------------|---------|------|-----|
| | | PROJE | ECT | ۲No. | 14815 | 0 | | |
| | - | FROOPE RAULIC I MA | MΡ | | ANALYSI | | | - , |
| NOT FOR CONSTRUCTION THIS DOCUMENT IS RELEASED FOR THE PURPOSE OF INTERIM REVIEW UNDER THE | - I | TY OF T | | , | | | A | |
| AUTHORITY OF TRICIA H. HATLEY P.E. OK NO: 20105 ON DATE: 04/12/2019 IT IS NOT TO BE USED FOR CONSTRUCTION BIDDING OR PERMIT PURPOSES. | . 7633 | FREES | | | DLS, INC. 74133 / PH:539 | -444-86 | 77 | |
| REVISION BY DATE | PLAN SCALE: | DRAWN | ккн | 04/01/19 | APPROVED: | | | |
| | 1 | DESIGNED | КНН | 04/01/19 | | | | |
| | | SURVEY | | | | | | |
| | PROFILE SCALE | PROJ. MGR. | | | | | | |
| | HORIZONTAL: | LEAD ENGR. | | | | | | |
| | | FIELD MGR. | | | | | | |
| | VERTICAL | RECOMMENT | JED: | | | | | |
| | | DESIGN MAN | AGER | | CITY ENGINE | ER | | |
| | | | | | DATE: | | | |
| | FILE: | DRAWI | NG: | | PAGE NO. | TS | 52 | |
| | ATLAS PAGE | NO: 01 & 08 | _ | _ | SHEET NO. | 110 | OF 1 | 23 |
| | | | | | | | | |





TrashTrooper[®] Monitoring & Maintenance Plan

1.0 Maintenance

A preventative maintenance cleanout schedule is the most valuable tool for maintaining the proper operation of ParkUSA TrashTrooper[®]. Maintenance costs will be greatly reduced if a good housekeeping plan for the property is developed i.e., trash pickup, lawn maintenance, dumpster control, etc.

ParkUSA TrashTrooper has no moving parts. ParkUSA recommends inspection after any major storm event and monthly inspections. Complete a TrashTrooper Maintenance Report after each inspection and maintain for inspections and water quality permit renewals. Record and retain manifests of any vacuum truck pump cleanings.

- A. Annual Maintenance
- 1. ParkUSA, manufacturer of TrashTrooper, recommends observation and maintenance be completed during non-flow (dry weather) conditions 5-7 days after the most recent
- 2. Pull all manhole covers & open all hatchways. Observe for trash and debris and remove It is particularly important to remove large solids like wood or trash bags as well as maintain cleared grating. Failure to remove trash and debris could be problematic to entire stormwater system
- ParkUSA TrashTrooper units are designed based on the inlet/outlet pipe type and size. ParkUSA recommends removal and cleaning of unit when measurable pollutants reach 25% of pipe diameter. For example: If 48" HDPE pipe is utilized on the inlet of the er cleaning should occur when measurable solids reach 12".
- 4. Typically, a vacuum truck may be used to remove sediment and other floatables from Typically, a vacuum tock may be used to reintove sequinent and other hotables into the notables into the unit. In most geographic areas the sediment can be disposed in a sanitary landfill once dewatered. Check with your provider regarding proper disposal. Pollutants are not allowed to be discharged back into the sanitary or storm sewer systems.
- 5. After cleaning via vacuum truck, replace manhole covers
- 6. After cleanout is accomplished, obtain a copy of the service truck manifest. Update the TrashTrooper® Monitoring/Maintenance Report (ST Form 3) and attach a copy of the manifest to the report.

TrashTrooper Operation and Maintenance

TrashTrooper Operation and Maintenance

B. Quarterly Inspections

6. Close access grate and secure.

and fires

DESIGNED.

C. Safety and Environmental Considerations

Monthly maintenance is advisable in heavy weather months and after any major storm event, using 1 inch in 24 hours as a minimum guideline depending on non-structural controls of the site.

During normal climate conditions, observation and maintenance should occur when non-flow (dry weather conditions) have existed, 2 – 3 days after the most recent rain.

Remove the control manhole basin cover or hatchway and observe for excessive trash and debris. Clean out if required. Replace or bolt down access covers. This is the most important maintenance requirement. Failure to remove trash and debris from the

At least quarterly or more frequently if there is a large amount of floatable debris washing onto the system, check the grating for blockage.

5. ParkUSA TrashTroooper units are designed based on the inlet/outlet pipe type and size. ParkUSA recommends removal and cleaning of unit when measurable pollutants reach 25% of pipe diameter. For example: If 48" HDPE pipe is utilized on the inlet of the Floatable Collection Screen cleaning should occur when measurable solids reach 12".

1. All normal safety precautions should be taken with this equipment to prevent accidents

2. Care should be taken to keep the area around the interceptor clean to prevent

The atmosphere inside the Park Environmental Equipment TrashTrooper^a may be a confined space and may be hazardous. Verify and follow OSHA confined space entry

4. SAFETY AND ENVIRONMENTAL PROTECTION ARE THE RESPONSIBILITY OF THE USER. PARK ENVIRONMENTAL LTD. ASSUMES NO LIABILITY FOR MISUSE OF

THIS SEPARATOR OR FOR USE OUTSIDE THE PARAMETERS FOR WHICH IT IS

Page 2 of 4

requirements. Entry is not recommended without proper equipment.

grating could cause a blockage or be problematic to the entire system

(ST Form 3)

TrashTrooper[®] Interceptor Monitoring / Maintenance Report

| Year : | |
|-----------------------|--|
| Company Name : | |
| Address : | |
| City/State/Zip: | |
| Contact Phone : | |
| TrashTrooper® Model : | |
| | |

Quarterly Record Keeping

| Maintenance Activity | March | June | September | De | | | | | |
|----------------------------|-------|------|-----------|----|--|--|--|--|--|
| Non Structural Controls | | | | | | | | | |
| Interceptor Debris Cleaned | | | | | | | | | |
| Hose off Inside Walls | | | | | | | | | |
| Debris Screens Cleaned | | | | | | | | | |
| Mowing of Trashtrooper | | | | | | | | | |
| Structural Controls | | | | 1 | | | | | |
| Solids Depth ** | | | | | | | | | |
| Pumped Out | | | | | | | | | |
| Inspections | | | 1 | | | | | | |
| Quarterly | | | | | | | | | |
| Annually | | | | | | | | | |

I certify that I supervised or performed TrashTrooper® monitoring per requirements and manufacturer's recommended monitoring and maintenance procedures on the dates listed above.

| Signed: | |
|---------|-------------------------------|
| | Owner or Owner Representative |

Date Submitted:

Note: Keep records along with clean out manifests for proof of performance of maintenance. Use records to show permitting officials that your TrashTrooper is operational and meets the intent of the original property BMP for stormwater design.

TrashTrooper Operation and Maintenance

(ST Form 5)

STORM WATER QUALITY MANAGEMENT PLAN (SWQMP)

For: Annual Review of Monthly TrashTrooper® Monitoring, Maintenance and Operation Design Engineer Certification Form

I, _____, certify that I have reviewed the StormTrooper® Storm Water Interceptor Quarterly Monitoring and Maintenance Reports for the facility listed below.

{PE Stamp Here}

Page 4 of 4

Page 1 of 4

Design Engineer's Name

Signature

Date

Engineer's Information Company:

Address

City, State, Zip:

TrashTrooper Operation and Maintenance


Facility Information


| City. | |
|-----------------|--|
| Facility No: | |
| Company: | |
| Owner Name: | |
| Address: | |
| City/State/Zip: | |
| Phone: | |
| Email: | |
| | |

ecember


Page 3 of 4


| | | | | ELM CREEK WEST POND | | | | | |
|---|--|-------|-----------------------------|--|-----------------------|-----------------------|--------------|--------------------------|--|
| | | | | | PROJE | EC | T No. | 148150 | |
| | | TRA | | | | ERATION AND E PLAN | | | |
| | NOT FOR CONSTRUCTION THIS DOCUMENT IS RELEASED FOR THE PURPOSE OF INTERIM REVIEW UNDER THE | | | | | | | OKLAHOMA S DEPARTMENT | |
| | AUTHORITY OF TRICIA H OK NO: 20105 ON IT IS NOT TO BE USEI BIDDING OR PERMIT P | DATE: | 03/28/2019 CONSTRUCTION. | FREESE & NICHOLS, INC. 7633 E 63RD PL SUITE 300 TULSA, OK 74133 / PH:539-444-8677 | | | | | |
| | REVISION | BY | DATE | PLAN SCALE: | DRAWN | ккн | 04/01/19 | APPROVED: | |
| l | | | | | DESIGNED | кнн | 04/01/19 | | |
| l | | | | | SURVEY | | | | |
| ł | | | | PROFILE SCALE: | PROJ. MGR. | | | | |
| ł | | | | HORIZONTAL: | LEAD ENGR. | | | | |
| ł | | | | | FIELD MGR. | | | | |
| ł | | | | VERTICAL | VERTICAL RECOMMENDED: | | | | |
| l | | | | | DESIGN MAN | AGEF | 2 | CITY ENGINEER | |
| I | | | | | | | | DATE: | |
| | | | FILE: | DRAWI | NG: | | PAGE NO. TS3 | | |
| | | | | ATLAS PAGE | NO: 01 & 08 | | | SHEET NO. 111 OF 123 | |







Vednesday. April 24. 2019 11:06:02 AM /fL 16-1050E Elm Ck West Pond, 148150-1, COTFLCIV3DFLPLANSFL 1050-Cross Sectio










| 40 | 45 | 50 | 55 | 60 | 65 | 70 |
|-------|--------------------------|----|----------|-----------|----|-----|
| | | | | | | 710 |
| | | | | | | 705 |
| | | | = | | | 700 |
| | | | 20 |)+75.9 | 5 | 695 |
| | | | | | | 690 |
| J | | | <u> </u> | | | 700 |
| | | | | | | 695 |
| | | | 20 |)+00.00 | 0 | 690 |
| | | | | | | 685 |
| | | | | | | 710 |
| | | | | | | 705 |
| | | | | | | 700 |
| | | | 10 | | | 695 |
| | | | 15 |)+50.0(| J | 690 |
| | | | | | | 685 |
| | | | | | | 700 |
| | | | 10 |)+00.00 | | 695 |
| | | | 15 | | | 690 |
| 40 | 45 | 50 | 55 | 60 | 65 | 685 |








| 40 | 45 | 50 | 55 | 60 | 65 | 70 |
|----|-------|---------|---------|------------|------------------------|------------------------------|
| | | | | | | |
| | | | | | | 700 |
| | | | | | | |
| | | | | | | |
| | | | | | | 695 |
| | | | | | | |
| | | | | | | 690 |
| | | | 20 | 6+00.00 | ۱ | |
| | | | 30 | J 1 00.00 | , | 685 |
| | | | | | | |
| | | | | | | 680 |
| | | | | | | |
| | | | | | | 700 |
| | | | | | | |
| | | | | | | |
| | | | | + | | 695 |
| | | | | | | |
| | | | | | | 690 |
| | | | 20 | 5+50.00 | <u> </u> | |
| | | | 5 | | , | 685 |
| | | | | | | |
| | | | | | | 680 |
| | | | | | | |
| | | | | | | 700 |
| | | | | | | |
| | | | | | | 005 |
| | | | | | | 695 |
| | | | | | | |
| | + | | | | | 690 |
| | | | 20 | 5+00.00 | \mathbf{v}^{\perp} – | |
| | | | 5 | J - 00.00 | , | 685 |
| | | | | | | |
| | | | | | | 680 |
| | | | | | | |
| | | | | | | 690 |
| | | | | | | 0301 |
| | | _ | | | | |
| | | | | | | 685 |
| | | | 34 | 4+35.00 |) | |
| | | | | | | 680 |
| | | | | | | |
| | | | | | | 675 |
| 40 | 45 | 50 | 55 | 60 | 65 | 70 |
| 5 | | ROSS SI | ECTION | S - NORF | OLK 8 | 5TH PLACE |
| | 10 ST | A. 34+5 | 0 TO ST | ГА. 36+00 | | PAGE NO. SHEET NO. 119 OF |
| | | | | | | ÷. |




5 0 VERTICAL SCALE IN FEET

| | | 55 | 60 | 65 | · | 70 |
|----------|------------|----|------------------|-------|---|---------------------------|
| | | | | | | |
| | | | | | | 700 |
| | | | | | | |
| | | | | | | 695 |
| | | | | | | |
| | | | | | | 690 |
| | | | +- | | | |
| | | | 38+00 | 00.0 | | 685 |
| | | | | | | 000 |
| | | | | | | 690 |
| | | | +- | | | 680 |
| | | | | | | 700 |
| | | | | | | 700 |
| | | | | | | - |
| | | | +- | | | 695 |
| <u> </u> | <u>+</u> + | - | | | | |
| | | | +- | | | 690 |
| | | | 37+6 | 5.00 | | |
| | | | | | | 685 |
| | | | | | | |
| | | | +- | | | 680 |
| | | | | | | |
| | | | | | | 695 |
| | + | _ | | | | |
| | | | +- | | | 690 |
| | | | | | | |
| | | | +- | | | 685 |
| | | | 37+3 | 158 | | |
| | | | | 1.00 | | 680 |
| | | | | | | |
| | | | +- | | | 675 |
| | | | | | | |
| | | | <u> </u> | | | 695 |
| | | | | | | |
| | | | — — - | | | 690/ |
| | | | 36+50 | 0 0 0 | | |
| | | | | | | 685 |
| | | | | | | |
| 10 | | | | | | 680 |
| .0 4 | 5 50 | | 60 | 65 | | ⁷⁰ 5TH PLAC |



| 40 | 45 | 50 | 55 | 60 | 65 | 70 |
|------------|-----------|---------|--------|------------|-------|--------------------------------|
| | | | | | | |
| | | | | | | 695 |
| | | | | | | |
| | | | | | | 690 |
| | | | | | | |
| Г | | | 42 | 2+20.0 | 0 | 685 |
| ICI DES 2D | | | | | | |
| | | | | | | 680 |
| | | | | | | |
| | | | | | | 690 |
| | | | | | | |
| | | | 4 | 1+85.10 |) | 685 |
| | | | | | | |
| | | | | | | 680 |
| | | | | | | |
| | | | | | | 695 |
| | | | | | - + - | · |
| | | | | | | 690 |
| | | | | | - | |
| ICI DES 2B | | | 4 | 1+50.00 | J | 685 |
| | | | | | | |
| | | | | | | 680 |
| | | | | | | |
| | | | | | | 6 <u>95</u> |
| | | | | | | |
| | | | | | | 690 |
| | | | | | - | |
| | | | 4 | 1+00.00 | J | 685 |
| | | | | | | |
| | | | | | | 680 |
| | | | | | | |
| | | | | | | 6 <u>95</u> |
| | | _ + _ | | | | |
| | | | | | | 690 |
| | | | | | | |
| | | | 4(| 0+50.0 | 0 | 685 |
| | | | | | | |
| | | | | | | 680 |
| 40 | 45 | 50 | 55 | 60 | 65 | 70 |
| 5 10 | CF | ROSS SI | ECTION | IS - S. OV | VASSC | |
| 5 10 | , St | A. 40+5 | 0 TO S | TA. 42+50 |) | PAGE NO. 2 SHEET NO. 121 OF |



| 40 49 | 5 50 5 | 55 60 |) 6 | 65 | 70 |
|------------------------------------|--|-----------|--------|-------------|---------------------------|
| | | | | | |
| | | | | | 690 |
| I DES 4 (STD) | | 45+1 | 0.00 | | 685 |
| DE34 (31D) | | | | | |
| | | | | | 680 |
| | | | | | |
| | | | | | |
| | | | | | 685 |
| | | 44+5 | 00.00 | | 000 |
| | | | | | 680 |
| | | | | | 675 |
| | | | | | |
| | N = 426,616.62 | | | | 690 |
| (14 | E = 2,565,585.83 STA 44+20.00, 6' RT. CONSTRUCT 6' I.D. M/ | ANHOLE | | | 685 |
| DES 2 (2B) | TR = 686.44, FL (N) = 682.14 (36") FL (S) = 683.14 (24") | 44+2 | 20.00 | | |
| | FL (E,W) = 683.64 (18") | | | | 680 |
| | | | | | 675 |
| | | | | | |
| | | | | | 690 |
| | | | | | 685 |
| | | 43+6 | 5 21 | | |
| | | 4010 | JJ.Z1 | | 680 |
| | | | | | 675 |
| | | | | | |
| | | | | | 695 |
| | | | | - - - | 690 |
| 5 48 | | 10.0 | | | |
|), 6' RT. 5' I.D. MANHO | LE | 43+0 | 0.00 | | 685 |
| 1.76 (36") 26 (18") 26 (18") | | | | | 690 |
| 40 4 | 5 50 5 | 55 60 |) 6 | 65 | 680 70 |
| 10 | CROSS SECT | TIONS - S | 6. OWA | sso į | |
| 10 | STA. 43+00 T | O STA. 4 | 5+00 | | PAGE NO. SHEET NO. 122 |



| 40 | 45 | 50 | 55 | 60 | 65 | 70 |
|--------------------------------|---------------------|----|------------|---------------------------|------------|-----|
| | | | | | | |
| | | | | | | 700 |
| | | | | | | 695 |
| | | | | | | |
| | | | Δ- | 7+18.5 | 2 | |
| | | | | 10.0 | · ∠ | 685 |
| | + | | | + | | 680 |
| | | | | | | 695 |
| | | | · = | | | |
| | | | | | | 690 |
| 00, 13' RT. T STD CICI , | DES 4B | | 46 | 6+67.0 | 00 | 685 |
| (24") | | | | | | |
| | | | | | | 680 |
| | | | | | | 700 |
| | | | | | | 695 |
| | | | | | | |
| | | | | + | | 690 |
| | | | 46 | 6+00.C |)0 | 685 |
| | | | | | | 680 |
| | | | | | | |
| | | | | | | 695 |
| | | | | | | 690 |
| | | | | | | 685 |
| | | | 4٢ | 5+50.0 |)() | |
| | | | <u></u> т. | | | 680 |
| | | | | | | 675 |
| 40 | 45 | | | ⁶⁰ S - S. O | 65 | 70 |